


AIR CONDITIONERS LINEUP

SPLIT
MULTI SPLIT
VRF
VENTILATION
AIR TO WATER



PRODUCT CATALOGUE 2016



FUJITSU GENERAL LIMITED



Creation of Comfort

Fujitsu General creates high-quality and environmentally-friendly products that provide good comfort in accordance with our basic policy to a “create comfortable environment” by utilizing the air conditioning technology and creativity we have fostered over many years.

004 MISSIONS

006 Green Aspect for Refrigerant
007 Our Pioneering Efforts Make Green Future
008 Energy Efficiency Classifications

010 ABOUT US

012 Our History
014 Global Network
016 High Quality Development & Production Facilities
018 Global Business Activities
020 Project Reference

022 CORE TECHNOLOGY

024 High Efficiency
026 Energy Saving Control
028 Comfort Performance
030 Easy-to-use Control
032 Smart Design

034 SUPPORT

036 AIRSTAGE™ Support
038 Design Simulator
040 WATERSTAGE™ Support Tool
042 Quick Service and Maintenance

044 PRODUCT CATEGORY

046 2015 Fujitsu General Solutions
050 Split
090 Multi Split
114 Optional Parts For Split & Multi Split
128 VRF
200 Ventilation
208 Optional Parts For VRF
214 Air to Water



MISSIONS

We always keep the future in mind to ensure that the air conditioning technology that makes people comfortable is also environmentally friendly.

006 Green Aspect for Refrigerant

007 Our Pioneering Efforts Make Green Future

008 Energy Efficiency Classifications

Green Aspect for Refrigerant

EU strengthen F-Gas Regulation introduced 2014.
We are active on that scenario for future.

Phase down scenario of HFC


EU strengthen F-gas Regulation introduced 2014.

New EU F-gas Regulation aims prevention of emissions and reduction the use of higher GWP F-gases.

Key elements

- Phase down approach
- Quota allocation
- Restrictions on the placing on the market
- Traceability of HFC contained in pre-charged equipment


Fujitsu General work on the reduction of HFC with innovative efforts



Road to 2025

From 2025, single split A/C containing less than 3 kg of F-gas (GWP_{eq} ≥ 750) will be banned.

As our investigation and evaluation, Fujitsu General think R32 is best balanced alternative gases.
We will gradually adopt R32 for our product range.



Our Pioneering Efforts Make Green Future

Approach to New Energy Efficiency Standard

Fujitsu General following The EU Climate Action Plan 20/20/20 by 2020

20% LESS
Primary Energy Use

Fujitsu General products with high efficiency and therefore low electricity input and low primary energy usage

20% LESS
CO₂ Emissions

Fujitsu General products sharply following the F-gas regulation 842/2006/EC

20% SHARE
of Renewable Energy

Fujitsu General promoting air sourced heat pumps as renewable energy source heating systems


Pursuit of Energy Saving Taking Actual Operation into Consideration

The heat load varies greatly depending on the time and season. However, the operation ratio EER or COP up to now has been calculated based on the rated value and the annual operating hours per outdoor temperatures was not taken into consideration. For this reason, SEER and SCOP* have been made the standard in terms of actual operating hours throughout the year.

*: SEER = Seasonal Energy Efficiency Ratio
SCOP = Seasonal Coefficient of Performance

Fujitsu General provides air conditioners with higher SEER and SCOP.

*SEER and SCOP are indexes that express the annual energy efficiency calculated based on the regulations of (EU) 626/2011




MISSIONS

Energy Efficiency Classifications

For Air Conditioners


New Energy Labelling Requirement 626 / 2011 / EU :
Our models have reached the "Class A" ranking, the highest energy efficiency level that is now shown on energy labels in Europe.

Current Energy Label



- Performance notation based on multiple points calculations that better matches the actual operation
- Energy labelling revision
- Raising of the "Class A" level

- Three climate zone for heating (Average zone: mandatory) (Warmer and colder zone are optional)
- Seasonal efficiency
- Sound power level



For Air to Water

New Energy Labelling Requirement 811 / 2013 / EU :
Our models have reached the "Class A" ranking, the highest energy efficiency level that is now shown on energy labels in Europe.

For Air to Water

Seasonal heating efficiency (Except low temp HP)	Seasonal heating efficiency (Low temp HP)
A+++ $\eta_{sx} \geq 150$	$\eta_{sx} \geq 175$
A++ $125 \leq \eta_{sx} < 150$	$150 \leq \eta_{sx} < 175$
A+ $98 \leq \eta_{sx} < 125$	$123 \leq \eta_{sx} < 150$
A $90 \leq \eta_{sx} < 98$	$115 \leq \eta_{sx} < 123$
B $82 \leq \eta_{sx} < 90$	$107 \leq \eta_{sx} < 115$
C $75 \leq \eta_{sx} < 82$	$100 \leq \eta_{sx} < 107$
D $36 \leq \eta_{sx} < 75$	$61 \leq \eta_{sx} < 100$
E $34 \leq \eta_{sx} < 36$	$59 \leq \eta_{sx} < 61$
F $30 \leq \eta_{sx} < 34$	$55 \leq \eta_{sx} < 59$
G $\eta_{sx} < 30$	$\eta_{sx} < 55$

From 26 September 2015, Ecodesign Requirements will apply to space heaters and combination heaters(including heat pumps)
All these products have to meet the requirements for energy efficiency and sound power level. A printed energy label and product fiche must be provided for all products.
There are three type of labels for space heaters of low-temperature, space heaters of high-temperature and combination heaters.

EER (Cooling mode)	COP (Heating mode)
A $3.20 < EER$	$3.60 < COP$
B $3.20 \geq EER > 3.00$	$3.60 \geq COP > 3.40$
C $3.00 \geq EER > 2.80$	$3.40 \geq COP > 3.20$
D $2.80 \geq EER > 2.60$	$3.20 \geq COP > 2.80$
E $2.60 \geq EER > 2.40$	$2.80 \geq COP > 2.60$
F $2.40 \geq EER > 2.20$	$2.60 \geq COP > 2.40$
G $2.20 \geq EER$	$2.40 \geq COP$


Gradual ranking regulation up to A+++ (2013 ~ 2019)

- 2013~: A, B, C, D, E, F, G
- 2015~: A+, A, B, C, D, E, F
- 2017~: A++, A+, A, B, C, D, E
- 2019~: A+++, A++, A+, A, B, C, D


* Enforcement on January 1, 2013 Air conditioners below 12 kW

SEER (Cooling mode)	SCOP (Heating mode)
A+++ $SEER \geq 8.50$	$SCOP \geq 5.10$
A++ $6.10 \leq SEER < 8.50$	$4.60 \leq SCOP < 5.10$
A+ $5.60 \leq SEER < 6.10$	$4.00 \leq SCOP < 4.60$
A $5.10 \leq SEER < 5.60$	$3.40 \leq SCOP < 4.00$
B $4.60 \leq SEER < 5.10$	$3.10 \leq SCOP < 3.40$
C $4.10 \leq SEER < 4.60$	$2.80 \leq SCOP < 3.10$
D $3.60 \leq SEER < 4.10$	$2.50 \leq SCOP < 2.80$
E $3.10 \leq SEER < 3.60$	$2.20 \leq SCOP < 2.50$
F $2.60 \leq SEER < 3.10$	$1.90 \leq SCOP < 2.20$
G $SEER < 2.60$	$SCOP < 1.90$


Current Energy Labelling Points




New Energy Labelling Points




2015 Space heaters for high-temperature




2019 Space heaters for high-temperature




Space heaters for low-temperature




Combination heaters



Space heaters for low-temperature



Combination heaters





ABOUT US

Since we began our air conditioning business in 1971, our products have been popular around the world and we continue to improve them.

- 012 Our History
- 014 Global Network
- 016 High Quality Development & Production Facilities
- 018 Global Business Activities
- 020 Project Reference

Our History

1960
Air conditioning business starts.
Japan-domestic business starts.

1971
Air conditioner exports to Middle East.

Overseas Air Conditioning
Business since

1971



1977
"Super Power, Super Quiet" series

1982
Window type 3 Super series
AL/AX series

1985
Large wall mounted and multi air
conditioner introduced.

1991
Air conditioner with the world's
first lambda heat exchanger



1995
Air conditioner with the world's
first power diffuser



2001 AIRSTAGE™ series is
released. VRF air conditioners for
large-sized buildings.

AIRSTAGE
Since 2001

2006 VRF Heat Pump
type Max. 42 HP

AIRSTAGE V

2009
VRF Heat Pump type Max. 48 HP

AIRSTAGE V-II



2012 VRF Heat Recovery type
Max. 48 HP

AIRSTAGE VR-II



2014-2015
VRF Heat Pump type Max. 54 HP

AIRSTAGE V-III



2016
New Small VRF series

AIRSTAGE J-III



2004 Small VRF series

AIRSTAGE J



2014 The small VRF series is
small & light weight outdoor unit.

AIRSTAGE J-IIS

2011 Small VRF series

AIRSTAGE J-II

2011
Hi-spec Design model




2014
Air to Water system
Monobloc type: Compact series

WATERSTAGE



2015-2016
New Wall Mounted &
Cassette/Duct models



2015-2016
New Air to Water system

WATERSTAGE



1936 Established
as Yaou Shouten Ltd.

~1999

2000-2010

2011-2015

2016 TOPICS

Manufacturing Company Establishment

1955

Headquarters in Kawasaki

1964
Electronic components factory in
Ichinoseki

1977
Air conditioner manufacturing
company in Hamamatsu (now
Hamamatsu business office.)

1991
Air conditioner manufacturing
company in Thailand.

1994
Air conditioner manufacturing
company in Shanghai, China.

1998
Air conditioner motor
manufacturing company in
Thailand.

2006
VRF air conditioner manufacturer,
sale, and service company in
China.

2007
Air conditioner technology
building completed on Main
Office group. Air conditioner R & D
Center in Kawasaki

2009
Operation of compressor factory
begins in Thailand.

2012
Joint venture in Thailand to
manufacture compressors



2016
Commercial use air conditioner
R & D Center in Thailand

Sales Company Establishment

1976
North America sales company

1977
Europe sales company (UK)

1978
Australia sales company
Europe sales company (Germany)

1980
Brazil sales company

1997
Asia sales company (Singapore)

1998
Middle East sales company (UAE)
New Zealand sales company

2000
Air conditioner
manufacturing and sale
technical partnership in India


2002
Taiwan sales company

2006
China sales company

2013
Moscow representative office

Global Network

Fujitsu General's air conditioning business has acquired a major share of the overseas market. We have many production and sales facilities overseas, and we continue to develop and sell products that are accepted around the world by their "easy-to-use and environmentally-friendly technology".



Fujitsu General (Shanghai) Co., Ltd.



F.G.L.S. Electric Co., Ltd.



Fujitsu General Central Air-conditioner (Wuxi) Co., Ltd.



FGA (Thailand) Co., Ltd.



Fujitsu General (Thailand) Co., Ltd.
Fujitsu General Engineering (Thailand) Co., Ltd.



TCFG Compressor (Thailand) Co., Ltd.

JAPAN Head Office
R & D Center and 60 m Height Difference
Testing Tower



11 Overseas Sales Companies &
6 Overseas Manufacturing Companies

● Head Office
■ Sales Companies
■ Manufacturing Companies

High Quality Development & Production Facilities

Advanced Research Facility and Equipment

Performance Testing



Air flow testing

Calorimeter testing

Sound testing


Reliability Testing



Severe environmental testing

Water shower testing

Transportation & Handling




Compressibility testing



Vibration testing

Testing Laboratory

Fujitsu General EMC Laboratory Limited



60 m Height Difference Testing Tower

Objective is to confirm oil circulation of compressor for reliability



Acquisition of ISO 9001 and ISO 14001



High Product Quality Assurance


All Fujitsu General factories have acquired ISO 9001, and have built a quality control system common around the world. High quality products are offered to all over the world based on stringent quality inspections.

Receiving inspection

Parts procurement requires a supplier's test report. European regulation RoHS inspection is also performed by special test department in-house. Total number inspection is performed especially on main parts to remove defectives.

Stringent product quality inspection

Stringent quality inspection is carried out at all production processes. High quality is maintained by stringent checks by inspectors and repetitive inspection.




Global Business Activities

We are engaging in advertising, human resource development, CS activities, and social contribution activities worldwide. These activities have been recognized throughout different regions by the awards we have been honored with.

America



HVAC trade show in Brazil



Billboard



Distributor meeting



Call center



"Dealer Design Awards" of "the NEWS"



Gold Award (Category: HVAC & PLUMBING) in Reader's Choice Awards



TOP OF MIND 2016" First prize in "MARCA DE EQUIPAMENTODE AR-CONDICIONADO" category of "CLIMATIZACAO" division

Middle East



Distributor meeting



Technical seminar



Training for dealers

Europe



HVAC trade show in Europe countries



Presentation & training

International authoritative design awards



The iF Product Design Award is given each year by "iF International Forum Design GmbH" for industrial products from around the world.



reddot design award winner 2012

The product design competition has existed since 1955. Its award, the "red dot", is an internationally recognised quality seal.

Oceania



HVAC trade show in Australia



Charity (Christchurch)



Service & Maintenance



Coolworld Industry Awards "Most Efficient Air Conditioner"



Canstar Blue Most Satisfied Customers Award

Asia



Distributor meeting



Presentation for sales companies



SE training



Call center



China State Construction Engineering Luban Prize



The Good Design Award is sponsored by the Japan Institute of Design Promotion and is awarded once a year for an item of excellent design.

Project Reference

The VRF is popular because of its high quality, energy saving, and easy installation, and so has been installed in a wide range of building types including high-rise office buildings, stores, hotels, public facilities, schools, and hospitals.



University-Chemistry Faculty in Europe

Fujitsu General's VRF has been installed in
over 50 countries worldwide.



Heritage Office in Europe




Office in Europe



Hotel in USA



Residential in Middle East



Office in Europe



Residential in Europe



Financial Business Center in China



Research Center in China



Office & Shopping Center in Asia



Catholic College in Oceania



CORE TECHNOLOGY

Our advanced technology is providing comfort in a wide variety of situations from residential applications to commercial use.

- 024 High Efficiency
- 026 Energy Saving Control
- 028 Comfort Performance
- 030 Easy-to-use Control
- 032 Smart Design

Pursuit of Seasonal Efficiency

Over 90% of actual operation time, air conditioners are operated at partial capacity instead of rated capacity. We focused on high seasonal efficiency by all DC inverter control and high efficiency technology.

CORE TECHNOLOGY

High Efficiency

Optimized Inverter Control



i-PAM (IPM*+PAM) inverter control

i-PAM inverter control is a technology which reduces loss by adjusting the current waveform to a better sine waveform. This promotes the effective use of the input power supply to attain high performance.
IPM*: Intelligent Power Module



V-PAM (Vector + I-PAM) inverter control

V-PAM inverter control reduces the effects of magnetic flux and increases the maximum speed and efficiency of the compressor by vector control technology. With this technology, further miniaturization, higher efficiency, and better performance are attained.



All DC Inverter Technology



DC twin rotary compressor

The high efficiency DC inverter type "2-cylinder rotary compressor" is used for our product ranges. It has achieved higher energy efficiency compared with similar compressors by optimizing the structure inside the compressor.

DC fan motor

DC fan motor produces high power, wide operation range, and high efficiency.

Sine-wave DC inverter control

High efficiency operation is realized by using a sine wave DC inverter control.




High Efficiency Heat Exchanger

High density multi-path heat exchanger

Heat exchange performance is substantially improved by thin and high-density heat exchanger and multi-path efficiency technology.

High performance sub-cool heat exchanger

Higher performance achieved by mounting of counter type bypass circuit. (Large multi type, VRF)





It's Smart Operation

CORE TECHNOLOGY


Energy Saving Control

Smart Operation




Human sensor control

Human sensor catches movements of people in a room, and operates with lower capacity when people leave the room. When people come back to the room, it automatically returns to the previous operating mode.




Economy operation

Limits the maximum operation current, and the power consumption is cut down and the maximum load is suppressed.




Room temperature set point limitation

The minimum and maximum temperature range can be set giving further energy saving while considering the comfort of the occupants.




Set temperature auto return

- The setting temperature automatically returns to the previous setting temperature.
- The time range in which the set temperature can be changed is 10 to 120 minutes.



Auto-off timer

- The indoor unit is turned off automatically when it reaches to the preset operating time frame.
- The time frame of the "Auto off timer" can be flexibly scheduled.
- Off time can be set from 30 to 240 minutes.




Comfort Performance

Quick Comfort




Power diffuser

Precision wind direction control is realized and ventilation efficiency is also improved by 3 technologies. Our airflow control makes your environment more comfortable.




Powerful operation

Continuous operation by maximum airflow and maximum compressor speed after a certain period of time allows the temperature to reach the setting temp. quickly.



10°C HEAT operation

When you leave, minimum heating operation is performed to maintain the room temperature. (Maintained at 10°C)




Quiet and Comfort Control




Outdoor unit low noise operation

Users can choose low noise levels, depending on the installation environment. The operation time can be set using the timer.



Auto-changeover function

At Auto setting, the cooling/heating mode is automatically switched according to the set temperature and room temperature.



Powerful Heating

High heating capacity is realized even at low outdoor temperature by mounting a large heat exchanger or large DC rotary compressor and developing high performance inverter PCB



Easy air conditioner control from inside or outside the house and office using the Smartphones, Tablets, and PC

It is the most advanced solution to remotely manage an Air Conditioning system using all sort of mobile devices such as Smartphones, Tablets, and PC.

CORE TECHNOLOGY

Easy-to-use Control

Fujitsu General provides Various Easy-to-use Controllers

Fujitsu General is using ergonomics to expand the use of easy-to-use designs such as easy-to-read large LCD panels, easy-to-operate buttons, and displays with easily recognizable icons.

The individual controllers match the user operational environments, and the home controller makes batch energy saving management easy. Ease of use was pursued using simple operation buttons, a large LCD screen, and other features.

Residential use



Home central control



Central Remote Controller

Simple individual control



Wired Remote Controller



Simple Remote Controller



Slim Wireless Remote Controller

Commercial use



Each floor or Small building management control



Touch Panel Controller

Individual & Simple central control



Wired Remote Controller



Wired Remote Controller (Touch Panel)

Large building management control




System Controller

Software

Fujitsu General provides an interface that supports central management systems such as KNX®, MODBUS®, BACnet®, and LONWORKS®.

This allows customers to easily perform central control and monitoring of air conditioning equipment.



NEW



CORE TECHNOLOGY

Smart Design

Standard Range Series

New Design & Large Capacity

ASYG30LMTA

ASYG36LMTA

Creating Harmony and New Interior Design Space in a Variety of Installation Environments

Thinness and simplicity was thoroughly pursued in this design to fit the interior design. The lambda shaped high-density multi-path heat exchanger construction and full cover slide open panel provide both beauty and functionality.

The remote controller has also been designed utilizing ergonomics for ease of use while also pursuing beauty even in the details.

Fujitsu General provides its customers with highly functional air conditioners designed with high artistic sensitivity



Designer Range Series

High Spec & Design

ASYG09LTCA

ASYG12LTCA



Designer Range Series

High COP

ASYG07LUCA

ASYG09LUCA

ASYG12LUCA

ASYG14LUCA



Standard Range Series

High Efficiency & Comfort

ASYG07LMCA

ASYG09LMCA

ASYG12LMCA

ASYG14LMCA



ECO Range Series

Compact & Comfort

ASYG07LLCC

ASYG09LLCC

ASYG12LLCC



reddot design award
winner 2012



SUPPORT

Our know-how supports you not only during the product release but also from guiding implementation to product maintenance.

- 036 AIRSTAGE™ Support
- 038 Design Simulator
- 040 WATERSTAGE™ Support Tool
- 042 Quick Service and Maintenance


AIRSTAGE™ Support

Technical information

We provide information and tools that are useful for air conditioning system design, such as unit performance data and tools that make model selection and estimation easy.

Features

- Design & Technical Manual
- Model Selection & Estimation
- Certificate Data
- 2D/3D CAD Data



Product information

New product information is provided in the form of documents and movies for every new model released. These can be downloaded from a private section of our website. To access this website, please contact your Fujitsu representative.

Features

- Product News
- Brochures & All Manuals
- Feature Promotion Movie




Technical support

Technical support is provided at every stage from design to installation to assist in providing the most suitable air conditioning solution.

Features

- CFD Simulation
- Guide line
- Commissioning Support



CFD Simulation



Commissioning Support

Fujitsu General provides a variety of product and technical information to engineers and consultants, and also conducts new product research and design support activities.

We provide a wide range of support to maintain high quality from design to installation.

Training

Fujitsu General has many training facilities around the world that regularly conduct specialized product, technical, and service training. These research facilities also support the development of people with high technical capability.

Features

- Designing AIRSTAGE™ Systems
- Control System on-site training



Head Office Training Center: Japan



Europe Training Center: U.K.

America Training Center: U.S.A.



Europe Training Center: Germany



China Training Center: China



Asia Training Center: Singapore


Middle East Training Center: UAE

Oceania Training Center: Australia

Design Simulator

Automatically create model selection information


- Each unit can be automatically set by entering the required performance, type, and temperature conditions for each indoor unit and then dragging and dropping into the outdoor unit.
- Piping and wiring diagrams can be created automatically and it is easy to set branches, grouping, and options.
- The additional refrigerant charging amount is automatically calculated when the pipe length is entered.
- It is also easy to set the remote controller groups, central controller and converters.
- The equipment list including the equipment information is created automatically.



Output the format that matches the application


The information specific to your project can be exported in a number of industry standard file formats.

- Word format (rtf)
- Excel format (csv)
- Auto CAD format (DXF)
- 2D Data (DXF)
- 3D Data (RFA)



Update your Design Simulator

Database can be easily updated online using AutoUpdate function through FTP.



BIM Building Information Modeling

Fujitsu General provides the Building Information Modeling (BIM) object models and contents for our VRF system and some products to the architect, designer and contractor using Autodesk® Revit® technology from our Website and Autodesk® Seek Website, etc.

3D and 2D product data

We provide 3D data that closely resemble the actual product appearance. 2D CAD design operations are supported and 2D display is also provided. The data can also be output in other formats, such as DXF and DWG, which are used by other design CAD.

Installation limitation


The equipment installation limitation range is shown. Installation requirements, such as distance from the wall, is automatically displayed to make it easy to produce highly reliable layout designs.

Installation information

Other information, such as symbols showing the airflow direction that are required for installation drawings, is built in and can be automatically reflected in 2D drawings. Installation drawings can be created easily.

Product specifications & link information

Contains the basic information required for air conditioner design, including unit size, capacity, input power, noise, and airflow rate. These data can be procured from the Fujitsu General Website, Design Simulator, and Autodesk® Seek Website.



Put the charts and pens away and design your projects on your computer with ease using the Design Simulator. Everything from selecting indoor and outdoor units, allocating controls and optional parts to designing the piping and wiring systems is made easier using the program's built-in features. Once your project is designed take advantage of the Export functions to easily get materials lists, product specifications, refrigerant calculations and more - it'll even export to Word or Excel formats, and group the relevant CAD data for your project.

WATERSTAGE™ Support Tool

Model selection with detailed technical information

- The software automatically selects the equipments just by inputting some factors, like the region where the equipment is installed, required capacity to heat up the space, and a heating method.
- The transition in the equipment capacity at each outdoor temperature condition and/or when back up heater is under operation can be easily created by this software.



The visible images of the optional items enables the correct configuration of the systems. All of the associated optional items are automatically chosen in a case the application requires several devices of the WATERSTAGE™ equipments.



The entire system configuration can be reviewed and modified once the units are selected. And by seeing the images and the list of equipments at the same time, it avoids mistake in the selection of equipments.





The software automatically provides graphs of monthly running cost, CO₂ emission volume, cost comparison against other heating sources, and other data to allow the users to see at a glance the financial benefit of choosing WATERSTAGE equipments.

Energy labels and Fiches can be downloaded from our homepage

You can find and download the ErP documents (energy labels, product fiches, pre-configured package labels, pre-configured package fiches, information sheets and EC Declaration) from our homepage.

In addition, we will provide a internet service to allow the various package labels and package fiches to be created easily by installers in the future.




Fujitsu General's new software for the WATERSTAGE™ automatically provides a combination of WATERSTAGE™ equipments just by giving few parameters. The software is featured with multiple languages, and automatic update function.

Quick Service and Maintenance

Design for easy maintenance

The air conditioner operating status and trouble status of the detailed are displayed at the 7-segment of the outdoor unit PCB or on the remote controller screen. The unit status can be checked rapidly and quick response is also possible.


- Operation mode status
- Discharge temperature/Pressure status
- Compressor operation indication
- Address/Type/Number of outdoor unit
- Error code.



Error diagnosis by Service Tool


The unit status details from single split models to VRF system can be checked on PC screen by connecting Service Tool. Quick countermeasures can be taken

- Operation status/control
- Monitoring operating condition
- Monitoring sensor data
- Indication of trend graph
- Error history
- Indication of refrigerant circuit diagram (For VRF)



Remote monitoring

VRF system operating status and trouble status details can be constantly and remotely monitored over the Internet, etc. Rapid cooperation with the service personnel are also possible.



Mobile troubleshooting tool for iPhone

We will release an App of troubleshooting tool for iPhone, iPod touch and other Apple products. This application is a troubleshooting tool for Fujitsu General air conditioner (RAC/PAC, VRF)

It helps you to check air conditioner condition. Error code check, Troubleshooting, and Sensor check are available.



If trouble should occur in a unit or system, abundant support tools such as trouble code display at the product, Service Tool that allows checking of the detailed status of the entire system, and remote monitoring tool that uses the internet, etc. support quick service and maintenance anywhere and at any time.



PRODUCT CATEGORY

046 2016 Fujitsu General Solutions

050 SPLIT

090 MULTI SPLIT

114 OPTIONAL PARTS for SPLIT & MULTI SPLIT

128 VRF

200 VENTILATION

208 OPTIONAL PARTS for VRF

214 AIR TO WATER

2016 FUJITSU GENERAL SOLUTIONS



NEW SPLIT

Large Wall Mounted

- 30/36 class. Standard Range
- High seasonal energy efficiency
- Energy saving control with Human sensor



Large Cassette

- 18 to 54 class. 6 models
- Unique Circular Flow design/Uniform air distribution by the seamless airflow louver
- Individual louver control



Medium Static Pressure Duct

- 12 to 54 class. 8 models
- High efficiency & Quiet operation by new structure design
- Adopting Automatic Airflow adjustment function
- Improved installation flexibility



NEW MULTI SPLIT

Simultaneous Multi


- 36 to 54 class. Single phase 3 models



NEW OPTIONAL PARTS For SPLIT and MULTI SPLIT

Controller

- Easy-to-use and highly-functional controllers
- The room temperature can be controlled accurately with built-in thermo sensor.
- Built in weekly/daily timer (ON/OFF, Weekly)



MODBUS® Convertor

- The MODBUS Convertor can be connected to MODBUS Network system.
- Simple installation due to small and compact size
- The MODBUS Convertor permits central monitoring and control of air conditioners from BMS.



Wireless LAN Interface

- Mobile application control for single indoor units and multi system indoor units.
- Control basic operation (ON/OFF, Mode, Fan, Room temp., Louver position)
- Error display & E-mail notification





NEW VRF

AIRSTAGE™ J-III

- 4/5/6 HP class. Single phase/3 phase 6 models
- High energy efficiency



Mini Duct

- 7 to 24 class 6 models
- Compact design of Depth 450 mm and Height 198 mm
- Installation is possible even in narrow ceiling space
- In spite of compact model, V-shaped heat exchanger, large fan casing, and optimized airflow path achieve significant low noise.



High Static Pressure Duct

- 96 class high energy efficiency
- Wide static pressure range of 0 to 300 Pa
- 5 static pressure selection



NEW OPTIONAL PARTS For VRF


Touch Panel Controller

- Up to 400 indoor units can be controlled.
- Remote control and remote monitoring functions
- Electricity charge apportionment function added (option)



Converter

- Network converter can be connected to single split 2 types of DC power supply type and AC power supply type are available
- MODBUS® Converter can be connected to MODBUS Network



Network Converter

MODBUS® Converter



NEW AIR TO WATER

Split, Split DHW Integrated and Monobloc types

- Corresponding to the new ecodesign standard
- All models 5 kW to 16 kW class. 21 models



SPLIT
































































Energy saving design to
provide a comfortable indoor environment
while being environment-friendly.

An air conditioner that is people-friendly is also environment-friendly. Fujitsu General offers a broad lineup of products from large living rooms to bedrooms and children's rooms. We make your room more comfortable with a wide range of air conditioner types from ceiling wall type with automatic filters and cleaning functions to wall mounted type that improve the air cleaning function. Of course these models feature highly efficient operation that conserves electricity.

9 types 64 models

- 052 All Type Lineup
- 054 Feature Explanation
- 056 Wall Mounted
- 068 Floor
- 070 Floor/Ceiling
- 072 Ceiling
- 074 Compact Cassette
- 076 Cassette
- 080 Slim Duct
- 082 Medium Static Pressure Duct
- 086 High Static Pressure Duct

All Type Lineup

Type	Series	BTU													
		4	7	9	12	14	18	24	30	36	45	54	60	72	90
Wall Mounted Page 56 ~	Designer Range Series High Spec & Design			 ASYG09LTCA	 ASYG12LTCA										
	Designer Range Series High COP		 ASYG07LUCA	 ASYG09LUCA	 ASYG12LUCA	 ASYG14LUCA									
	Standard Range Series High Efficiency & Comfort		 ASYG07LMCA	 ASYG09LMCA	 ASYG12LMCA	 ASYG14LMCA									
	NEW Standard Range Series New Design & Large Capacity								 ASYG30LMTA	 ASYG36LMTA					
	Standard Range Series Comfort for Large Room						 ASYG18LFCA	 ASYG24LFCC	 ASYG30LFCA						
	ECO Range Series Compact & Comfort		 ASYG07LLCC	 ASYG09LLCC	 ASYG12LLCC										
Floor Compact & Comfort Page 68				 AGYG09LVCA	 AGYG12LVCA	 AGYG14LVCA									
Floor/Ceiling Comfort & Dual Design Page 70							 ABYG18LVTB	 ABYG24LVTA							
Ceiling Comfort for Large Room Page 72									 ABYG30LRTE	 ABYG36LRTE ABYG36LRTA	 ABYG45LRTA	 ABYG54LRTA			
Compact Cassette Page 74	4-way Flow Series Compact & Comfort				 AUYG12LVLB	 AUYG14LVLB	 AUYG18LVLB	 AUYG24LVLA							
Cassette Page 76 ~	4-way Flow Series Comfort for Large Room								 AUYG30LRLE	 AUYG36LRLE AUYG36LRLA	 AUYG45LRLA	 AUYG54LRLA			
	NEW Circular Flow Series Comfort for large room						 AUXG18LRLB	 AUXG24LRLB	 AUXG30LRLB	 AUXG36LRLB	 AUXG45LRLB	 AUXG54LRLB			
Slim Duct Slim & Comfort Page 80					 ARYG12LLTB	 ARYG14LLTB	 ARYG18LLTB								
Medium Static Pressure Duct High Efficiency & Comfort Page 82								 ARYG24LMLA	 ARYG30LMLE	 ARYG36LMLE ARYG36LMLA	 ARYG45LMLA				
NEW Medium Static Pressure Duct Compact & Comfort Page 84					 ARYG12LMTBP	 ARYG14LMTBP	 ARYG18LHTBP	 ARYG24LHTBP	 ARYG30LHTBP	 ARYG36LHTBP	 ARYG45LHTBP	 ARYG54LHTBP			
High Static Pressure Duct Page 86 ~											 ARYG45LHTA	 ARYG54LHTA	 ARYG60LHTA		
														 ARYC72LHTA	 ARYC90LHTA

FeatureExplanation

Energy Saving Function

Save human sensor
Human sensor detects the movement of people in the room and judges whether the energy saving operation.

Save & Stop human sensor
Human sensor detects the movement of people in the room and judges whether the energy saving or stop operation.

Economy mode
Thermostat setting automatically changes according to the temperature to avoid unnecessary cooling and heating.

Room temperature set point limitation
The minimum and maximum temperature range can be set giving further energy saving while considering the comfort of the occupants.

Set temperature auto return
The setting temperature automatically returns to the previously set temperature.

Comfortable Function

Powerful heating
Keeping the rated heating capacity even when the outdoor ambient temperature is -7°C.

Power diffuser
An additional louver that opens based on monitoring sensors to quickly enhance immediate comfort needs.

Powerful mode
Operation at maximum air flow and compressor speed, and quickly makes the room comfortable.

10°C HEAT operation
The room temperature can be set to go no lower than 10°C, thus ensuring that the room does not get too cold when not occupied.

Auto-changeover
The unit automatically switches between heating and cooling modes based on your temperature setting and the room temperature.

Up/down swing flaps
The up/down flaps automatically swing up and down.

Automatic fan speed
The micro-computer automatically adjusts the airflow effectively to follow the changes of room temperature.

Auto restart
In the event of a temporary power failure, the air conditioner will automatically restart in the same operating mode as before, once power supply is restored.

Fresh air intake
Fresh air can be taken in by a fan which can be connected using external control unit.

Connectable distributing duct
Systems are capable of attaching Locally purchased branch ducts distributing the airflow.

Convenient Function

Auto off timer
Automatically stops operation when a fixed time has elapsed from the start of operation.

Sleep timer
The micro-computer gradually changes the room temperature automatically to afford a comfortable night's sleep.

Weekly timer
Different ON-OFF times can be set for each day.

Weekly + setback timer
Weekly + Setback timer can set temperature for two times spans and for each day of the week.

External error output

External ON/OFF input

Clean Function

Ion deodorization filter
The filter deodorizes by powerfully decomposing absorbed odors using the oxidizing and reducing effects of ions generated by the ultra-fine-particle ceramic.

Apple-catechin filter
The Apple-catechin filter uses static electricity to clean fine particles and dust in the air.

Installation

Automatic airflow adjustment
Automatically detects required airflow in each application case and adjust the volume.

Drain pump as standard

Blue fin

Feature Summary

	Wall Mounted	Floor	Floor/Ceiling	Ceiling	Compact Cassette	Cassette	Slim Duct	Medium Static Pressure Duct	High Static Pressure Duct	
	ASYG09/12/LCA	ASYG07/09/12/14/LCA	ASYG07/09/12/14/LCA	ASYG07/09/12/14/LCA	ASYG07/09/12/14/LCA	ASYG07/09/12/14/LCA	ASYG07/09/12/14/LCA	ASYG07/09/12/14/LCA	ASYG07/09/12/14/LCA	
Energy Saving Function	Save human sensor	●	●							
	Save & Stop human sensor							○		
	Economy mode	●	●	●	●	●	●	●	●	●
	Room temperature set point limitation	○	○	○	○	○	○	○	○	○
	Set temperature auto return	○	○	○	○	○	○	○	○	○
Comfortable Function	Powerful heating	●								
	Power diffuser		●		●					
	Powerful mode	●	●	●	●	●	●	●	●	●
	Server room operation			●						
	10°C HEAT operation	●	●	●	●	●	●	○	○	○
	Low Noise mode	●	●	●	●	●	○	○	○	○
	Auto-changeover	●	●	●	●	●	●	●	●	●
	Up/down swing flaps	●	●	●	●	●	●	○		
	Double swing automatic			●		●	●			
	Automatic fan speed	●	●	●	●	●	●	●	●	●
	Auto restart	●	●	●	●	●	●	●	●	●
	Connectable fresh air duct						○	○	○	○
Convenient Function	Auto off timer	○	○	○	○	○	○	○	○	○
	Sleep timer	●	●	●	●	●	●	●	●	●
	Program timer	●	●	●	●	●	●	●	●	●
	Weekly timer	●	●	●	●	●	●	●	●	●
	Weekly + setback timer	○	○	○	○	○	○	○	○	○
	External error output	○	○	○	○	○	○	○	○	○
	External ON/OFF input	○	○	○	○	○	○	○	○	○
Clean Function	Ion deodorization filter	●	●	●	●	●	●	●	●	●
	Apple-catechin filter	●	●	●	●	●	●	●	●	●
	Washable panel		●	●	●	●	●	●	●	●
Installation	Automatic airflow adjustment									
	Drain pump as standard									
	Blue fin									


Wall Mounted Designer Range High Spec & Design



Features


Thin & Slim design

Thin and slim design is realized by high density multi-path heat exchanger and high efficiency wind blower.




Human sensor

Human sensor catches movements of people in a room, and operates with lower capacity when people leave the room. When people come back to the room, it automatically returns to previous operating mode.



Powerful heating

Rated heating capacity is maintained up to an outdoor temperature lower than -7 °C. This new model can operate even at -20 °C low outdoor temperature.




3 Mode timer (Weekly/Program/Sleep)

Weekly timer can be easily set by wireless remote controller. ON, OFF can be set up to 4 times in 1 day and up to 28 times in 1 week. For other modes, program timer and sleep timer can be also selected by one push.



Low ambient operation



Model: ASYG09LTCA / ASYG12LTCA



Wireless R.C.



For ASYG09LTCA



For ASYG12LTCA

Specifications


Model No.	Indoor unit		ASYG09LTCA		ASYG12LT CA		
	Outdoor unit		AOYG09LTC		AOYG12LTC		
Power Source			Single-phase, ~230V, 50Hz				
Capacity	Cooling	kW	2.5 (0.9-3.5)		3.5 (1.1-4.0)		
	Heating		3.2 (0.9-5.4)		4.0 (0.9-6.5)		
Input Power	Cooling/Heating	kW	0.505/0.660		0.850/0.910		
EER	Cooling	W/W	4.95		4.12		
COP	Heating		4.85		4.40		
Pdesign	Cooling/Heating(-10°C)	kW	2.5/3.0		3.5/4.0		
SEER	Cooling	W/W	8.50		8.50		
SCOP	Heating (Average)		4.60		4.60		
Energy Efficiency Class	Cooling		A+++		A+++		
	Heating (Average)		A++		A++		
Max. Operating Current	Cooling/Heating	A	6.5/9.0		9.0/10.5		
Annual Energy Consumption	Cooling	kWh/a	103		144		
	Heating		912		1217		
Moisture Removal			l/h		1.3		
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	42/36/32/21		43/37/32/21	
	Indoor (Heating)	H/M/L/Q		42/37/32/21		43/38/32/21	
Sound Power Level	Outdoor(Cooling/Heating)	High		48/50		48/49	
	Indoor(Cooling/Heating)	High		59/61		60/62	
Airflow Rate	Outdoor(Cooling/Heating)	High	63/65		64/65		
	Indoor / Outdoor	High	m³/h		800/1,700		
Net Dimensions H x W x D	Indoor	mm	282×870×185		282×870×185		
		kg(lbs)	9.5 (21)		9.5 (21)		
	Outdoor	mm	540×790×290		620×790×290		
		kg(lbs)	33 (73)		40 (88)		
Connection Pipe Diameter (Liquid / Gas)			mm		6.35/9.52		
Drain hose Diameter (I.D./O.D.)			mm		13.8/15.8 to 16.7		
Max Pipe Length (Pre-Charge)			m		20 (15)		
Max Height Difference			m		15		
Operation Range	Cooling	°CDB	-10 to 43		-10 to 43		
	Heating		-20 to 24		-20 to 24		
Refrigerant	Type (Global Warming Potential)		R410A (2,088)		R410A (2,088)		
	Charge	g	1,050		1,200		

Optional parts

Wired Remote Controller: UTY-RNNYM / UTY-RVNYM
Simple Remote Controller: UTY-RSNYM
Communication kit: UTY-TWBXF

Dimensions

(Unit : mm)




Wall Mounted Designer Range High COP



Features


Thin & Slim design

Thin and slim design is realized by Ø5-mm heat exchanger and high efficiency wind blower.




Powerful operation

20 minutes continuous operation by maximum airflow and maximum compressor speed is possible. Rapid cooling and heating makes the room comfortable quickly.




3 Mode timer (Weekly/Program/Sleep)

Weekly timer can be easily set by wireless remote controller. ON, OFF can be set up to 4 times in 1 day and up to 28 times in 1 week. For other modes, program timer and sleep timer can be also selected by one push.




10°C HEAT Operation

The room temperature can be set to go no lower than 10°C, thus ensuring that the room does not get too cold when not occupied. *Only available with Wireless RC.



Low ambient operation



Model: ASYG07LUCA / ASYG09LUCA / ASYG12LUCA / ASYG14LUCA



Wireless R.C.



For ASYG07/09LUCA



For ASYG12/14LUCA

Specifications


Model No.	Indoor unit		ASYG07LUCA	ASYG09LUCA	ASYG12LUCA	ASYG14LUCA
	Outdoor unit		AOYG07LUCA	AOYG09LUCB	AOYG12LUC	AOYG14LUC
Power Source			Single-phase, ~230V, 50Hz			
Capacity	Cooling	kW	2.0 (0.5-3.0)	2.5 (0.5-3.2)	3.5 (0.9-4.0)	4.2 (0.9-5.0)
	Heating	kW	3.0 (0.5-4.0)	3.2 (0.5-4.2)	4.0 (0.9-5.6)	5.4 (0.9-6.0)
Input Power	Cooling/Heating	kW	0.460/0.660	0.555/0.680	0.905/0.930	1.235/1.380
EER	Cooling	W/W	4.35	4.50	3.87	3.40
COP	Heating	W/W	4.55	4.71	4.30	3.91
Pdesign	Cooling/Heating(-10°C)	kW	2.0/2.6	2.5/2.8	3.5/3.9	4.2/4.8
SEER	Cooling	W/W	7.20	7.10	7.05	6.78
SCOP	Heating (Average)	W/W	4.10	4.10	4.00	4.00
Energy Efficiency Class	Cooling		A++	A++	A++	A++
	Heating (Average)		A+	A+	A+	A+
Max. Operating Current	Cooling/Heating	A	6.0/7.5	6.0/7.5	6.5/9.0	9.0/10.5
Annual Energy Consumption	Cooling	kWh/a	97	123	174	217
	Heating	kWh/a	887	956	1363	1677
Moisture Removal		l/h	1.0	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	38/35/31/21	42/36/32/21	43/37/32/21	45/40/33/25
	Indoor (Heating)	H/M/L/Q	38/35/31/21	42/37/32/21	43/38/32/21	45/40/34/27
Sound Power Level	Outdoor(Cooling/Heating)	High	46/46	48/48	50/50	50/50
	Indoor(Cooling/Heating)	High	57/59	59/61	60/62	60/64
Airflow Rate	Indoor / Outdoor	High	58/58	60/60	65/65	65/65
		m³/h	680/1,720	800/1,720	850/1,940	900/1,940
Net Dimensions H x W x D	Indoor	mm	282×870×185	282×870×185	282×870×185	282×870×185
	Outdoor	mm	540×660×290	540×660×290	540×790×290	540×790×290
Weight	Indoor	kg(lbs)	23 (51)	25 (55)	33 (73)	34 (75)
	Outdoor	kg(lbs)	23 (51)	25 (55)	33 (73)	34 (75)
Connection Pipe Diameter (Liquid / Gas)		mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.7
Drain hose Diameter (I.D./O.D.)		mm	13.8/15.8 to 16.7	13.8/15.8 to 16.7	13.8/15.8 to 16.7	13.8/15.8 to 16.7
Max Pipe Length (Pre-Charge)		m	20 (15)	20 (15)	20 (15)	20 (15)
Max Height Difference		m	15	15	15	15
Operation Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 43	-10 to 43
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	g	700	850	1,050	1,050

Optional parts


Wired Remote Controller: UTY-RNNYM, UTY-RVNYM
Simple Remote Controller: UTY-RSNYM
Communication kit: UTY-TWBXF

Dimensions

(Unit : mm)





Wall Mounted Standard Range High Efficiency & Comfort




Features

High efficient compact design




More comfort airflow




Powerful operation

20 minutes continuous operation by maximum airflow and maximum compressor speed is possible. Rapid cooling and heating makes the room comfortable quickly.




10°C HEAT Operation

The room temperature can be set to go no lower than 10°C, thus ensuring that the room does not get too cold when not occupied




Low noise mode for outdoor unit

Low noise mode of outdoor unit can be selected by wireless remote controller.



Low ambient operation



Model: ASYG07LMCA / ASYG09LMCA / ASYG12LMCA / ASYG14LMCA



Wireless R.C.



For ASYG07/09/12LMCA



For ASYG14LMCA

Specifications



Model No.	Indoor unit		ASYG07LMCA	ASYG09LMCA	ASYG12LMCA	ASYG14LMCA	
	Outdoor unit		AOYG07LMCA	AOYG09LMCA	AOYG12LMCA	AOYG14LMCA	
Power Source			Single-phase, ~230V, 50Hz				
Capacity	Cooling	kW	2.0 (0.5-3.0)	2.5 (0.5-3.2)	3.4 (0.9-3.9)	4.0 (0.9-4.4)	
	Heating		3.0 (0.5-3.4)	3.2 (0.5-4.0)	4.0 (0.9-5.3)	5.0 (0.9-6.0)	
Input Power	Cooling/Heating	kW	0.465/0.685	0.65/0.73	0.97/1.02	1.135/1.365	
EER	Cooling	W/W	4.30	3.85	3.50	3.52	
COP	Heating		4.38	4.38	3.92	3.66	
Pdesign	Cooling/Heating(-10°C)	kW	2.0/2.3	2.5/2.4	3.4/3.5	4.0/3.9	
SEER	Cooling	W/W	6.80	7.00	7.00	6.90	
SCOP	Heating (Average)		4.10	4.10	4.00	4.00	
Energy Efficiency Class	Cooling		A++	A++	A++	A++	
	Heating (Average)		A+	A+	A+	A+	
Max. Operating Current	Cooling/Heating	A	6.0/7.5	6.0/7.5	6.5/9.0	9.0/10.5	
Annual Energy Consumption	Cooling	kWh/a	103	125	170	203	
	Heating		786	820	1225	1365	
Moisture Removal			l/h	1.0	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q		43/40/32/21	43/40/32/21	43/40/32/21	44/40/33/25
	Indoor (Heating)	H/M/L/Q		43/38/33/22	43/38/33/22	43/38/33/22	44/40/35/27
Sound Power Level	Outdoor(Cooling/Heating)	High	dB(A)	45/45	45/45	50/50	50/50
	Indoor(Cooling/Heating)	High		59/59	59/59	59/59	60/60
	Outdoor(Cooling/Heating)	High		58/56	58/56	61/61	65/65
Airflow Rate	Indoor / Outdoor	High	m³/h	750/1670	750/1670	750/1830	750/1800
Net Dimensions H x W x D	Indoor	mm		268×840×203	268×840×203	268×840×203	268×840×203
		kg(lbs)		8.5 (19)	8.5 (19)	8.5 (19)	8.5 (19)
Weight	Outdoor	mm		535×663×293	535×663×293	535×663×293	540×790×290
		kg(lbs)		21 (46)	21 (46)	26 (57)	34 (75)
Connection Pipe Diameter (Liquid / Gas)			mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.7
Drain hose Diameter (I.D./O.D.)			mm	13.8/15.8 to 16.7	13.8/15.8 to 16.7	13.8/15.8 to 16.7	13.8/15.8 to 16.7
Max Pipe Length (Pre-Charge)			m	20 (15)	20 (15)	20 (15)	20 (15)
Max Height Difference				15	15	15	15
Operation Range	Cooling	°CDB	-10 to 43	-10 to 43	-10 to 43	-10 to 43	
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)			R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	g		700	700	850	1,050

Optional parts

Wired Remote Controller: UTY-RNNYM, UTY-RVNYM
Simple Remote Controller: UTY-RSNYM
Communication kit: UTY-XCBX22

Dimensions

(Unit : mm)




NEW Wall Mounted Standard Range New Design & Large Capacity



Features

Large Capacity & Powerful airflow

Achieved large capacity and powerful airflow by large heat exchanger, long cross-flow fan, high output DC fan motor and new airflow structure design.



Human sensor

Human sensor catches movements of people in a room, and operates with lower capacity when people leave the room. When people come back to the room, it automatically returns to previous operating mode.



Server room function*


The following interlock operation is possible by connecting 2 indoor units with a cable. Cooling operation can be performed even in the low outdoor temperature and low humidity environment.

- **Alternative operation:** Two units operate alternately
- **Backup operation:** When 1 unit breaks down, the other unit starts operating automatically.
- **Supporting operation:** Both units operate simultaneously when the loaded capacity is not enough with one unit


*2 x UTY-XWNX of optional parts are required.



High seasonal energy efficiency



Low ambient operation



Model: ASYG30LMTA / ASYG36LMTA



Wireless R.C.



Specifications


Model No.	Indoor unit		ASYG30LMTA		ASYG36LMTA		
	Outdoor unit		AOYG30LMTA		AOYG36LMTA		
Power Source			Single-phase, ~230V, 50Hz				
Capacity	Cooling	kW	8.0 (2.9-9.0)		9.4 (2.9-10.0)		
	Heating		8.8 (2.2-11.0)		10.1 (2.7-11.2)		
Input Power	Cooling/Heating	kW	2.33/2.41		3.16/2.96		
EER	Cooling	W/W	3.43		2.97		
COP	Heating		3.65		3.41		
Pdesign	Cooling/Heating(-10°C)	kW	8.0/6.5		9.4/7.1		
SEER	Cooling	W/W	6.35		5.73		
SCOP	Heating (Average)		4.15		4.19		
Energy Efficiency Class	Cooling		A++		A+		
	Heating (Average)		A+		A+		
Max. Operating Current	Cooling/Heating	A	14.5/14.5		19.0/19.0		
Annual Energy Consumption	Cooling	kWh/a	441		575		
	Heating		2,193		2,373		
Moisture Removal			l/h		3.7		
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	50/44/38/31		50/44/38/31	
	Indoor (Heating)	H/M/L/Q		49/44/39/33		49/44/39/33	
	Outdoor(Cooling/Heating)	High		52/55		55/56	
Sound Power Level	Indoor(Cooling/Heating)	High		65/65		65/65	
	Outdoor(Cooling/Heating)	High	67/68		68/70		
Airflow Rate	Indoor / Outdoor	High	m³/h	1380/3600		1380/3800	
Net Dimensions H x W x D	Indoor		mm	340×1150×280		340×1150×280	
			kg(lbs)	18 (40)		18 (40)	
Weight	Outdoor		mm	830×900×330		830×900×330	
			kg(lbs)	61 (134)		61 (134)	
Connection Pipe Diameter (Liquid / Gas)			mm	9.52/15.88		9.52/15.88	
Drain hose Diameter (I.D./O.D.)			mm	13.8 / 15.8 to 16.7		13.8 / 15.8 to 16.7	
Max Pipe Length (Pre-Charge)			m	50 (20)		50 (20)	
Max Height Difference				30		30	
Operation Range	Cooling	°CDB	-15 to 46		-15 to 46		
	Heating		-15 to 24		-15 to 24		
Refrigerant	Type (Global Warming Potential)		R410A (2,088)		R410A (2,088)		
	Charge		g	2,100		2,100	

Optional parts


- Wired Remote Controller (Touch panel (two-wire)): UTY-RNRYZ1 + UTY-TWRX
- Wired Remote Controller (High grade (three-wire)): UTY-RVNYM + UTY-XWNX
- Wired Remote Controller (two-wire): UTY-RLRY + UTY-TWRX
- Wired Remote Controller(three-wire): UTY-RNNYM + UTY-XWNX
- Simple Remote Controller (three-wire): UTY-RSNYM + UTY-XWNX
- External input and output PCB (with box): UTY-XCSXZ1 + UTZ-GXXB
- External Connect Kit: UTY-XWZX

Dimensions

(Unit : mm)




Wall Mounted Standard Range Comfort for Large Room




Features


“Vertical airflow” provides powerful floor level heating



“Horizontal airflow” does not blow cool air directly at the occupants in the room




Air conditioner filter features



Flexible Installation

	18 type	24 type	30 type
Max. Piping Length	25 m	30 m	50 m
Max. Height	20 m	20 m	30 m

Low ambient operation



Model: ASYG18LFCA / ASYG24LFCC / ASYG30LFCA



Wireless R.C.



For ASYG18LFCA, ASYG24LFCC



For ASYG30LFCA

Specifications

Model No.	Indoor unit		ASYG18LFCA	ASYG24LFCC	ASYG30LFCA	
	Outdoor unit		AOYG18LFC	AOYG24LFCC	AOYG30LFT	
Power Source			Single-phase, ~230V, 50Hz			
Capacity	Cooling	kW	5.2 (0.9-6.0)	7.1 (0.9-8.0)	8.0 (2.9-9.0)	
	Heating		6.3 (0.9-9.1)	8.0 (0.9-10.6)	8.8 (2.2-11.0)	
Input Power	Cooling/Heating	kW	1.52/1.71	2.20/2.21	2.49/2.44	
EER	Cooling	W/W	3.42	3.23	3.21	
COP	Heating		3.68	3.61	3.61	
Pdesign	Cooling/Heating(-10°C)	kW	5.2/5.9	7.1/7.1	8.0/8.0	
SEER	Cooling	W/W	6.94	6.11	5.69	
SCOP	Heating (Average)		3.87	3.80	3.80	
Energy Efficiency Class	Cooling		A++	A++	A+	
	Heating (Average)		A	A	A	
Max. Operating Current	Cooling/Heating	A	9.0/12.5	13.5/18.5	17.0/19.0	
Annual Energy Consumption	Cooling	kWh/a	262	406	492	
	Heating		2130	2610	2941	
Moisture Removal		l/h	2.6	2.7	3.2	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	43/37/33/26	49/42/37/32	48/42/37/33
	Indoor (Heating)	H/M/L/Q		42/37/33/25	48/42/37/32	49/42/37/33
Sound Power Level	Outdoor(Cooling/Heating)	High		50/51	55/56	53/56
	Indoor(Cooling/Heating)	High		58/58	64/64	64/64
Airflow Rate	Outdoor(Cooling/Heating)	High	65/-	68/-	68/-	
	Indoor / Outdoor	High	m³/h	900/2150	1120/2460	1100/3600
Net Dimensions H x W x D	Indoor	mm	320×998×238	320×998×238	320×998×238	
		kg(lbs)	14 (31)	14 (31)	14 (31)	
	Outdoor	mm	620×790×290	620×790×290	830×900×330	
		kg(lbs)	41 (90)	41 (90)	61 (135)	
Connection Pipe Diameter (Liquid / Gas)			6.35/12.7	6.35/15.88	9.52/15.88	
Drain hose Diameter (I.D./O.D.)			mm	12/16	12/16	
Max Pipe Length (Pre-Charge)			m	25 (15)	30 (15)	50 (20)
Max Height Difference				20	20	30
Operation Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	
	Heating		-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	
	Charge	g	1,200	1,800	2,100	


Optional parts

Wired Remote Controller: UTY-RNNYM, UTY-RVNYM

Simple Remote Controller: UTY-RSNYM

Dimensions

(Unit : mm)




- ① Refrigerant pipe flare connection (Liquid)
- ② Refrigerant pipe flare connection (Gas)
- ③ Drain hose connection (Drain hose)

Wall Mounted ECO Range Compact & Comfort




Features

High efficient compact design




ON-OFF Programmable timer

You can set an integrated ON-OFF or OFF-ON timer suitable for your life style. (Setting time: 0.5, 1, 1.5, 2, 2.5, -----9.5, 10, 11, 12 hours)




Powerful operation

20 minutes continuous operation by maximum airflow and maximum compressor speed is possible. Rapid cooling and heating makes the room comfortable quickly.




Economy operation

Setting temp. is shifted by 1°C automatically.



Low ambient operation



Model: ASYG07LLCC / ASYG09LLCC / ASYG12LLCC



Wireless R.C.



Specifications


Model No.	Indoor unit		ASYG07LLCC	ASYG09LLCC	ASYG12LLCC
	Outdoor unit		AOYG07LLCC	AOYG09LLCC	AOYG12LLCC
Power Source			Single-phase, ~230V, 50Hz		
Capacity	Cooling	kW	2.0 (0.9-2.8)	2.5 (0.9-3.0)	3.4 (0.9-3.8)
	Heating		2.7 (0.9-3.6)	3.0 (0.9-3.8)	4.0 (0.9-5.0)
Input Power	Cooling/Heating	kW	0.470/0.620	0.730/0.740	1.080/1.130
EER	Cooling	W/W	4.26	3.42	3.15
COP	Heating		4.35	4.05	3.54
Pdesign	Cooling/Heating(-10°C)	kW	2.0/2.2	2.5/2.3	3.4/3.2
SEER	Cooling	W/W	6.70	6.90	6.60
SCOP	Heating (Average)		4.00	4.00	3.80
Energy Efficiency Class	Cooling		A++	A++	A++
	Heating (Average)		A+	A+	A
Max. Operating Current	Cooling/Heating	A	6.0/7.5	6.0/7.5	6.5/9.0
Annual Energy Consumption	Cooling	kWh/a	104	127	180
	Heating		770	805	1,179
Moisture Removal		l/h	1.0	1.3	1.8
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	43/38/33/22	43/38/33/22	43/38/33/22
	Indoor (Heating)	H/M/L/Q			
Sound Power Level	Outdoor(Cooling/Heating)	High	47/48	47/48	50/51
	Indoor(Cooling/Heating)	High	59/60	59/60	59/60
	Outdoor(Cooling/Heating)	High	61/61	61/61	65/65
Airflow Rate	Indoor / Outdoor	High	m³/h	720/1,670	720/1,830
Net Dimensions H x W x D	Indoor		mm	262×820×206	262×820×206
			kg(lbs)	7.0 (15)	7.0 (15)
	Outdoor		mm	535×663×293	535×663×293
			kg(lbs)	24 (53)	24 (53)
Connection Pipe Diameter (Liquid / Gas)				6.35/9.52	6.35/9.52
Drain hose Diameter (I.D./O.D.)			mm	13.8/15.8 to 16.7	13.8/15.8 to 16.7
Max Pipe Length (Pre-Charge)			m	20 (15)	20 (15)
Max Height Difference				15	15
Operation Range	Cooling	°CDB	-10 to 43	-10 to 43	-10 to 43
	Heating		-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	g	650	650	850

Optional parts

Remote Controller Holder: UTZ-RXLA

Dimensions

(Unit : mm)




Floor Compact & Comfort



Features


2-Fan & Wide airflow

Individual vertical airflow by 2-fan can control the whole room comfortably.




Flexible & easy installation

Due to compact and whole surface suction method model, floor, concealed, half concealed, or wall mounted installation can be available to match the room layout.




Flexible piping connection 6 direction of drain & piping

Drain horse and piping can be drawn flexibly in the right, left, side, and down directions




10°C HEAT Operation

The room temperature can be set to go no lower than 10°C, thus ensuring that the room does not get too cold when not occupied



Low ambient operation



Model: AGYG09LVCA / AGYG12LVCA / AGYG14LVCA



Wireless R.C.



For AGYG09/12LVCA



For AGYG14LVCA

Specifications

Model No.	Indoor unit		AGYG09LVCA	AGYG12LVCA	AGYG14LVCA	
	Outdoor unit		A0YG09LVCA	A0YG12LVCA	A0YG14LVLA	
Power Source			Single-phase, ~230V, 50Hz			
Capacity	Cooling	kW	2.6 (0.9-3.5)	3.5 (0.9-4.0)	4.2 (0.9-5.0)	
	Heating		3.5 (0.9-5.5)	4.5 (0.9-6.6)	5.2 (0.9-8.0)	
Input Power	Cooling/Heating	kW	0.53/0.79	0.94/1.19	1.14/1.44	
EER	Cooling	W/W	4.91	3.72	3.68	
COP	Heating		4.43	3.78	3.61	
Pdesign	Cooling/Heating(-10°C)	kW	2.6/2.9	3.5/3.8	4.2/4.7	
SEER	Cooling	W/W	7.00	6.50	6.40	
SCOP	Heating (Average)		4.20	4.00	4.00	
Energy Efficiency Class	Cooling		A++	A++	A++	
	Heating (Average)		A+	A+	A+	
Max. Operating Current	Cooling/Heating	A	7.0/10.0	7.0/10.0	9.0/13.5	
Annual Energy Consumption	Cooling	kWh/a	130	188	230	
	Heating		967	1330	1645	
Moisture Removal			l/h	1.3	1.8	2.1
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	40/35/29/22	40/35/29/22	44/38/31/22
	Indoor (Heating)	H/M/L/Q		40/35/29/22	40/35/29/22	43/37/29/22
	Outdoor(Cooling/Heating)	High		47/48	48/49	50/50
Sound Power Level	Indoor(Cooling/Heating)	High	55/56	55/56	58/58	
	Outdoor(Cooling/Heating)	High	64/65	64/65	65/66	
Airflow Rate	Indoor / Outdoor	High	m³/h	570/1680	570/1680	650/1910
Net Dimensions H x W x D	Indoor		mm	600×740×200	600×740×200	600×740×200
			kg(lbs)	14 (31)	14 (31)	14 (31)
Weight	Outdoor		mm	540×790×290	540×790×290	578×790×300
			kg(lbs)	36 (79)	36 (79)	40 (88)
Connection Pipe Diameter (Liquid / Gas)			mm	6.35/9.52	6.35/9.52	6.35/12.7
Drain hose Diameter (I.D./O.D.)			mm	13.8/15.8 to 16.7	13.8/15.8 to 16.7	13.8/15.8 to 16.7
Max Pipe Length (Pre-Charge)			m	20 (15)	20 (15)	20 (15)
Max Height Difference				15	15	15
Operation Range	Cooling	°CDB	-10 to 43	-10 to 43	-10 to 43	
	Heating		-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	
	Charge	g	1,050	1,050	1,150	

Optional parts


Wired Remote Controller: UTY-RNNYM, UTY-RVNYM

Simple Remote Controller: UTY-RSNYM

Half Concealed Kit: UTR-STA

Dimensions

(Unit : mm)



Floor/Ceiling Comfort & Dual Design



Features

Flexible installation

Example for floor installation

Floor console




Example for ceiling installation

Under ceiling




Double auto swing

A combination of right/left and up/down directional swing allows 3-dimensional air direction control




High power DC fan motor

- High power
- Wide rotation range
- High efficiency



Low ambient operation



Model : ABYG18LVTB / ABYG24LVTA



Wireless R.C.



For ABYG18LVTB



For ABYG24LVTA

Specifications

Model No.	Indoor unit		ABYG18LVTB		ABYG24LVTA			
	Outdoor unit		AOYG18LALL		AOYG24LALA			
Power Source			Single-phase, ~230V, 50Hz					
Capacity	Cooling	kW	5.2 (0.9-5.9)		6.8 (0.9-8.0)			
	Heating		6.0 (0.9-7.5)		8.0 (0.9-9.1)			
Input Power	Cooling/Heating	kW	1.62/1.66		2.21/2.26			
EER	Cooling	W/W	3.21		3.08			
COP	Heating		3.61		3.54			
Pdesign	Cooling/Heating(-10°C)	kW	5.2/5.2		6.8/6.0			
SEER	Cooling	W/W	6.10		5.60			
SCOP	Heating (Average)		4.00		3.90			
Energy Efficiency Class	Cooling		A++		A+			
	Heating (Average)		A+		A			
Max. Operating Current	Cooling/Heating	A	9.0/12.5		12.0/13.5			
Annual Energy Consumption	Cooling	kWh/a	298		425			
	Heating		1819		2150			
Moisture Removal			l/h		2.7			
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	dB(A)	43/40/34/31		48/44/40/35		
	Indoor (Heating)	H/M/L/Q		43/40/34/31		48/44/40/35		
	Outdoor(Cooling/Heating)	High		50/50		52/53		
Sound Power Level	Indoor(Cooling/Heating)	High	57/57		61/61			
	Outdoor(Cooling/Heating)	High	62/65		67/70			
Airflow Rate	Indoor / Outdoor	High	m³/h		780/2000		980/2470	
Net Dimensions H x W x D	Indoor	mm	199×990×655		199×990×655			
		kg(lbs)	27 (59)		27 (59)			
Weight	Outdoor	mm	578×790×300		578×790×315			
		kg(lbs)	40 (88)		44 (97)			
Connection Pipe Diameter (Liquid / Gas)			mm		6.35/12.70		6.35/15.88	
Drain hose Diameter (I.D./O.D.)			mm		25/32		25/32	
Max Pipe Length (Pre-Charge)			m		25 (15)		30 (15)	
Max Height Difference			m		15		20	
Operation Range	Cooling	°CDB	-10 to 46		-10 to 46			
	Heating		-15 to 24		-15 to 24			
Refrigerant	Type (Global Warming Potential)		R410A (2,088)		R410A (2,088)			
	Charge		g		1,250		1,700	


Optional parts

Wired Remote Controller: UTY-RNNYM, UTY-RVNYM

Simple Remote Controller: UTY-RSNYM

Dimensions

(Unit : mm)



- ① Refrigerant piping flare connection (Liquid)
- ② Refrigerant piping flare connection (Gas)
- ③ Drain piping connection

Ceiling


Comfort for Large Room



Features


Flexible installation

Various installations are possible to match the room layout.




Multi auto swing


A combination of right/left and up/down directional swing allows 3-dimensional air direction control.



Fresh air intake




Low ambient operation



Model : ABYG30LRTE / ABYG36LRTE / ABYG45LRTA /
ABYG36LRTA [3phase] / ABYG45LRTA [3phase] / ABYG54LRTA [3phase]



Wireless R.C.



For ABYG30/36LRTE



For ABYG36/45/54LRTE

Specifications

Model No.	Indoor unit		ABYG30LRTE	ABYG36LRTE	ABYG45LRTA	ABYG36LRTA	ABYG45LRTA	ABYG54LRTA	
	Outdoor unit		AOYG30LETL	AOYG36LETL	AOYG45LETL	AOYG36LATT	AOYG45LATT	AOYG54LATT	
Power Source			Single-phase, ~230V, 50Hz			3-phase, ~400V, 50Hz			
Capacity	Cooling	kW	8.5 (2.8-10.0)	9.4 (2.8-11.2)	12.1 (4.0-13.3)	10.0 (4.7-11.4)	12.5 (5.0-14.0)	14.0 (5.4-16.0)	
	Heating		10.0 (2.7-11.2)	11.2 (2.7-12.7)	13.3 (4.2-15.5)	11.2 (5.0-14.0)	14.0 (5.4-16.2)	16.0 (5.8-18.0)	
Input Power	Cooling/Heating	kW	2.65/2.77	2.93/3.02	3.77/3.68	2.84/2.87	3.89/3.88	4.65/4.67	
EER	Cooling	W/W	3.21	3.21	3.21	3.52	3.21	3.01	
COP	Heating		3.61	3.71	3.61	3.90	3.61	3.43	
Pdesign	Cooling/Heating(-10°C)	kW	8.5/8.0	9.4/8.7	-	10.0/10.0	-	-	
SEER	Cooling	W/W	6.10	6.00	-	6.10	-	-	
SCOP	Heating		4.20	4.10	-	4.10	-	-	
Energy Efficiency Class	Cooling	A	A++	A+	-	A++	-	-	
	Heating		A+	A+	-	A+	-	-	
Max. Operating Current	Cooling/Heating	A	17.0/17.0	18.5/20.0	20.5/20.5	7.9/7.9	8.9/8.9	9.9/9.9	
Annual Energy Consumption	Cooling	kWh/a	487	548	-	573	-	-	
	Heating		2662	2965	-	3414	-	-	
Moisture Removal			l/h	2.5	3.0	4.0	3.0	4.5	5.0
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	45/43/37/32	47/43/37/32	49/45/39/34	47/43/37/32	49/45/39/34	51/48/42/38	
	Indoor (Heating)	H/M/L/Q	45/43/37/32	47/43/37/32	49/45/39/34	47/43/37/32	49/45/39/34	51/48/42/38	
Sound Power Level	Outdoor(Cooling/Heating)	High	53/55	54/55	55/55	51/53	54/54	55/56	
	Indoor(Cooling/Heating)	High	57/60	60/61	-	61/61	-	-	
Airflow Rate	Outdoor(Cooling/Heating)	High	68/69	69/70	-	67/69	-	-	
	Indoor / Outdoor	High	m³/h	1660/3600	1900/3800	2100/6200	1900/6200	2100/6900	2300/6900
Net Dimensions H x W x D	Indoor	mm	240×1660×700	240×1660×700	240×1660×700	240×1660×700	240×1660×700	240×1660×700	
		kg(lbs)	46 (101)	46 (101)	46 (101)	46 (101)	46 (101)	48 (106)	
Weight	Outdoor	mm	830×900×330	830×900×330	1290×900×330	1290×900×330	1290×900×330	1290×900×330	
		kg(lbs)	61 (134)	61 (134)	86 (189)	104 (229)	104 (229)	104 (229)	
Connection Pipe Diameter (Liquid / Gas)			mm	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	
Drain port Diameter (I.D./O.D.)			mm	22.0/25.6	22.0/25.6	22.0/25.6	22.0/25.6	22.0/25.6	
Max Pipe Length (Pre-Charge)			m	50 (20)	50 (20)	50 (20)	75 (30)	75 (30)	75 (30)
Max Height Difference			m	30	30	30	30	30	30
Operation Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	
	Charge	g	2,100	2,100	3,350	3,450	3,450	3,450	


Optional parts

Wired Remote Controller: UTY-RNNYM, UTY-RVNYM

Simple Remote Controller: UTY-RSNYM


Drain Pump Unit: UTR-DPB24T

Flange: UTD-RF204



Dimensions

(Unit : mm)



- ① Refrigerant piping flare connection (Liquid)
- ② Refrigerant piping flare connection (Gas)
- ③ Drain piping connection


Compact Cassette 4-way Flow Compact & Comfort



Features


2-stage turbo fan

High efficiency design by 2 stage structure




Quiet quality

Optimization of wing form (laminar wing type) and wing number (7 blades each)




Improvement of the airflow distribution

New louvre: The louvre design distributes air leaving a space between the chassis and the ceiling allowing far and wide airflow distribution.



Low ambient operation



Model : AUYG12LVLB / AUYG14LVLB / AUYG18LVLB / AUYG24LVLA



Wireless R.C.



For AUYG12/14/18LVLB



For AUYG24LVLA

Specifications

Model No.	Indoor unit		AUYG12LVLB	AUYG14LVLB	AUYG18LVLB	AUYG24LVLA
	Outdoor unit		AOYG12LALL	AOYG14LALL	AOYG18LALL	AOYG24LALA
Power Source			Single-phase, ~230V, 50Hz			
Capacity	Cooling	kW	3.5 (0.9-4.4)	4.3 (0.9-5.4)	5.2 (0.9-5.9)	6.8 (0.9-8.0)
	Heating		4.1 (0.9-5.7)	5.0 (0.9-6.5)	6.0 (0.9-7.5)	8.0 (0.9-9.1)
Input Power	Cooling/Heating	kW	1.05/1.11	1.33/1.34	1.62/1.66	2.21/2.26
EER	Cooling	W/W	3.33	3.21	3.21	3.08
COP	Heating		3.69	3.71	3.61	3.54
Pdesign	Cooling/Heating(-10°C)	kW	3.5/4.2	4.3/4.5	5.2/5.2	6.8/6.0
SEER	Cooling	W/W	6.20	6.40	6.20	5.60
SCOP	Heating (Average)		4.10	4.40	4.20	3.90
Energy Efficiency Class	Cooling		A++	A++	A++	A+
	Heating (Average)		A+	A+	A+	A
Max. Operating Current	Cooling/Heating	A	7.5/10.0	9.0/12.5	9.0/12.5	12.0/13.5
Annual Energy Consumption	Cooling	kWh/a	198	235	293	425
	Heating		1431	1432	1731	2151
Moisture Removal		l/h	1.2	1.5	2.2	2.7
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	37/34/30/27	38/34/30/27	38/34/30/26	49/44/36/30
	Indoor (Heating)	H/M/L/Q	37/34/31/29	43/38/34/30	43/38/34/30	49/45/40/33
Sound Power Level	Outdoor(Cooling/Heating)	High	47/48	49/49	50/50	52/53
	Indoor(Cooling/Heating)	High	49/49	50/55	50/55	59/61
Airflow Rate	Outdoor(Cooling/Heating)	High	61/63	62/64	62/65	67/70
	Indoor / Outdoor	High	600/1780	680/1910	680/2000	930/2470
Net Dimensions H x W x D	Indoor	mm	245×570×570	245×570×570	245×570×570	245×570×5700
		kg(lbs)	15 (33)	15 (33)	15 (33)	16 (35)
Weight	Outdoor	mm	578×790×300	578×790×300	578×790×300	578×790×315
		kg(lbs)	40 (88)	40 (88)	40 (88)	44 (97)
Connection Pipe Diameter (Liquid / Gas)		mm	6.35/9.52	6.35/12.70	6.35/12.70	6.35/15.88
Drain hose Diameter (I.D./O.D.)			25/32	25/32	25/32	25/32
Max Pipe Length (Pre-Charge)		m	25 (15)	25 (15)	25 (15)	30 (15)
Max Height Difference			15	15	15	20
Operation Range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	g	1,150	1,250	1,250	1,700
Cassette Grille	Model name		UTG-UFYD-W	UTG-UFYD-W	UTG-UFYD-W	UTG-UFYD-W
	Dimensions (H × W × D)	mm	49×700×700	49×700×700	49×700×700	49×700×700
	Weight	kg(lbs)	2.6 (6)	2.6 (6)	2.6 (6)	2.6 (6)


Optional parts

- Air Outlet Shutter Plate: UTR-YDZB
Wired Remote Controller: UTY-RNNYM, UTY-RVNYM
Simple Remote Controller: UTY-RSNYM
Insulation Kit For High Humidity: UTZ-KXGC
Fresh Air Intake Kit: UTZ-VXAA




Dimensions

(Unit : mm)



Cassette 4-way Flow Comfort for large room




Features

High efficiency turbo fan with 3-dimensional blade


Previous turbo fan: Air passing through the heat exchanger was uneven and the air would only flow close to the ceiling.

New turbo fan: High efficiency airflow distribution has been achieved by the introduction of a 3 dimensional blade which increases the air passing over the heat exchanger.




Improvement of the airflow distribution

New louvre: The louvre design distributes air leaving a space between the chassis and the ceiling allowing far and wide airflow distribution.




Adjustment of hanger position is possible after installation

Hanging bracket can be checked directly by removing the corner cover. Hanging position can be arranged easily.



Low ambient operation



Model : AUYG30LRLE / AUYG36LRLE / AUYG45LRLA / AUYG54LRLA / AUYG36LRLA [3phase] / AUYG45LRLA [3phase] / AUYG54LRLA [3phase]



Wired R.C.



For AUYG30/36LRLE



For AUYG36/45/54LRLA

Specifications

Model No.	Indoor unit		AUYG30LRLE	AUYG36LRLE	AUYG45LRLA	AUYG54LRLA	AUYG36LRLA	AUYG45LRLA	AUYG54LRLA
	Outdoor unit		AOYG30LETL	AOYG36LETL	AOYG45LETL	AOYG54LETL	AOYG36LATT	AOYG45LATT	AOYG54LATT
Power Source			Single-phase, ~230V, 50Hz				3-phase, ~400V, 50Hz		
Capacity	Cooling	kW	8.5 (2.8-10.0)	10.0 (2.8-11.2)	12.5 (4.0-14.0)	13.3 (4.5-14.5)	10.0 (4.7-11.4)	12.5 (5.0-14.0)	14.0 (5.4-16.0)
	Heating		10.0 (2.7-11.2)	11.2 (2.7-12.7)	14.0 (4.2-16.2)	16.0 (4.7-16.5)	11.2 (5.0-14.0)	14.0 (5.4-16.2)	16.0 (5.8-18.0)
Input Power	Cooling/Heating	kW	2.65/2.77	3.12/3.02	3.88/3.77	4.42/4.69	2.44/2.56	3.54/3.58	4.36/4.43
EER	Cooling	W/W	3.21	3.21	3.22	3.01	4.10	3.53	3.21
COP	Heating		3.61	3.71	3.71	3.41	4.38	3.91	3.61
Pdesign	Cooling/Heating (-10°C)	kW	8.5/8.0	10.0/8.7	-	-	10.0/10.0	-	-
SEER	Cooling	W/W	6.50	6.30	-	-	6.50	-	-
SCOP	Heating (Average)		4.30	4.20	-	-	4.30	-	-
Energy Efficiency Class	Cooling	A++	A++	-	-	A++	-	-	
	Heating (Average)	A+	A+	-	-	A+	-	-	
Max. Operating Current	Cooling/Heating	A	17.0/17.0	18.5/20.0	20.5/20.5	21.5/21.5	7.9/7.9	8.9/8.9	9.9/9.9
Annual Energy Consumption	Cooling	kWh/a	458	555	-	-	538	-	-
	Heating		2604	2897	-	-	3253	-	-
Moisture Removal		l/h	2.5	3.5	4.5	5.0	3.0	4.5	5.0
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	40/38/36/32	43/38/36/32	46/42/40/36	47/43/41/37	44/39/36/33	46/42/40/36	47/43/41/37
	Indoor (Heating)	H/M/L/Q	40/38/36/32	43/38/36/32	46/42/40/36	47/43/41/37	44/39/36/33	46/42/40/36	47/43/41/37
Sound Power Level	Outdoor(Cooling/Heating)	High	53/55	54/55	55/55	55/57	51/53	54/54	55/56
	Indoor(Cooling/Heating)	High	54/54	57/57	-	-	58/58	-	-
	Outdoor(Cooling/Heating)	High	68/69	69/70	-	-	67/69	-	-
Airflow Rate	Indoor / Outdoor	High	m³/h 1600/3600	1800/3800	1900/6750	2000/6750	1800/6200	1900/6750	2000/6900
Net Dimensions H x W x D	Indoor	mm	288x840x840	288x840x840	288x840x840	288x840x840	288x840x840	288x840x840	288x840x840
	Outdoor	kg(lbs)	26 (57)	26 (57)	26 (57)	26 (57)	26 (57)	26 (57)	26 (57)
		mm	830x900x330	830x900x330	1290x900x330	1290x900x330	1290x900x330	1290x900x330	1290x900x330
Weight		kg(lbs)	61 (135)	61 (135)	86 (190)	86 (190)	104 (229)	104 (229)	104 (229)
Connection Pipe Diameter (Liquid / Gas)		mm	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Drain hose Diameter (I.D./O.D.)		mm	25.0/32.0	25.0/32.0	25.0/32.0	25.0/32.0	25.0/32.0	25.0/32.0	25.0/32.0
Max Pipe Length (Pre-Charge)		m	50 (20)	50 (20)	50 (20)	50 (20)	75 (30)	75 (30)	75 (30)
Max Height Difference			30	30	30	30	30	30	30
Operation Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	g	2,100	2,100	3,350	3,350	3,450	3,450	3,450
Cassette Grille	Model name		UTG-UGYA-W	UTG-UGYA-W	UTG-UGYA-W	UTG-UGYA-W	UTG-UGYA-W	UTG-UGYA-W	UTG-UGYA-W
	Dimensions (H x W x D)	mm	50x950x950	50x950x950	50x950x950	50x950x950	50x950x950	50x950x950	50x950x950
	Weight	kg(lbs)	5.5 (12)	5.5 (12)	5.5 (12)	5.5 (12)	5.5 (12)	5.5 (12)	5.5 (12)


Optional parts

Wired Remote Controller:	UTY-RNNYM, UTY-RVNYM	Panel Spacer:	UTG-BKXA-W
Simple Remote Controller:	UTY-RSNYM	Air Outlet Shutter Plate:	UTR-YDZK
IR Receiver Kit:	UTY-LRHYA2	Insulation Kit For High Humidity:	UTZ-KXRA
Wide Panel:	UTG-AKXA-W	Fresh Air Intake Kit:	UTZ-VXRA



Dimensions

(Unit : mm)





Features

Unique Circular Flow design


New Cassette type realizes Circular Flow to blow large airflow in 360° direction by mounting high performance DC fan motor, new turbo fan and unique seamless airflow louver design.

ø7mm high density heat exchanger

New DC fan motor


High efficient turbo fan

Seamless airflow louver



Uniform temperature air conditioning


Achieve a comfortable air conditioning spread to every corner of the room by circular flow & wide vertical airflow.



Individual louver control

Each louver can be set individually by Touch Panel Wired Remote Controller to enjoy the comfort of different directional airflows according to various room layouts.

*Touch Panel Wired RC (UTY-RNRYZ1) only




Comfortable air conditioning by preventing direct blowing of cold air and by providing swinging air flow simultaneously.



Efficient air conditioning based on the room layout

Human sensor increases more energy saving

Energy saving operation starts automatically by detecting the motion of a person. 2 modes of save operation mode and stop mode can be selected.



Human sensor (Option)

2 modes can be selected.

Auto saving


Power is saved while people are away.

Auto OFF

Operation stops after people go out.

*Touch Panel Wired RC (UTY-RNRYZ1) only

Low ambient operation



Model: AUXG18LRLB / AUXG24LRLB
AUXG30LRLB / AUXG36LRLB / AUXG45LRLB / AUXG54LRLB




Touch Panel Wired R.C.



For AUXG18/24LRLB



For AUXG30/36LRLB




For AUXG45/54LRLB

Specifications

Model No.	Indoor unit		AUXG18LRLB	AUXG24LRLB	AUXG30LRLB	AUXG36LRLB	AUXG45LRLB	AUXG54LRLB
	Outdoor unit		AOYG18LBCA	AOYG24LBCA	AOYG30LBTB	AOYG36LBTB	AOYG45LBTB	AOYG54LBTB
Power Source			Single-phase, ~230V, 50Hz					
Capacity	Cooling	kW	5.2 (0.9-6.5)	6.8 (0.9-8.0)	8.5 (2.8-10.0)	9.5 (2.8-11.2)	12.5 (4.0-14.0)	13.3 (4.5-14.5)
	Heating	kW	6.0 (0.9-8.0)	7.8 (0.9-9.1)	10.0 (2.7-11.2)	10.8 (2.7-12.7)	14.0 (4.2-16.2)	15.8 (4.7-16.5)
Input Power	Cooling/Heating	kW	1.42/1.50	2.16/2.18	2.56/2.77	2.96/2.91	3.85/3.73	4.38/4.58
EER	Cooling		3.66	3.15	3.32	3.21	3.25	3.04
COP	Heating		4.00	3.58	3.61	3.71	3.75	3.45
Pdesign	Cooling/Heating (-10°C)	kW	5.2/4.3	6.8/6.0	8.5/8.0	9.5/8.7	-	-
SEER	Cooling		7.05	6.60	6.70	6.40	-	-
SCOP	Heating (Average)		4.40	4.20	4.30	4.30	-	-
Energy Efficiency Class	Cooling		A++	A++	A++	A++	-	-
	Heating (Average)		A+	A+	A+	A+	-	-
Max. Operating Current	Cooling/Heating	A	10.0/13.5	13.5/18.5	17.0/17.0	20.0/20.0	20.5/20.5	21.5/21.5
Annual Energy Consumption	Cooling	kWh/a	258	361	444	519	-	-
	Heating	kWh/a	1367	1999	2604	2833	-	-
Moisture Removal		l/h	2.2	2.7	2.5	3.3	4.5	5.0
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	33/32/31/28	35/33/32/29	40/38/36/33	44/41/38/34	46/42/39/35	47/43/40/36
	Indoor (Heating)	H/M/L/Q	33/32/31/28	35/33/32/29	40/38/36/33	44/41/38/34	46/42/39/35	47/43/40/36
	Outdoor (Cooling/Heating)	High	51/50	55/56	53/55	54/55	55/55	55/57
Sound Power Level	Indoor (Cooling/Heating)	High	47/47	49/49	54/54	58/58	60/60	61/61
	Outdoor (Cooling/Heating)	High	64/62	68/68	67/69	68/70	68/68	69/71
	Outdoor (Cooling/Heating)	High	64/62	68/68	67/69	68/70	68/68	69/71
Airflow Rate	Indoor / Outdoor	High	1050/1900	1150/2460	1600/3600	1900/3800	2000/6750	2100/6750
		mm	246×840×840	246×840×840	288×840×840	288×840×840	288×840×840	288×840×840
Net Dimensions H x W x D	Indoor	kg (lbs)	24 (53)	24 (53)	26 (57)	26 (57)	29 (64)	29 (64)
	Outdoor	kg (lbs)	620×790×290	620×790×290	830×900×330	830×900×330	1290×900×330	1290×900×330
Weight	Indoor	kg (lbs)	41 (90)	41 (90)	61 (134)	61 (134)	86 (189)	86 (189)
	Outdoor	kg (lbs)	41 (90)	41 (90)	61 (134)	61 (134)	86 (189)	86 (189)
Connection Pipe Diameter (Liquid / Gas)		mm	6.35/12.7	6.35/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Drain hose Diameter (I.D./O.D.)		mm	25/32	25/32	25/32	25/32	25/32	25/32
Max Pipe Length (Pre-Charge)		m	30 (15)	30 (15)	50 (20)	50 (20)	50 (20)	50 (20)
Max Height Difference		m	20	20	30	30	30	30
Operation Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating	°CDB	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	g	1,800	1,800	2,100	2,100	3,350	3,350
Cassette Grille	Model name		UTG-UKYA-W	UTG-UKYA-W	UTG-UKYA-W	UTG-UKYA-W	UTG-UKYA-W	UTG-UKYA-W
	Dimensions (H × W × D)	mm	53×950×950	53×950×950	53×950×950	53×950×950	53×950×950	53×950×950
	Weight	kg (lbs)	6.0 (13)	6.0 (13)	6.0 (13)	6.0 (13)	6.0 (13)	6.0 (13)


Optional parts

Wired Remote Controller:	UTY-RNRYZ1, UTY-RVNYM, UTY-RLRY, UTY-RNNYM	Panel Spacer:	UTG-BKXA-W
Simple Remote Controller:	UTY-RSNYM	Air Outlet Shutter Plate:	UTR-YDZK
IR Receiver Kit:	UTY-LBTYC	Insulation Kit For High Humidity:	UTZ-KXRA
Human Sensor Kit:	UTY-SHZXC	Flesh Air Intake Kit:	UTZ-VXRA
Wide Panel:	UTG-AKXA-W	External input and output PCB (with box):	UTY-XCSX + UTZ-GXRA
		External connect kit:	UTY-XWZXZG, UTY-XWZXZ3



Dimensions

(Unit : mm)



() : AUXG18/24LRLB


Slim Duct Slim & Comfort



Features


Slim design

The slim design allows installations where ceilings are narrow.
Drain hose as standard accessory



Flexible installation

2-type installation methods of ceiling concealed and floor concealed can be selected.



Selectable with a wide range of static pressure



By using the DC fan motor, it is possible to change the static pressure range from 0 to 90 Pa.
The change of static pressure range is possible by remote controller.



Static pressure range
0 to 90 Pa

Auto Louver Grille Kit (Option)


Simple flat Auto Louver will provide comfort airflow and harmonize with luxury interior.




Model : ARYG12LLTB / ARYG14LLTB / ARYG18LLTB



Wired R.C.



ARYG12/14LLTB



ARYG18LLTB




Specifications

Model No.	Indoor unit		ARYG12LLTB		ARYG14LLTB		ARYG18LLTB		
	Outdoor unit		AOYG12LALL		AOYG14LALL		AOYG18LALL		
Power Source			Single-phase, ~230V, 50Hz						
Capacity	Cooling	kW	3.5 (0.9-4.4)		4.3 (0.9-5.4)		5.2 (0.9-5.9)		
	Heating		4.1 (0.9-5.7)		5.0 (0.9-6.5)		6.0 (0.9-7.5)		
Input Power	Cooling/Heating	kW	1.05/1.11		1.33/1.34		1.62/1.66		
EER	Cooling	W/W	3.33		3.21		3.21		
COP	Heating		3.69		3.71		3.61		
Pdesign	Cooling/Heating(-10°C)	kW	3.5/4.2		4.3/4.5		5.2/5.2		
SEER	Cooling	W/W	5.90		5.80		6.20		
SCOP	Heating		4.00		3.90		4.10		
Energy Efficiency Class	Cooling		A+		A+		A++		
	Heating		A+		A		A+		
Max. Operating Current	Cooling/Heating	A	7.5/10.0		9.0/12.5		9.0/12.5		
Annual Energy Consumption	Cooling	kWh/a	207		259		293		
	Heating		1467		1614		1774		
Moisture Removal		l/h	1.3		1.5		2.0		
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	29/28/26/25		32/30/28/26		32/30/29/27		
	Indoor (Heating)	H/M/L/Q	29/28/26/24		32/30/28/25		32/30/29/27		
	Outdoor(Cooling/Heating)	High	47/48		49/49		50/50		
Sound Power Level	Indoor(Cooling/Heating)	High	58/58		60/60		58/58		
	Outdoor(Cooling/Heating)	High	61/63		62/64		62/65		
Airflow Rate	Indoor / Outdoor	High	m³/h	650/1780		800/1910		940/2000	
Static pressure range (Standard)			Pa	0 to 90 (25)		0 to 90 (25)		0 to 90 (25)	
Net Dimensions H x W x D Weight	Indoor		mm	198×700×620		198×700×620		198×900×620	
			kg(lbs)	19 (42)		19 (42)		23 (51)	
	Outdoor		mm	578×790×300		578×790×300		578×790×300	
			kg(lbs)	40 (88)		40 (88)		40 (88)	
Connection Pipe Diameter (Liquid / Gas)			mm	6.35/9.52		6.35/12.70		6.35/12.70	
Drain hose Diameter (I.D./O.D.)			mm	25/32		25/32		25/32	
Max Pipe Length (Pre-Charge)			m	25 (15)		25 (15)		25 (15)	
Max Height Difference				15		15		15	
Operation Range	Cooling	°CDB		-10 to 46		-10 to 46		-10 to 46	
	Heating			-15 to 24		-15 to 24		-15 to 24	
Refrigerant	Type (Global Warming Potential)			R410A (2,088)		R410A (2,088)		R410A (2,088)	
	Charge	g		1,150		1,250		1,250	


Optional parts

Wired Remote Controller: UTY-RNNYM, UTY-RVNYM
Simple Remote Controller: UTY-RSNYM
IR Receiver Kit: UTY-LRHYM
Remote Sensor Unit: UTY-XSZX
Auto Louver Grille Kit: UTD-GXTA-W (For ARYG12 / 14LLTB)
UTD-GXTB-W (For ARYG18LLTB)



Dimensions

(Unit : mm)



	ARYG12 / 14LLTB	ARYG18LLTB
A	700	900
B	650	850
C	734	934
D	650	850
E	P100x6=600	P100x8=800
F	18xØ5	22xØ5
G	574	774


Medium Static Pressure Duct High Efficiency & Comfort




Features

Slim & Compact design

In the case of bottom return air connection, not only does the indoor unit design allow for installation in a narrow ceiling space of up to 270 mm, Further space savings have been achieved by mounting the control box internally inside the chassis.




Two-direction drain piping




Easy maintenance

Structural improvement is attained by making the bottom panel two pieces, front and rear. The internal fan casing is also manufactured in two pieces, namely upper and lower. The maintenance of the motor and fan can be easily carried out by removing the rear panel and the lower part of the casing while leaving the main chassis installed.

See below for the case of rear suction type



Low ambient operation



Model : ARYG24LMLA / ARYG30LMLE / ARYG36LMLE / ARYG45LMLA / ARYG36LMLA [3phase] / ARYG45LMLA [3phase]




Wired R.C.



For ARYG24LMLA



For ARYG30/36LMLE




For ARYG36/45LMLA

Specifications

Model No.	Indoor unit		ARYG24LMLA	ARYG30LMLE	ARYG36LMLE	ARYG45LMLA	ARYG36LMLA	ARYG45LMLA	
	Outdoor unit		AOYG24LALA	AOYG30LETL	AOYG36LETL	AOYG45LETL	AOYG36LATT	AOYG45LATT	
Power Source			Single-phase, ~230V, 50Hz				3-phase, ~400V, 50Hz		
Capacity	Cooling	kW	6.8 (0.9-8.0)	8.5 (2.8-10.0)	9.4 (2.8-11.2)	12.1 (4.0-13.3)	10.0 (4.7-11.4)	12.5 (5.0-14.0)	
	Heating		8.0 (0.9-9.1)	10.0 (2.7-11.2)	11.2 (2.7-12.7)	13.1 (4.2-15.5)	11.2 (5.0-14.0)	14.0 (5.4-16.2)	
Input Power	Cooling/Heating	kW	2.21/2.26	2.65/2.68	2.96/3.10	3.77/3.68	2.84/2.87	3.89/3.88	
EER	Cooling	W/W	3.08	3.21	3.18	3.21	3.52	3.21	
COP	Heating		3.54	3.73	3.61	3.61	3.90	3.61	
Pdesign	Cooling/Heating(-10°C)	kW	6.8/6.0	8.5/8.0	9.4/8.7	-	10.0/10.0	-	
SEER	Cooling	W/W	6.20	5.90	5.70	-	5.80	-	
SCOP	Heating		4.00	3.90	3.80	-	4.00	-	
Energy Efficiency Class	Cooling	A	A++	A+	A+	-	A+	-	
	Heating		A+	A	A	-	A+	-	
Max. Operating Current	Cooling/Heating	A	12.0/13.5	17.0/17.0	18.5/20.0	21.0/21.0	8.5/8.5	9.5/9.5	
Annual Energy Consumption	Cooling	kWh/a	384	504	576	-	603	-	
	Heating		2098	2868	3202	-	3497	-	
Moisture Removal		l/h	2.5	2.5	3.0	4.0	3.0	4.5	
Sound Pressure Level	Indoor (Cooling)	H/M/L/Q	31/29/27/25	39/35/30/26	39/35/30/26	42/38/32/28	38/36/31/26	42/38/32/28	
	Indoor (Heating)	H/M/L/Q	31/29/27/25	42/35/30/26	42/35/30/26	42/38/32/28	40/36/31/26	42/38/32/28	
Sound Power Level	Outdoor(Cooling/Heating)	High	52/53	53/55	54/55	55/55	51/53	54/54	
	Indoor(Cooling/Heating)	High	60/62	65/69	65/70	-	65/67	-	
	Outdoor(Cooling/Heating)	High	67/70	68/69	69/70	-	67/69	-	
Airflow Rate	Indoor / Outdoor	High	m³/h 1100/2470	1900/3600	1900/3800	2100/6750	1800/6200	2100/6750	
Static pressure range (Standard)			Pa	30 to 150 (35)	30 to 150 (47)	30 to 150 (47)	30 to 150 (60)	30 to 150 (47)	30 to 150 (60)
Net Dimensions H x W x D	Indoor	mm	270×1135×700	270×1135×700	270×1135×700	270×1135×700	270×1135×700	270×1135×700	
		kg(lbs)	38 (84)	40 (88)	40 (88)	40 (88)	40 (88)	40 (88)	
Weight	Outdoor	mm	578×790×315	830×900×330	830×900×330	1290×900×330	1290×900×330	1290×900×330	
		kg(lbs)	44 (97)	61 (134)	61 (134)	86 (190)	104 (229)	104 (229)	
Connection Pipe Diameter (Liquid / Gas)			mm	6.35/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	
Drain hose Diameter (I.D./O.D.)			mm	35.7/38.1	35.7/38.1	35.7/38.1	35.7/38.1	35.7/38.1	
Max Pipe Length (Pre-Charge)			m	30 (15)	50 (20)	50 (20)	50 (20)	75 (30)	75 (30)
Max Height Difference				20	30	30	30	30	30
Operation Range	Cooling	°CDB	-10 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	
	Charge		g	1,700	2,100	2,100	3,350	3,450	3,450


Optional parts

Wired Remote Controller:	UTY-RNNYM, UTY-RVNYM	Long Life Filter:	UTD-LF25NA
Simple Remote Controller:	UTY-RSNYM	Remote Sensor Unit:	UTY-XS2X
Flange (Round):	UTD-RF204	Drain Pump Unit:	UTZ-PX1NBA
Flange (Square):	UTD-SF045T	IR Receiver Kit:	UTY-LRHYM




Dimensions

(Unit : mm)




NEW Medium Static Pressure Duct Compact & Comfort



Features

High Efficiency & Quiet operation

The combination of the V-shaped heat exchanger, air stabilizer, and the high efficient DC fan motor allowed high efficiency and quiet operation despite of the small structural design.




Automatic Airflow adjustment function

This unique and innovative function detects required air flow in each application case and automatically adjust the volume.



Improved installation flexibility


- Capable to be installed in various applications that requires static pressure of 30Pa to 200 Pa
- Built-in drain pump, rises drain up to 850 mm
- Unified depth throughout the range enables the selection of the capacity regardless of the additional space.



Improved service and maintenance

- Drain pump is easily detachable from the side
- Easy access to electrical box
- Error code can be checked more in detail from error history

Low ambient operation



Model: ARYG12LHTBP / ARYG14LHTBP / ARYG18LHTBP / ARYG24LHTBP
ARYG30LHTBP / ARYG36LHTBP / ARYG45LHTBP / ARYG54LHTBP




Specifications

Model No.	Indoor unit	ARYG12LHTBP	ARYG14LHTBP	ARYG18LHTBP	ARYG24LHTBP	ARYG30LHTBP	ARYG36LHTBP	ARYG45LHTBP	ARYG54LHTBP
	Outdoor unit	AOYG12LBLA	AOYG14LBLA	AOYG18LBCA	AOYG24LBCA	AOYG30LBTB	AOYG36LBTB	AOYG45LBTB	AOYG54LBTB
Power Source		Single-phase, ~230V, 50Hz							
Capacity	Cooling	3.5 (0.9-4.4)	4.3 (0.9-5.4)	5.2 (0.9-6.5)	6.8 (0.9-8.0)	8.5 (2.8-10.0)	9.4 (2.8-11.2)	12.1 (4.0-14.0)	13.4 (4.5-14.5)
	Heating	4.1 (0.9-5.7)	5.0 (0.9-6.5)	6.0 (0.9-8.0)	8.0 (0.9-9.1)	10.0 (2.7-11.2)	11.2 (2.7-12.7)	13.3 (4.2-16.2)	16.0 (4.7-16.5)
Input Power	Cooling/Heating	0.90/1.00	1.18/1.25	1.37/1.48	1.95/2.21	2.65/2.70	2.83/3.07	3.59/3.44	4.42/4.62
		3.89	3.64	3.80	3.49	3.21	3.32	3.37	3.03
EER	Cooling	4.10	4.00	4.05	3.62	3.70	3.65	3.87	3.46
	Heating	3.5/4.2	4.3/4.5	5.2/4.3	6.8/6.0	8.5/8.0	9.4/8.7	-	-
Pdesign	Cooling/Heating (-10°C)	6.20	6.10	7.15	6.50	5.95	5.81	-	-
		4.10	4.00	4.11	4.01	3.95	3.81	-	-
SEER	Cooling	A++	A++	A++	A++	A+	A+	-	-
	Heating (Average)	A+	A+	A+	A+	A	A	-	-
SCOP	Cooling	7.5/10.0	9.0/12.5	10.0/13.5	13.5/18.5	17.0/17.0	20.0/20.0	22.5/22.5	23.5/23.5
	Heating	*	*	255	366	500	566	*	*
Max. Operating Current	Cooling/Heating	A	A	A	A	A	A	A	A
		*	*	1462	2092	2833	3194	*	*
Annual Energy Consumption	Cooling	*	*	1.2	1.8	2.3	2.0	2.6	3.7
	Heating	*	*	1.2	1.8	2.3	2.0	2.6	3.7
Moisture Removal	Indoor (Cooling)	H/M/L/Q	H/M/L/Q	H/M/L/Q	H/M/L/Q	H/M/L/Q	H/M/L/Q	H/M/L/Q	H/M/L/Q
	Indoor (Heating)	H/M/L/Q	H/M/L/Q	H/M/L/Q	H/M/L/Q	H/M/L/Q	H/M/L/Q	H/M/L/Q	H/M/L/Q
Sound Pressure Level	Outdoor(Cooling/Heating)	High	High	High	High	High	High	High	High
		47/48	49/49	50/51	55/56	53/55	54/55	55/55	55/57
Sound Power Level	Indoor(Cooling/Heating)	High	High	High	High	High	High	High	High
		60/61	64/63	63/62	68/68	68/69	69/70	68/68	69/71
Airflow Rate (High)	Indoor / Outdoor	High	High	High	High	High	High	High	High
		850/1780	950/1910	1050/ 1900	1360/ 2460	1700/ 3600	2050/ 3800	2550/ 6750	2550/ 6750
Static pressure range (Standard)		Pa	Pa	Pa	Pa	Pa	Pa	Pa	Pa
		30 to 200 (35)	30 to 200 (35)	30 to 200 (35)	30 to 200 (35)	30 to 200 (47)	30 to 200 (47)	30 to 200 (60)	30 to 200 (60)
Net Dimensions	Indoor	mm	mm	mm	mm	mm	mm	mm	mm
		300×700×700	300×700×700	300×1000×700	300×1000×700	300×1000×700	300×1400×700	300×1400×700	300×1400×700
H x W x D	Outdoor	kg(lbs)	kg(lbs)	kg(lbs)	kg(lbs)	kg(lbs)	kg(lbs)	kg(lbs)	kg(lbs)
		27 (59)	27 (59)	36 (79)	36 (79)	36 (79)	46 (101)	46 (101)	46 (101)
Weight		mm	mm	mm	mm	mm	mm	mm	mm
		578×790×300	578×790×300	620×790×290	620×790×290	830×900×330	830×900×330	1290×900×330	1290×900×330
Connection Pipe Diameter (Liquid / Gas)		kg(lbs)	kg(lbs)	kg(lbs)	kg(lbs)	kg(lbs)	kg(lbs)	kg(lbs)	kg(lbs)
		40 (88)	40 (88)	41 (90)	41 (90)	61 (134)	61 (134)	86 (189)	86 (189)
Drain hose Diameter (I.D./O.D.)		mm	mm	mm	mm	mm	mm	mm	mm
		6.35/9.52	6.35/12.70	6.35/12.70	6.35/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Max Pipe Length (Pre-Charge)		mm	mm	mm	mm	mm	mm	mm	mm
		25/32	25/32	25/32	25/32	25/32	25/32	25/32	25/32
Max Height Difference		m	m	m	m	m	m	m	m
		25 (15)	25 (15)	30 (15)	30 (15)	50 (20)	50 (20)	50 (20)	50 (20)
Operation Range		°CDB	°CDB	°CDB	°CDB	°CDB	°CDB	°CDB	°CDB
		-10 to 46	-10 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
Refrigerant	Cooling	g	g	g	g	g	g	g	g
		-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Charge	Type (Global Warming Potential)	g	g	g	g	g	g	g	g
		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)

*:That specification is not fixed yet.


Optional parts

Wired Remote Controller:	UTY-RNRYZ1,UTY-RVNYM,UTY-RNNYM,UTY-RLRY	Long life filter:	UTD-LFNA (for ARYG36/45/54LHTBP)
Simple Remote Controller:	UTY-RSNYM		UTD-LFNB (for ARYG24/30LHTBP)
IR Receiver Unit :	UTY-LBTYM		UTD-LFNC (for ARYG12/14LHTBP)
External input and output PCB (with bracket):	UTY-XCSX + UTZ-GXNA	Remote Sensor Unit:	UTY-XSZX
External connect kit:	UTY-XWZXZG, UTY-XWZXZ3		



Dimensions

(Unit : mm)



	ARYG12/14LHTBP	ARYG18/24/30LHTBP	ARYG36/45/54LHTBP
A	700	1,000	1,400
B	462	762	1,162
C	650	895	1,295
D	740	1,040	1,440

High Static Pressure Duct




Features

High energy efficiency


Significantly greater efficiency is realized by using all DC inverter technology. (60 type)

Design also corresponding to high static pressure




Easy installation
(Compact size & Lightweight)

A compact size and lightweight indoor unit has been developed by reducing the basic chassis and the overall material weight.




Low noise

Cutting off the corners has enabled less turbulent airflow. Low noise is realized by adopting a plastic case and a plastic fan.



Low ambient operation



Model : ARYG45LHTA / ARYG54LHTA /
ARYG45LHTA [3phase] / ARYG54LHTA [3phase] / ARYG60LHTA [3phase]



Wired R.C.



ARYG45/54LHTA



ARYG60LHTA



Specifications


Model No.	Indoor unit		ARYG45LHTA	ARYG54LHTA	ARYG45LHTA	ARYG54LHTA	ARYG60LHTA
	Outdoor unit		AOYG45LETL	AOYG54LETL	AOYG45LATT	AOYG54LATT	AOYG60LATT
Power Source			Single-phase, ~230V, 50Hz		3-phase, ~400V, 50Hz		
Capacity	Cooling	kW	12.5 (4.5-14.0)	13.4 (5.0-14.5)	12.5 (5.0-14.0)	14.0 (5.4-16.0)	15.0 (6.2-17.5)
	Heating		14.0 (5.0-16.2)	16.0 (5.5-18.0)	14.0 (5.4-16.2)	16.0 (5.8-18.0)	18.0 (6.2-20.0)
Input Power	Cooling/Heating	kW	4.30/3.80	4.77/4.69	4.06/3.67	4.65/4.37	4.70/5.15
EER	Cooling	W/W	2.91	2.81	3.08	3.01	3.19
COP	Heating		3.68	3.41	3.81	3.66	3.50
Max. Operating Current	Cooling/Heating	A	22.5/22.5	23.5/23.5	11.0/11.0	12.0/12.0	12.5/12.5
Moisture Removal		l/h	1.5	2.0	1.5	2.5	2.0
Sound Pressure	Indoor (Cooling)	H/M/L/Q	47/43/40/-	47/43/40/-	47/43/40/-	47/43/40/-	45/40/36/-
	Indoor (Heating)	H/M/L/Q	47/43/40/-	47/43/40/-	47/43/40/-	47/43/40/-	45/40/36/-
	Outdoor(Cooling/Heating)	High	55/55	55/57	54/54	55/56	56/58
Airflow Rate	Indoor / Outdoor	High	m³/h	3350/6750	3350/6750	3350/6900	3350/6900
Static pressure range	Standard	Pa	100 to 250 (100)	100 to 250 (100)	100 to 250 (100)	100 to 250 (100)	60 to 260 (60)
Net Dimensions	Indoor	mm	400×1050×500	400×1050×500	400×1050×500	400×1050×500	425×1250×490
H x W x D		kg(lbs)	46 (101)	46 (101)	46 (101)	46 (101)	54 (119)
Weight		mm	1290×900×330	1290×900×330	1290×900×330	1290×900×330	1290×900×330
Connection Pipe Diameter (Liquid / Gas)	Outdoor	kg(lbs)	86 (189)	86 (189)	104 (229)	104 (229)	104 (229)
		mm	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Drain hose Diameter (I.D./O.D.)		mm	23.4/25.4	23.4/25.4	23.4/25.4	23.4/25.4	23.4/25.4
Max Pipe Length (Pre-Charge)		m	50 (20)	50 (20)	75 (30)	75 (30)	75 (30)
Max Height Difference			30	30	30	30	30
Operation Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	g	3,350	3,350	3,450	3,450	3,450

Optional parts

- Wired Remote Controller: UTY-RNNYM, UTY-RVNYM
Simple Remote Controller: UTY-RSNNYM
Long-Life Filter: UTD-LF60KA (For ARYG45/54LHTA only)
Remote Sensor Unit: UTY-XSZX
IR Receiver Kit: UTY-LRHYM(For ARYG60LHTA only)

Dimensions

(Unit : mm)




High Static Pressure Duct



Features


High energy efficiency

Significantly greater efficiency is realized by using DC twin rotary compressor, all DC inverter technology, and large heat exchanger.



5 Static Pressure selection

Improvement and design flexibility has allowed multiple fan speeds and static pressure modes. Low noise is realized by adopting plastic case, plastic fan.




Outdoor unit quiet operation

A low outdoor noise operation mode allows the outdoor unit to have two quiet mode operation settings.

Peak cut operation

A peak power consumption mode controls a 4 step outdoor operation control to cut down energy usage at peak energy usage times.

Low ambient operation



Model : ARYC72LHTA [3phase] / ARYC90LHTA [3phase]



Wired R.C.



ARYC72LHTA



ARYC90LHTA



Specifications

Model No.	Indoor unit		ARYC72LHTA		ARYC90LHTA	
	Outdoor unit		AOYA72LALT		AOYA90LALT	
Power Source			3-phase, ~400V, 50Hz			
Capacity	Cooling	kW	20.3 (10.8-23.5)		25.0 (11.2-28.0)	
	Heating		22.6 (12.0-26.5)		28.0 (12.5-31.5)	
Input Power	Cooling/Heating	kW	6.25/6.27		7.82/8.24	
EER	Cooling	W/W	3.25		3.20	
COP	Heating		3.60		3.40	
Max. Operating Current	Cooling/Heating	A	22.8/22.8		25.8/25.8	
Moisture Removal		l/h	4.5		6.0	
Sound Pressure	Indoor (Cooling)	H/M/L/Q	47/44/41/-		49/46/43/-	
	Indoor (Heating)	H/M/L/Q	47/44/41/-		49/46/43/-	
	Outdoor(Cooling/Heating)	High	57/57		58/59	
Airflow Rate	Indoor / Outdoor	High	m³/h 4300/9300		4850/10700	
Static pressure range (Standard)		Pa	50 to 250 (72)		50 to 250 (72)	
Net Dimensions H x W x D Weight	Indoor	mm	450×1587×700		550×1587×700	
		kg(lbs)	100 (220)		110 (242)	
	Outdoor	mm	1690×930×765		1690×930×765	
		kg(lbs)	215 (473)		215 (473)	
Connection Pipe Diameter (Liquid / Gas)		mm	12.70/25.40		12.70/25.40	
Drain Hose Diameter (I.D./O.D.)			35.7/38.1		35.7/38.1	
Max Pipe Length (Pre-Charge)		m	75 (20)		75 (20)	
Height Difference			30		30	
Operation Range	Cooling	°CDB	-5 to 46		-5 to 46	
	Heating		-15 to 24		-15 to 24	
Refrigerant	Type (Global Warming Potential)		R410A (2,088)		R410A (2,088)	
	Charge		g 11,200		11,200	

Optional parts



Wired Remote Controller: UTY-RNNYM, UTY-RVNYM

Simple Remote Controller: UTY-RSNYM

Remote Sensor Unit: UTY-XSZX

Dimensions

(Unit : mm)



MULTI SPLIT



Control several indoor units
with one outdoor unit.
Build the optimum system you desire.





If you want to keep a large floor as well as many rooms comfortable, we recommend you use Multi Split to build a simple system using one outdoor unit. Choose from a large lineup of indoor units that best matches your rooms. You can mix and match them at will. Build the system that is just right for you.

Multi Split provides comfort in
a variety of situations

from home to
office and store.

- 092 2-8 Rooms Multi type Lineup
- 094 2 & 3-4 Rooms Multi
- 096 8 Rooms Multi
- 100 Specifications of All Indoor Units
- 102 Simultaneous Multi Twin/Triple
- 104 Multi Combination Table
- 114 Optional Parts for Split & Multi Split

2-8 Rooms Multi Type Lineup

		Indoor unit					
Model No.		14	18		24	30	45
Cooling rated capacity(kW)		4	5	5.4	6.8	8	14
2 Rooms Multi Up to 2 units	 Outdoor unit	● AOYG14LAC2	● AOYG18LAC2				
3 Rooms Multi Up to 3 units	 Outdoor unit			● AOYG18LAT3	● AOYG24LAT3		
4 Rooms Multi Up to 4 units	 Outdoor unit					● AOYG30LAT4	
8 Rooms Multi Up to 8 units	 Outdoor unit						● AOYG45LBT8



Note : 1. 2 Rooms Multi : Connectable indoor units are 2 units.
AOYG14LAC2: Total capacity of indoor units connected must be between 4.0 kW and 6.2 kW.
AOYG18LAC2: Total capacity of indoor units connected must be between 4.0 kW and 7.0 kW.

2. 3 Rooms Multi : Connectable indoor units are 2 to 3 units.
AOYG18LAT3: Total capacity of indoor units connected must be between 4.0 kW and 8.5 kW.
AOYG24LAT3: Total capacity of indoor units connected must be between 4.0 kW and 10.5 kW.

3. 4 Rooms Multi : Connectable indoor units are 3 to 4 units.
AOYG30LAT4: Total capacity of indoor units connected must be between 7.9 kW and 14.4 kW.

4. 8 Rooms Multi : Connectable indoor units are 2 to 8 units.
AOYG45LBT8: Total capacity of indoor units connected must be between 11.2 kW and 18.2 kW.

Connectable Indoor unit line-up

Outdoor Unit	Type		2 Rooms		3 Rooms		4 Rooms	8 Rooms
	Model name		AOYG14LAC2	AOYG18LAC2	AOYG18LAT3	AOYG24LAT3	AOYG30LAT4	AOYG45LBT8
								
	Capacity (kW)	Heating Cooling	4.0 4.4	5.0 5.6	5.4 6.8	6.8 8.0	8.0 9.6	14.0 16.0
Indoor Unit		BTU	kW Class					
 ASYG07/09/12/14LM	7000	2.0	●	●	●	●	●	●
	9000	2.5	●	●	●	●	●	●
 ASYG07/09/12/14LU	12000	3.5	●	●	●	●	●	●
	14000	4.0	—	●	●	●	●	●
 ASYG18/24LF	18000	5.0	—	—	—	●	●	●
	24000	7.0	—	—	—	—	●	●
 AGYG09/12/14LV	9000	2.5	—	●	●	●	●	●
	12000	3.5	—	●	●	●	●	●
	14000	4.0	—	—	●	●	●	●
 AUYG07/09/12/14/18LV	7000	2.0	—	●	●	●	●	●
	9000	2.5	—	●	●	●	●	●
	12000	3.5	—	●	●	●	●	●
	14000	4.0	—	—	●	●	●	●
	18000	5.0	—	—	—	●	●	●
 ABYG14/18LV	14000	4.0	—	—	●	●	●	●
	18000	5.0	—	—	—	●	●	●
 ARYG07/09/12/14/18LL	7000	2.0	—	●	●	●	●	●
	9000	2.5	—	●	●	●	●	●
	12000	3.5	—	●	●	●	●	●
	14000	4.0	—	—	●	●	●	●
	18000	5.0	—	—	—	●	●	●

Indoor unit features

	Economy	Powerful	HEAT	Auto Changeover	Up/Down	Double	Adjust	Restart	Dust	Intake	Sleep	Program	Weekly	+Setback	Filter	ION	AF	Washable
ASYG07/09/12/14LM	●	●	●	●	●		●	●			●	●		○	●	●	●	●
ASYG07/09/12/14LU	●		●	●	●		●	●			●	●	●	○	●	●	●	●
ASYG18/24LF	●	●	●			●	●	●			●	●		○	●	●	●	●
AGYG09/12/14LV	●		●	●	●		●	●			●	●		○	●	●	●	●
AUYG07/09/12/14/18LV	●		●	●	●		●	●	○	○	●	●		○	●			
ABYG14/18LV	●		●	●		●	●	●		○	●	●		○	●			
ARYG07/09/12/14/18LL	●		○	●	○		●	●		○	○	○		●	●			

○: Optional function


2 & 3-4 Rooms Multi



Features

Wide range of indoor units with various models

7 types 25 models are lined up in the capacity range from 2 kW to 7 kW class. Wide range of needs can be met from rooms of private homes to large shops and hotels.



Space-saving installation

Multiple indoor units can be connected to 1 outdoor unit, and long piping connection is also possible. Compared with single type, the outdoor unit can be installed in various places to realize the space-saving installation.



Flexible installation

Up to max. piping length of 70 m (AOYG30LAT4), max. height difference of 15 m can be supported. Multi type can be installed at large-size residence or buildings with multiple floors.

Max. Piping Length (Each Unit):
20 m (AOYG14LAC2 / 18LAC2),
25 m (AOYG18LAT3 / 24LAT3 / 30LAT4)

Max. Height:
15 m (AOYG14LAC2/18LAC2/18LAT3/24LAT3/30LAT4)

Total Piping Length:
30 m (AOYG14LAC2 / 18LAC2),
50 m (AOYG18LAT3 / 24LAT3),
70 m (AOYG30LAT4)



2 Rooms: AOYG14LAC2 / AOYG18LAC2
3 Rooms: AOYG18LAT3 / AOYG24LAT3
4 Rooms: AOYG30LAT4




Specifications (2 ROOMS, 3 ROOMS, 4 ROOMS)

Model No.	Outdoor unit		AOYG14LAC2	AOYG18LAC2	AOYG18LAT3	AOYG24LAT3	AOYG30LAT4
Power Source			Single-phase, ~230V, 50Hz				
Rated Capacity (min-max)	Cooling	kW	4.0 (1.4-4.4)	5.0 (1.7-5.6)	5.4 (1.8-6.8)	6.8 (1.8-8.5)	8.0 (3.5-10.1)
	Heating		4.4 (1.1-5.4)	5.6 (1.8-6.1)	6.8 (2.0-8.0)	8.0 (2.0-8.8)	9.6 (3.7-12.0)
EER	Cooling	W/W	3.67	3.21	4.00	3.51	3.60
COP	Heating		4.27	3.97	4.20	4.00	4.00
Sound Pressure Level (High)	Cooling	dB(A)	47	50	46	48	50
	Heating		49	51	47	49	51
Sound Power Level (High)	Cooling		61	63	65	68	68
	Heating		63	64	67	70	70
Net Dimensions H × W × D		mm	540×790×290	540×790×290	700×900×330	700×900×330	830×900×330
Weight		kg(lbs)	37 (82)	38 (84)	55 (121)	55 (121)	68 (150)
Connection Pipe Diameter	Liquid	mm	Ø6.35×2	Ø6.35×2	Ø6.35×3	Ø6.35×3	Ø6.35×4 (*Ø6.35×3, Ø9.52)
	Gas		9.52 × 2	9.52 × 2 (*9.52, 12.7)	9.52 × 2, 12.7 (*9.52 × 3)	9.52 × 2, 12.7 (*9.52 × 3)	9.52 × 2, 12.7 × 2 (*9.52 × 3, 12.7) (*9.52 × 2, 12.7, 15.88)
Max. Pipe Length		Total / Each	30 / 20	30 / 20	50 / 25	50 / 25	70 / 25
Max. Height Difference	Between Outdoor Unit and Each Indoor Units.	m	15	15	15	15	15
	Between Indoor Units.		10	10	10	10	10
Operation Range	Cooling	°CDB	10 to 46	10 to 46	-10 to 46	-10 to 46	0 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	-10 to 24
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	g	1,250	1,300	2,200	2,200	3,300

* Connect to connection valve by the adapter.

Dimensions

(Unit : mm)




8 Rooms Multi



Features


Compact outdoor unit

The compact design outdoor unit allows to be installed below a window and in a narrow space.



High seasonal efficiency

The actual performance is conducted under various outside temperatures depending on weather and seasons, furthermore, especially for multi system, not all the rooms are operated all the time. So over 90% of actual operation time, air conditioners are operated at partial capacity instead of rated capacity. Considering these, we focused on energy-saving performance which is based on actual use. Efficiency of part load performance was drastically improved by developing ALL DC and our own inverter system.



Innovated technology



High efficiency large fan:
New high efficiency fan is mounted.



DC fan motor:
High performance and high efficiency has been realized by using a small DC fan motor.




Heat exchanger:
Reduced compact size and energy saving has been realized by utilizing high density piping design and 3-Row heat exchanger.



High efficiency DC twin rotary compressor:
A high performance, low noise, large capacity DC twin rotary compressor is used.

Quick comfort by optimized refrigerant control

Every room meets the set point most quickly and comfortably by optimized refrigerant control.



Central Remote Controller Option

Max. Controllable
1 multi system

Max. Controllable
8 indoor units

Central remote controller developed for residential applications. All indoor units can be batched controlled using simple operations. Schedule management and other functions can be used to achieve even greater energy savings.



Central & Individual Control

Batched control of up to 8 indoor units. The temperature, airflow volume, and remote control prohibition settings of all indoor units can be batched.


Multiple language support

Corresponds to 9 different languages (English, German, French, Spanish, Russian, Portuguese, Italian, Greek, and Turkish)

Easy-To-Use operation

- Large backlight LED screen
- Large easy-to-see operation panel


System configuration



Central Remote Controller Functions

Weekly schedule timer

The ON/OFF setting can be set for 4 times a day. Two weekly patterns can be set to match the cooling and heating seasons.



Low noise operation

Users can choose from 4 low noise levels, depending on the installation environment. The operation time can be set using the timer.

10°C heat operation


When you leave, minimum heating operation is performed to maintain the room temperature (maintain at 10°C).

Economy operation

Economy operation is energy saving, as the set temperature of indoor unit is shifted by 1°C and the maximum electric value of the outdoor unit is suppressed.


Prohibited Settings

The remote controller operation of all indoor units comes with a lock function to prevent unapproved operations in the various rooms. The central remote controller also has a key lock function to prevent children from playing with it, etc





Large capacity connection

Up to 8 indoor units can be connected to one outdoor unit.
A maximum of 130% indoor unit connectable capacity.
Match any room layout.




Long piping design

Can be installed in high rise condominiums or commercial buildings.




Branch Box can be mounted flexibly.


Allowed Branch Box Mounting Direction



Hanging from the ceiling
Do not hang from the ceiling when performing a vertical installation.



Horizontal Wall Mounting
Install the unit with its top side facing upwards.



Vertical Wall Mounting
Install the unit with the control box facing upwards.

8 Rooms: AOYG45LBT8



Specifications

Model Name			AOYG45LBT8	
Maximum Connectable Indoor Unit			8	
Indoor Unit Connectable Capacit	Cooling	kW	11.2 - 18.2	
Power source			Single-phase, ~230V, 50Hz	
Rated Capacity	Cooling	kW	14.0	
	Heating		16.0	
Input Power	Cooling	kW	5.20	
	Heating		5.07	
Airflow rate	Cooling	m³/h	4,650	
	Heating		4,800	
Sound Pressure Level	Cooling	dB(A)	56	
	Heating		58	
Heat Exchanger Fin			Plate fin coil	
Net Dimensions H × W × D		mm	914 ×970×370	
Weight		kg(lbs)	98 (217)	
Connection Pipe Diameter (Liquid / Gas)		mm	9.52/15.88	
Max Pipe Length		m	115 (Total)	
Max Height Difference (O.U ~ I.U)			30	
Operating Range	Cooling	°CDB	-5 to 46	
	Heating		-15 to 24	
Refrigerant	Type (Global Warming Potential)	g	R410A (2,088)	
	Charge		3,450	


Model Name			UTP-PY03A	UTP-PY02A
Connectable Indoor Unit			1 to 3 Units	1 to 2 Units
Power source			230/1/50	230/1/50
Available Voltage Range			198-264V	198-264V
Power Consumption		W	10	10
Running Current		A	0.05	0.05
Net Dimensions H × W × D		mm	195×433×370	195×433×370
Weight		kg(lbs)	9 (20)	9 (20)
Connection pipe diameter	Liquid	°CDB	Main: 9.52×1, Branch: 6.35×3	Main: 9.52×1, Branch: 6.35×2
	Gas		Main: 15.88×1, Branch: 12.7×3	Main: 15.88×1, Branch: 12.7×2
		Method	Flare	Flare

Note: Specifications are based on the following conditions.
• In case of connecting two indoor units(7 kW class).
• These are the measured values in the manufacturer's anechoic chamber.
• Cooling: Indoor temp. of 27°CDB/19°CWB, outdoor temp. of 35°CDB/24°CWB Heating: Indoor temp. of 20°CDB/15°CWB, outdoor temp. of 7°CDB/6°CWB
Pipe length: 5m (Outdoor unit - Branch box), 3m (Branch box - Indoor unit) Height difference : 0m


Dimensions

(Unit : mm)


Outdoor Unit:
AOYG45LBT8



Branch Box :
UTP-PY03A (3 branches type)



Branch Box :
UTP-PY02A (2 branches type)



Specifications of All Indoor Units

Compact wall mounted



Model No.	Indoor unit			ASYG07LUCA	ASYG09LUCA	ASYG12LUCA	ASYG14LUCA
kW Class		kW		2.0	2.5	3.5	4.0
Power Source				Single-phase, ~230V, 50Hz			
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	35/30/28/21	36/32/28/21	37/34/31/21	41/36/33/25
	Heating			35/30/28/21	36/32/28/21	37/34/31/21	41/36/34/27
Sound Power Level	Cooling	H	dB(A)	53	54	55	59
	Heating			53	54	55	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	570/520/470/330	600/550/470/330	660/600/530/330	710/640/570/390
	Heating			570/520/470/330	600/550/470/330	660/600/530/330	710/640/590/430
Net Dimensions			mm	282×870×185	282×870×185	282×870×185	282×870×185
Weight			9.5 (21) kg(lbs)	9.5 (21)	9.5 (21)	9.5 (21)	9.5 (21)
Connection Pipe Diameter		Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.7

Floor ceiling



Model No.	Indoor unit			ABYG14LVTA	ABYG14LUCA
kW Class		kW		4.0	5.0
Power Source				Single-phase, ~230V, 50Hz	
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	36/34/33/29 (Under ceiling) 39/37/36/32 (Floor console)	41/38/34/32 (Under ceiling) 44/41/37/35 (Floor console)
	Heating			36/34/33/29 (Under ceiling) 39/37/36/32 (Floor console)	41/38/34/32 (Under ceiling) 44/41/37/35 (Floor console)
Sound Power Level	Cooling	H	dB(A)	51	55
	Heating			51	55
Airflow Rate	Cooling	H/M/L/Q	m³/h	640/590/540/480	780/700/560/500
	Heating			640/590/540/480	780/700/560/500
Net Dimensions			mm	199×990×655	
Weight			kg(lbs)	27 (60)	
Connection Pipe Diameter		Liquid/Gas	mm	6.35/12.7	

Wall mounted



Model No.	Indoor unit			ASYG07LMCA	ASYG09LMCA	ASYG12LMCA	ASYG14LMCA	ASYG18LFCA	ASYG24LFCC
kW Class		kW		2.0	2.5	3.5	4.0	5.0	7.0
Power Source				Single-phase, ~230V, 50Hz					
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	36/32/29/21	37/33/29/21	40/36/30/21	42/38/33/25	43/37/33/26	49/42/37/33
	Heating			36/32/29/22	37/33/29/22	40/36/31/22	42/38/35/27	42/37/33/25	48/42/37/33
Sound Power Level	Cooling	H	dB(A)	51	52	54	56	58	64
	Heating			51	52	55	57	58	64
Airflow Rate	Cooling	H/M/L/Q	m³/h	560/500/430/310	600/520/430/310	660/560/450/310	730/600/530/360	900/740/620/550	1120/900/740/620
	Heating			560/500/430/330	600/520/430/330	660/560/470/330	730/615/560/375	900/740/620/550	1100/900/740/620
Net Dimensions			mm	268×840×203	268×840×203	268×840×203	268×840×203	320×998×238	320×998×238
Weight			kg(lbs)	8.5 (19)	8.5 (19)	8.5 (19)	8.5 (19)	14 (30.8)	14 (30.8)
Connection Pipe Diameter		Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.7	6.35/12.7	Ø6.35/Ø15.88

Compact cassette



Model No.	Indoor unit			AUYG07LVLA	AUYG09LVLA	AUYG12LVLB	AUYG14LVLB	AUYG18LVLB
kW Class		kW		2.0	2.5	3.5	4.0	5.0
Power Source				Single-phase, ~230V, 50Hz				
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	33/31/29/27	33/31/29/27	37/33/31/28	40/35/32/29	42/37/33/29
	Heating			34/32/29/27	34/32/29/27	37/33/31/28	40/37/34/29	44/40/37/30
Sound Power Level	Cooling	H	dB(A)	46	46	49	52	54
	Heating			47	47	49	52	56
Airflow Rate	Cooling	H/M/L/Q	m³/h	540/490/440/390	540/490/440/390	610/530/470/410	680/580/490/410	750/610/520/410
	Heating			540/490/440/390	540/490/440/390	610/530/470/410	700/620/550/430	800/710/600/450
Net Dimensions			mm	245×570×570	245×570×570	245×570×570	245×570×570	245×570×570
Weight			kg(lbs)	15 (33.1)	15 (33.1)	15 (33.1)	15 (33.1)	15 (33.1)
Panel				UTG-UFYD-W				
Connection Pipe Diameter		Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.7	6.35/12.7

Floor



Model No.	Indoor unit			AGYG09LVCA	AGYG12LVCA	AGYG14LVCA
kW Class		kW		2.5	3.5	4.0
Power Source				Single-phase, ~230V, 50Hz		
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	39/34/28/22	42/36/30/22	44/38/31/22
	Heating			39/35/30/22	42/38/32/22	44/39/33/22
Sound Power Level	Cooling	H	dB(A)	52	55	56
	Heating			52	55	56
Airflow Rate	Cooling	H/M/L/Q	m³/h	530/440/360/270	600/490/380/270	650/520/400/270
	Heating			530/460/380/270	600/510/410/270	650/540/430/270
Net Dimensions			mm	600×740×200	600×740×200	600×740×200
Weight			kg(lbs)	14 (30.7)	14 (30.7)	14 (30.7)
Connection Pipe Diameter		Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/12.7

Slim duct



Model No.	Indoor unit			ARYG07LLTA	ARYG09LLTA	ARYG12LLTB	ARYG14LLTB	ARYG18LLTB
kW Class		kW		2.0	2.5	3.5	4.0	5.0
Power Source				Single-phase, ~230V, 50Hz				
Sound Pressure Level	Cooling	H/M/L/Q	dB(A)	28/26/25/24	28/27/26/25	29/28/27/26	32/30/28/26	32/31/30/29
	Heating			28/26/25/24	28/26/25/24	29/28/27/24	33/30/28/25	33/32/31/29
Sound Power Level	Cooling	H	dB(A)	57	57	58	60	58
	Heating			57	57	58	61	59
Airflow Rate	Cooling	H/M/L/Q	m³/h	550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750
	Heating			550/490/470/440	600/550/500/450	650/600/550/480	800/700/600/480	940/880/820/750
Net Dimensions			mm	198×700×620	198×700×620	198×700×620	198×700×620	198×900×620
Weight			kg(lbs)	17 (37.5)	19 (41.8)	19 (41.8)	19 (41.8)	23 (50.6)
Connection Pipe Diameter		Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.7	6.35/12.7
External static pressure				0 to 90				
Drain pump				Standard				

Simultaneous Multi Twin / Triple


ALL
DC

Features


Can support various installation scenes from office to commercial space by same place multi connection of up to 3 units.

Indoor units distributed layout according to the shape and number of people and lighting conditions of the room even on wide floors and atypical floors. Ideal comfortable air flow distribution can be realized.


Installation according to floor layout



Installation according to lighting conditions




Installation according to layout and lighting conditions



Simultaneous control

Max 16 indoor units are simultaneously controlled with a wired remote controller.



Simultaneous Operation Multi type Indoor Unit Line up

	Twin			Triple
	18x2	22x2	24x2	18x3
Cassette	AUYG18LV×2	AUYG22LV×2	AUYG24LV×2	AUYG18LV×3
Duct	ARYG18LL×2	ARYG22LM×2	ARYG24LM×2	ARYG18LL×3
Ceiling	ABYG18LV×2	ABYG22LV×2	ABYG24LV×2	ABYG18LV×3
Outdoor unit	AOYG36LBTB / AOYG36LATT	AOYG45LBTB / AOYG45LATT	AOYG54LBTB / AOYG54LATT	

Model : AOYG36LBTB / AOYG45LBTB / AOYG54LBTB **NEW**
AOYG36LATT [3phase] / AOYG45LATT [3phase] / AOYG54LATT [3phase]



Specifications

Model No.	Indoor unit		Compact Cassette		
			AUYG18VLVB	AUYG22LVLA	AUYG24LVLA
Power Source			Single-phase, ~230V, 50Hz		
Airflow Rate (High)	Cooling	H/M/L/Q	m³/h	680/580/490/410	930/830/600/450
Net Dimension H × W × D			mm	245×570×570	245×570×570
Weight			kg (lbs)	15 (33)	16 (35)
Cassette Grille				UTG-UFYD-W	UTG-UFYD-W

Model No.	Indoor unit		Duct			Floor/Ceiling Universal		
			ARYG18LLTB	ARYG22LMVA	ARYG24LMVA	ABYG18LVTB	ABYG22LVTVA	ABYG24LVTVA
Power Source			Single-phase, ~230V, 50Hz			Single-phase, ~230V, 50Hz		
Airflow Rate (High)	Cooling	H/M/L/Q	m³/h	1100/910/750/580	1100/910/750/580	780/700/560/500	980/820/680/540	
Net Dimension H × W × D			mm	270 × 1135 × 700	270 × 1135 × 700	199 × 990 × 655	199 × 990 × 655	
Weight			kg (lbs)	38 (84)	38 (84)	27 (60)	27 (60)	


Model No.	Outdoor unit		AOYG36LBTB	AOYG45LBTB	AOYG54LBTB	AOYG36LATT	AOYG45LATT	AOYG54LATT
Capacity	Cooling	kW	10.0	12.1	13.3	10.0	12.5	14.0
	Heating		11.2	14.0	15.0	11.2	14.0	16.0
Power Source			Single-phase, ~230V, 50Hz			3-phase, ~400V, 50Hz		
Pdesign	Cooling	kW	10.0	-	-	10.0	-	-
	Heating (-10°C)		10.0	-	-	10.0	-	-
SEER	Cooling	W/W	5.56	-	-	6.00	-	-
SCOP	Heating		3.90	-	-	4.00	-	-
Annual Energy Consumption	Cooling	kWh/a	629	-	-	583	-	-
	Heating		3588	-	-	3499	-	-
Energy Efficiency Class	Cooling	dB(A)	A	-	-	A+	-	-
	Heating		A	-	-	A+	-	-
Sound Pressure Level (High)	Cooling	dB(A)	52	54	55	51	54	55
Sound Power Level (High)	Heating		69	70	72	69	69	71
Net Dimension H × W × D			mm	1290×900×330	1290×900×330	1290×900×330	1290×900×330	1290×900×330
Weight			kg(lbs)	93(205)	93(205)	93(205)	104 (229)	104 (229)
Connection Pipe Diameter (Liquid / Gas)			mm	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88	9.52/15.88
Max Pipe Length (Pre-Charge)			m	75(30)	75(30)	75(30)	75(30)	75(30)
Height Difference				30	30	30	30	30
Operation Range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46
	Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	g	3,450	3,450	3,450	3,450	3,450	3,450
Separation tube			UTP-SX236A(Twin)	UTP-SX254A(Twin)	UTP-SX254A(Twin)/UTP-SX354A(Triple)	UTP-SX236A (Twin)	UTP-SX254A (Twin)	UTP-SX254A (Twin) / UTP-SX354A (Triple)

*Different type and capacity indoor units can not be connected.
*The above table is the value for connecting with cassette type.

Dimensions

(Unit : mm)

Outdoor Unit: AOYG36LBTB / AOYG36LATT / AOYG45LBTB / AOYG45LATT / AOYG54LBTB / AOYG54LATT



Multi Combination Table

2 Rooms Multi cooling

AOYG14LAC2	Combination of Indoor Unit		COOLING OPERATION							
			Cooling Capacity			Input Power (min-max)	EER	Seasonal Data		
			Room 1 kW	Room 2 kW	Total Capacity (min-max) kW			Pdesign kW	SEER	Energy efficiency class
2 Room	7	7	2.00	2.00	4.00 (1.4 - 4.4)	1.09 (0.35 - 1.40)	3.67	4.0	6.7	A++
	7	9	1.95	2.05	4.00 (1.4 - 4.4)	1.09 (0.35 - 1.40)	3.67	4.0	6.6	A++
	7	12	1.65	2.35	4.00 (1.4 - 4.6)	1.05 (0.35 - 1.47)	3.81	4.0	6.5	A++
	9	9	2.00	2.00	4.00 (1.4 - 4.5)	1.09 (0.35 - 1.43)	3.67	4.0	6.6	A++
	9	12	1.70	2.30	4.00 (1.4 - 4.7)	1.05 (0.35 - 1.47)	3.81	4.0	6.5	A++

Note: •7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h models
•The above is the value for connecting with Wall Mounted type.
•2 or more indoor units should be connected.
•Cooling capacity is based on 27°CDB/19°CWB (indoor temperature), 35°CDB (outdoor temperature).
•Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
•The Total ability of connected a indoor unit is up to 21000Btu from 14000Btu.

AOYG18LAC2	Combination of Indoor Unit		COOLING OPERATION							
			Cooling Capacity			Input Power (min-max)	EER	Seasonal Data		
			Room 1	Room 2	Total Capacity (min-max)			Pdesign	SEER	Energy efficiency class
2 Room	7	7	2.10	2.10	4.20 (1.7 - 5.2)	1.24 (0.35 - 1.68)	3.39	4.2	7.0	A++
	7	9	2.10	2.50	4.60 (1.7 - 5.3)	1.26 (0.35 - 1.79)	3.65	4.6	6.8	A++
	7	12	1.90	3.10	5.00 (1.7 - 5.6)	1.55 (0.35 - 1.95)	3.23	5.0	6.5	A++
	7	14	1.80	3.20	5.00 (1.8 - 5.7)	1.55 (0.40 - 1.99)	3.23	5.0	6.5	A++
	9	9	2.50	2.50	5.00 (1.7 - 5.6)	1.56 (0.35 - 1.95)	3.21	5.0	6.6	A++
	9	12	2.10	2.90	5.00 (1.7 - 5.7)	1.55 (0.35 - 1.95)	3.23	5.0	6.5	A++
	9	14	2.00	3.00	5.00 (1.8 - 5.8)	1.55 (0.40 - 1.99)	3.23	5.0	6.4	A++
	12	12	2.50	2.50	5.00 (1.7 - 5.8)	1.56 (0.35 - 1.99)	3.21	5.0	6.4	A++

Note: •7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h / 14:14000Btu/h models
•The above is the value for connecting with Wall Mounted type.
•2 or more indoor units should be connected.
•Cooling capacity is based on 27°CDB/19°CWB (indoor temperature), 35°CDB (outdoor temperature).
•Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
•The Total ability of connected a indoor unit is up to 24000Btu from 14000Btu.
•Where "14" means "wall mounted type" only models. Other types of indoor units can not be connected.

3 Rooms Multi cooling

AOYG18LAT3			Combination of Indoor Unit		COOLING OPERATION								
					Cooling Capacity				Input Power (min-max)	EER	Seasonal Data		
					Room 1	Room 2	Room 3	Total Capacity (min-max)			Pdesign	SEER	Energy efficiency class
					kW	kW	kW	kW			kW		
2 Room	7	7	-	2.30	2.30	-	4.60 (1.8 - 5.0)	1.22 (0.50 - 1.43)	3.77	4.6	6.3	A++	
	7	9	-	2.30	2.70	-	5.00 (1.8 - 5.7)	1.35 (0.50 - 1.81)	3.70	5.0	6.2	A++	
	7	12	-	1.98	3.02	-	5.00 (1.8 - 6.1)	1.34 (0.50 - 2.06)	3.73	5.0	6.2	A++	
	7	14	-	1.88	3.42	-	5.30 (1.8 - 6.6)	1.34 (0.50 - 2.06)	3.96	5.3	6.1	A++	
	9	9	-	2.50	2.50	-	5.00 (1.8 - 6.2)	1.35 (0.50 - 2.06)	3.70	5.0	6.2	A++	
	9	12	-	2.18	2.82	-	5.00 (1.8 - 6.3)	1.35 (0.50 - 2.06)	3.70	5.0	6.2	A++	
	9	14	-	2.07	3.23	-	5.30 (1.8 - 6.7)	1.35 (0.50 - 2.06)	3.93	5.3	6.1	A++	
	12	12	-	2.55	2.55	-	5.10 (1.8 - 6.3)	1.35 (0.50 - 2.06)	3.78	5.1	6.1	A++	
	12	14	-	2.41	2.89	-	5.30 (1.8 - 6.7)	1.35 (0.50 - 2.06)	3.93	5.3	6.1	A++	
3 Room	7	7	7	1.80	1.80	1.80	5.40 (1.8 - 6.8)	1.35 (0.50 - 2.06)	4.00	5.4	6.9	A++	
	7	7	9	1.70	1.70	2.00	5.40 (1.8 - 6.8)	1.35 (0.50 - 2.06)	4.00	5.4	6.9	A++	
	7	7	12	1.53	1.53	2.33	5.40 (1.8 - 6.8)	1.35 (0.50 - 2.06)	4.00	5.4	6.7	A++	
	7	7	14	1.41	1.41	2.58	5.40 (2.0 - 6.8)	1.35 (0.60 - 2.06)	4.00	5.4	6.7	A++	
	7	9	9	1.61	1.89	1.89	5.40 (1.8 - 6.8)	1.35 (0.50 - 2.06)	4.00	5.4	6.8	A++	
	7	9	12	1.46	1.72	2.22	5.40 (1.8 - 6.8)	1.35 (0.50 - 2.06)	4.00	5.4	6.7	A++	
	7	9	14	1.35	1.58	2.47	5.40 (2.0 - 6.8)	1.35 (0.60 - 2.06)	4.00	5.4	6.7	A++	
	9	9	9	1.80	1.80	1.80	5.40 (1.8 - 6.8)	1.35 (0.50 - 2.06)	4.00	5.4	6.8	A++	
	9	9	12	1.64	1.64	2.12	5.40 (1.8 - 6.8)	1.35 (0.50 - 2.06)	4.00	5.4	6.7	A++	

AOYG24LAT3			Combination of Indoor Unit		COOLING OPERATION								
					Cooling Capacity				Input Power (min-max)	EER	Seasonal Data		
					Room 1	Room 2	Room 3	Total Capacity (min-max)			Pdesign	SEER	Energy efficiency class
			kW	kW	kW	kW	kW						
2 Room	7	7	-	2.30	2.30	-	4.60 (1.8 - 5.0)	1.20 (0.50 - 1.40)	3.83	4.6	6.3	A++	
	7	9	-	2.30	2.70	-	5.00 (1.8 - 5.7)	1.36 (0.50 - 1.78)	3.68	5.0	6.2	A++	
	7	12	-	2.38	3.42	-	5.80 (1.8 - 6.1)	1.70 (0.50 - 1.97)	3.41	5.8	6.1	A++	
	7	14	-	2.37	4.13	-	6.50 (1.8 - 7.2)	1.91 (0.50 - 2.46)	3.40	6.5	6.0	A+	
	7	18	-	2.08	4.52	-	6.60 (1.8 - 7.8)	1.91 (0.50 - 2.87)	3.46	6.6	5.9	A+	
	9	9	-	2.75	2.75	-	5.50 (1.8 - 6.2)	1.55 (0.50 - 2.02)	3.55	5.5	6.1	A++	
	9	12	-	2.79	3.41	-	6.20 (1.8 - 6.8)	1.90 (0.50 - 2.45)	3.26	6.2	5.9	A+	
	9	14	-	2.66	3.94	-	6.60 (1.8 - 7.7)	1.91 (0.50 - 2.77)	3.46	6.6	6.0	A+	
	9	18	-	2.35	4.35	-	6.70 (1.8 - 7.9)	1.91 (0.50 - 2.87)	3.51	6.7	5.9	A+	
	12	12	-	3.15	3.15	-	6.30 (1.8 - 7.2)	1.90 (0.50 - 2.74)	3.32	6.3	5.9	A+	
	12	14	-	3.03	3.67	-	6.70 (1.8 - 7.8)	1.91 (0.50 - 2.87)	3.51	6.7	5.9	A+	
	12	18	-	2.66	4.04	-	6.70 (1.8 - 7.9)	1.92 (0.50 - 2.87)	3.49	6.7	5.8	A+	
	7	7	7	2.23	2.23	2.23	6.70 (1.8 - 7.4)	1.89 (0.50 - 2.37)	3.54	6.7	6.4	A++	
	7	7	9	2.14	2.14	2.52	6.80 (1.8 - 7.8)	1.94 (0.60 - 2.87)	3.51	6.8	6.4	A++	
3 Room	7	7	12	1.98	1.98	2.84	6.80 (1.8 - 8.1)	1.93 (0.50 - 2.87)	3.52	6.8	6.3	A++	
	7	7	14	1.82	1.82	3.16	6.80 (2.0 - 8.4)	1.94 (0.60 - 2.87)	3.51	6.8	6.2	A++	
	7	7	18	1.63	1.63	3.54	6.80 (2.0 - 8.5)	1.94 (0.60 - 2.87)	3.51	6.8	6.1	A++	
	7	9	9	2.03	2.38	2.38	6.80 (1.8 - 8.2)	1.93 (0.50 - 2.87)	3.52	6.8	6.4	A++	
	7	9	12	1.88	2.21	2.70	6.80 (1.8 - 8.2)	1.93 (0.50 - 2.87)	3.52	6.8	6.2	A++	
	7	9	14	1.74	2.04	3.02	6.80 (2.0 - 8.4)	1.94 (0.60 - 2.87)	3.51	6.8	6.2	A++	
	7	9	18	1.56	1.84	3.40	6.80 (2.0 - 8.5)	1.94 (0.60 - 2.87)	3.51	6.8	6.1	A++	
	7	12	12	1.76	2.52	2.52	6.80 (1.8 - 8.2)	1.94 (0.50 - 2.87)	3.51	6.8	6.2	A++	
	7	12	14	1.63	2.34	2.83	6.80 (2.0 - 8.5)	1.94 (0.60 - 2.87)	3.51	6.8	6.2	A++	
	9	9	9	2.27	2.27	2.27	6.80 (1.8 - 8.2)	1.94 (0.50 - 2.87)	3.51	6.8	6.4	A++	
	9	9	12	2.11	2.11	2.58	6.80 (1.8 - 8.3)	1.94 (0.50 - 2.87)	3.51	6.8	6.2	A++	
	9	9	14	1.95	1.95	2.89	6.80 (2.0 - 8.5)	1.94 (0.60 - 2.87)	3.51	6.8	6.2	A++	
	9	9	18**	1.77	1.77	3.27	6.80 (2.0 - 8.5)	1.94 (0.60 - 2.87)	3.51	6.8	6.1	A++	
	9	12	12	1.97	2.41	2.41	6.80 (1.8 - 8.3)	1.94 (0.50 - 2.87)	3.51	6.8	6.2	A++	
	9	12	14	1.84	2.24	2.72	6.80 (2.0 - 8.5)	1.94 (0.60 - 2.87)	3.51	6.8	6.2	A++	
	12	12	12	2.27	2.27	2.27	6.80 (1.8 - 8.3)	1.94 (0.50 - 2.87)	3.51	6.8	6.1	A++	

Note: •7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h / 14:14000Btu/h / 18:18000Btu/h models
•The above is the value for connecting with Wall Mounted type.
•2 or more indoor units should be connected.
•Cooling capacity is based on 27°CDB/19°CWB (indoor temperature), 35°CDB (outdoor temperature).
•Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
•The total ability of connectable indoor units is up to 36000Btu from 14000Btu.
*1: When ASYG18L is connected, connect at least 1 wall mounted type of 9000Btu.

2 Rooms Multi heating

AOYG14LAC2	Combination of Indoor Unit		HEATING OPERATION							
			Heating Capacity			Input Power (min-max)	EER	Seasonal Data		
			Room 1	Room 2	Total Capacity (min-max)			Pdesign	SEER	Energy efficiency class
			kW	kW	kW	kW	kW	kW	kW	kW
2 Room	7	7	2.20	2.20	4.40 (1.1 - 5.4)	1.03 (0.25 - 1.78)	4.27	3.8	4.1	A+
	7	9	2.15	2.25	4.40 (1.1 - 5.4)	1.03 (0.25 - 1.78)	4.27	3.8	4.1	A+
	7	12	1.95	2.45	4.40 (1.1 - 5.5)	1.02 (0.25 - 1.76)	4.31	3.8	4.0	A+
	9	9	2.20	2.20	4.40 (1.1 - 5.4)	1.03 (0.25 - 1.78)	4.27	3.8	4.0	A+
	9	12	2.00	2.40	4.40 (1.1 - 5.5)	1.02 (0.25 - 1.76)	4.31	3.8	4.0	A+

Note: •7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h models
•The above is the value for connecting with Wall Mounted type.
•2 or more indoor units should be connected.
•Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
•Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
•The Total ability of connected a indoor unit is up to 21000Btu from 14000Btu.

AOYG18LAC2	Combination of Indoor Unit		HEATING OPERATION							
			Heating Capacity			Input Power (min-max)	EER	Seasonal Data		
			Room 1	Room 2	Total Capacity (min-max)			Pdesign	SEER	Energy efficiency class
			kW	kW	kW	kW				
2 Room	7	7	2.70	2.70	5.40 (1.8 - 6.0)	1.24 (0.50 - 1.61)	4.37	3.8	4.1	A+
	7	9	2.50	3.00	5.50 (1.8 - 6.0)	1.36 (0.50 - 1.87)	4.04	4.0	4.1	A+
	7	12	2.30	3.30	5.60 (1.8 - 6.1)	1.38 (0.50 - 1.88)	4.06	4.2	4.0	A+
	7	14	2.25	3.35	5.60 (1.9 - 6.2)	1.35 (0.55 - 1.86)	4.15	4.2	4.0	A+
	9	9	2.80	2.80	5.60 (1.8 - 6.1)	1.41 (0.50 - 1.90)	3.97	4.2	4.1	A+
	9	12	2.45	3.15	5.60 (1.8 - 6.2)	1.38 (0.50 - 1.88)	4.07	4.2	4.0	A+
	9	14	2.35	3.25	5.60 (1.9 - 6.3)	1.35 (0.55 - 1.86)	4.15	4.2	4.0	A+
	12	12	2.80	2.80	5.60 (1.8 - 6.3)	1.34 (0.50 - 1.84)	4.18	4.2	4.0	A+

4 Rooms Multi cooling

AOYG30LAT4	Combination of Indoor Unit				COOLING OPERATION									
					Cooling Capacity					EER	Seasonal Data			
					Room 1	Room 2	Room 3	Room 4	Total Capacity (min-max)		Input Power (min-max)	Pdesign	SEER	Energy efficiency class
					kW	kW	kW	kW	kW		kW			
3 Room	7	7	14	-	1.96	1.96	3.27	-	7.20 (1.6-8.9)	2.22 (0.68-3.43)	3.24	7.2	5.9	A+
	7	7	18	-	1.81	1.81	4.08	-	7.70 (2.8-10.0)	2.22 (0.98-3.55)	3.47	7.7	5.8	A+
	7	7	24	-	1.61	1.61	4.57	-	7.80 (2.8-10.1)	2.19 (0.98-3.53)	3.56	7.8	5.8	A+
	7	9	12	-	2.08	2.34	2.78	-	7.20 (1.6-8.9)	2.22 (0.68-3.41)	3.24	7.2	5.9	A+
	7	9	14	-	1.90	2.14	3.16	-	7.20 (2.8-9.1)	2.22 (0.98-3.56)	3.24	7.2	5.9	A+
	7	9	18	-	1.76	1.98	3.96	-	7.70 (2.8-9.9)	2.22 (0.98-3.56)	3.47	7.7	5.8	A+
	7	9	24	-	1.57	1.77	4.46	-	7.80 (2.8-10.1)	2.19 (0.98-3.53)	3.56	7.8	5.8	A+
	7	12	12	-	1.96	2.62	2.62	-	7.20 (1.6-9.1)	2.22 (0.68-3.54)	3.24	7.2	5.9	A+
	7	12	14	-	1.83	2.43	3.04	-	7.30 (2.8-9.2)	2.22 (0.98-3.56)	3.29	7.3	5.9	A+
	7	12	18	-	1.68	2.24	3.78	-	7.70 (2.8-9.9)	2.22 (0.98-3.56)	3.47	7.7	5.8	A+
	7	12	24	-	1.51	2.01	4.28	-	7.80 (2.8-10.1)	2.19 (0.98-3.56)	3.56	7.8	5.8	A+
	7	14	14	-	1.68	2.81	2.81	-	7.30 (2.8-9.3)	2.22 (0.98-3.58)	3.29	7.3	5.9	A+
	7	14	18	-	1.57	2.61	3.52	-	7.70 (3.5-10.0)	2.22 (1.17-3.58)	3.47	7.7	5.8	A+
	7	14	24	-	1.44	2.39	4.07	-	7.90 (3.5-10.1)	2.20 (1.17-3.58)	3.59	7.9	5.8	A+
	7	18	18	-	1.42	3.19	3.19	-	7.80 (3.5-10.1)	2.22 (1.17-3.58)	3.51	7.8	5.7	A+
	7	18	24	-	1.30	2.92	3.68	-	7.90 (4.7-10.1)	2.22 (1.17-3.58)	3.56	7.9	5.7	A+
	9	9	9	-	2.40	2.40	2.40	-	7.20 (2.8-8.9)	2.22 (0.98-3.42)	3.24	7.2	5.9	A+
	9	9	12	-	2.26	2.26	2.68	-	7.20 (2.8-9.1)	2.22 (0.98-3.54)	3.24	7.2	5.9	A+
	9	9	14	-	2.10	2.10	3.11	-	7.30 (2.8-9.2)	2.22 (0.98-3.57)	3.29	7.3	5.9	A+
	9	9	18	-	1.93	1.93	3.85	-	7.70 (2.8-9.9)	2.22 (0.98-3.56)	3.47	7.7	5.8	A+
	9	9	24	-	1.73	1.73	4.35	-	7.80 (2.8-10.1)	2.20 (1.17-3.54)	3.55	7.8	5.8	A+
	9	12	12	-	2.14	2.53	2.53	-	7.20 (2.8-9.1)	2.22 (0.98-3.54)	3.24	7.2	5.9	A+
	9	12	14	-	1.99	2.36	2.95	-	7.30 (2.8-9.2)	2.22 (0.98-3.57)	3.29	7.3	5.9	A+
	9	12	18	-	1.84	2.18	3.68	-	7.70 (2.8-9.9)	2.22 (0.98-3.56)	3.47	7.7	5.8	A+
	9	12	24	-	1.66	1.97	4.18	-	7.80 (2.8-10.1)	2.19 (0.98-3.56)	3.56	7.8	5.8	A+
	9	14	14	-	1.84	2.73	2.73	-	7.30 (3.5-9.3)	2.22 (1.17-3.58)	3.29	7.3	5.9	A+
	9	14	18	-	1.74	2.58	3.48	-	7.80 (3.5-10.0)	2.22 (1.17-3.58)	3.51	7.8	5.8	A+
	9	14	24	-	1.58	2.34	3.98	-	7.90 (3.5-10.1)	2.22 (1.17-3.56)	3.56	7.9	5.8	A+
	9	18	18	-	1.56	3.12	3.12	-	7.80 (4.7-10.1)	2.22 (1.17-3.58)	3.51	7.8	5.7	A+
	12	12	12	-	2.43	2.43	2.43	-	7.30 (2.8-9.2)	2.22 (0.98-3.55)	3.29	7.3	5.9	A+
	12	12	14	-	2.28	2.28	2.85	-	7.40 (2.8-9.3)	2.22 (0.98-3.58)	3.33	7.4	5.9	A+
	12	12	18	-	2.12	2.12	3.57	-	7.80 (3.5-10.0)	2.22 (1.17-3.57)	3.51	7.8	5.8	A+
	12	12	24	-	1.92	1.92	4.07	-	7.90 (3.5-10.1)	2.20 (1.17-3.54)	3.59	7.9	5.8	A+
	12	14	14	-	2.11	2.64	2.64	-	7.40 (3.5-9.4)	2.22 (1.17-3.58)	3.33	7.4	5.9	A+
	12	14	18	-	1.98	2.48	3.34	-	7.80 (3.5-10.1)	2.22 (1.17-3.58)	3.51	7.8	5.8	A+
	12	18	18	-	1.81	3.05	3.05	-	7.90 (4.7-10.1)	2.22 (1.17-3.58)	3.56	7.9	5.7	A+
4 Room	7	7	7	7	1.93	1.93	1.93	1.93	7.70 (1.6-9.6)	2.20 (0.68-3.41)	3.50	7.7	6.2	A++
	7	7	7	9	1.89	1.89	1.89	2.13	7.80 (1.6-9.8)	2.22 (0.68-3.54)	3.51	7.8	6.2	A++
	7	7	7	12	1.83	1.83	1.83	2.41	7.90 (1.6-9.9)	2.22 (0.68-3.54)	3.56	7.9	6.1	A++
	7	7	7	14	1.70	1.70	1.70	2.80	7.90 (2.8-9.9)	2.22 (0.98-3.56)	3.56	7.9	6.1	A++
	7	7	7	18	1.52	1.52	1.52	3.43	8.00 (2.8-10.1)	2.20 (0.98-3.55)	3.64	8.0	6.0	A+
	7	7	9	9	1.86	1.86	2.09	2.09	7.90 (2.8-9.7)	2.22 (0.98-3.42)	3.56	7.9	6.2	A++
	7	7	9	12	1.78	1.78	1.99	2.35	7.90 (2.8-9.9)	2.22 (0.98-3.55)	3.56	7.9	6.1	A++
	7	7	9	14	1.68	1.68	1.88	2.76	8.00 (2.8-10.0)	2.22 (0.98-3.57)	3.60	8.0	6.1	A++
	7	7	9	18	1.49	1.49	1.67	3.35	8.00 (3.5-10.1)	2.20 (1.17-3.55)	3.64	8.0	6.0	A+
	7	7	12	12	1.72	1.72	2.28	2.28	8.00 (2.8-10.0)	2.22 (0.98-3.55)	3.60	8.0	6.1	A++
	7	7	12	14	1.61	1.61	2.13	2.65	8.00 (2.8-10.0)	2.22 (0.98-3.57)	3.60	8.0	6.1	A++
	7	7	12	18	1.43	1.43	1.91	3.22	8.00 (3.5-10.1)	2.20 (1.17-3.56)	3.64	8.0	6.0	A+
	7	7	14	14	1.50	1.50	2.50	2.50	8.00 (3.5-10.1)	2.22 (1.17-3.58)	3.60	8.0	6.0	A+
	7	7	14	18	1.35	1.35	2.25	3.04	8.00 (3.5-10.1)	2.22 (1.17-3.58)	3.60	8.0	6.0	A+
	7	9	9	9	1.81	2.03	2.03	2.03	7.90 (2.8-9.9)	2.22 (0.98-3.56)	3.56	7.9	6.2	A++
	7	9	9	12	1.76	1.96	1.96	2.32	8.00 (2.8-10.0)	2.22 (0.98-3.56)	3.60	8.0	6.1	A++
	7	9	9	14	1.64	1.83	1.83	2.70	8.00 (3.5-10.1)	2.22 (1.17-3.58)	3.60	8.0	6.1	A++
	7	9	9	18	1.45	1.64	1.64	3.27	8.00 (3.5-10.1)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+
	7	9	12	12	1.68	1.88	2.22	2.22	8.00 (2.8-10.0)	2.22 (0.98-3.56)	3.60	8.0	6.1	A++
	7	9	12	14	1.57	1.76	2.08	2.59	8.00 (3.5-10.1)	2.22 (1.17-3.58)	3.60	8.0	6.0	A+
	7	9	12	18	1.40	1.58	1.87	3.15	8.00 (3.5-10.1)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+
	7	9	14	14	1.48	1.66	2.43	2.43	8.00 (3.5-10.1)	2.22 (1.17-3.58)	3.60	8.0	6.0	A+
	7	9	14	18	1.32	1.49	2.21	2.98	8.00 (4.7-10.1)	2.22 (1.17-3.57)	3.60	8.0	6.0	A+
	7	12	12	12	1.61	2.13	2.13	2.13	8.00 (2.8-10.1)	2.22 (0.98-3.56)	3.60	8.0	6.0	A+
	7	12	12	14	1.51	2.00	2.00	2.49	8.00 (3.5-10.1)	2.22 (1.17-3.58)	3.60	8.0	6.0	A+
	7	12	12	18	1.35	1.80	1.80	3.04	8.00 (3.5-10.1)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+
	7	12	14	14	1.41	1.89	2.35	2.35	8.00 (3.5-10.1)	2.22 (1.17-3.58)	3.60	8.0	6.0	A+
	9	9	9	9	2.00	2.00	2.00	2.00	8.00 (3.5-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.2	A++
	9	9	9	12	1.91	1.91	1.91	2.27	8.00 (3.5-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.1	A++
	9	9	9	14	1.79	1.79	1.79	2.63	8.00 (3.5-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+
	9	9	9	18**	1.60	1.60	1.60	3.20	8.00 (4.7-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+
	9	9	12	12	1.83	1.83	2.17	2.17	8.00 (3.5-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+
	9	9	12	14	1.72	1.72	2.03	2.53	8.00 (3.5-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+
	9	9	12	18**	1.54	1.54	1.83	3.09	8.00 (4.7-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+
	9	9	14	14	1.62	1.62	2.38	2.38	8.00 (4.7-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+
	9	12	12	12	1.76	2.08	2.08	2.08	8.00 (3.5-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+
9	12	12	14	1.66	1.95	1.95	2.44	8.00 (3.5-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+	
9	12	14	14	1.55	1.85	2.30	2.30	8.00 (4.7-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+	
12	12	12	12	2.00	2.00	2.00	2.00	8.00 (3.5-10.0)	2.22 (1.17-3.56)	3.60	8.0	6.0	A+	

Note: •7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h / 14:14000Btu/h / 18:18000Btu/h / 24:24000Btu/h models
•The above is the value for connecting with Wall Mounted type.
•3 or more indoor units should be connected.
•Cooling capacity is based on 27°CDB/19°CWB (indoor temperature), 35°CDB (outdoor temperature).
•Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
•The Total ability of connected a indoor unit is up to 49000Btu from 27000Btu.
*1: Connection of ASYG18L + ARYG09L + ARYG09L + ARYG09L is not available. All types other than this combination can be connected.
*2: Connection of ASYG18L + ARYG12L + ARYG09L + ARYG09L is not available. All types other than this combination can be connected.

4 Rooms Multi heating

AOYG30LAT4		Combination of Indoor Unit		HEATING OPERATION										Seasonal Data			
				Heating Capacity				Total Capacity (min-max)	Input Power (min-max)		EER						
				Room 1	Room 2	Room 3	Room 4		kW								
				kW	kW	kW	kW		kW	kW		SEER	Energy efficiency class				
3 Room	7	7	14	-	2.42	2.42	4.15	-	9.00 (1.8 - 10.1)	2.66 (0.58 - 3.53)	3.38	5.8	3.8	A			
	7	7	18	-	2.27	2.27	4.86	-	9.40 (3.3 - 11.2)	2.46 (0.87 - 3.52)	3.82	5.8	3.8	A			
	7	7	24	-	2.03	2.03	5.44	-	9.50 (3.3 - 11.5)	2.47 (0.87 - 3.52)	3.85	5.8	3.8	A			
	7	9	12	-	2.49	2.94	3.56	-	9.00 (1.8 - 10.0)	2.69 (0.58 - 3.51)	3.35	5.8	3.8	A			
	7	9	14	-	2.33	2.75	4.00	-	9.10 (3.3 - 10.2)	2.64 (0.87 - 3.50)	3.45	5.8	3.8	A			
	7	9	18	-	2.17	2.56	4.66	-	9.40 (3.3 - 11.3)	2.45 (0.87 - 3.50)	3.84	5.8	3.8	A			
	7	9	24	-	1.98	2.33	5.29	-	9.60 (3.3 - 11.5)	2.46 (0.87 - 3.51)	3.90	5.8	3.8	A			
	7	12	12	-	2.33	3.33	3.33	-	9.00 (1.8 - 10.1)	2.66 (0.58 - 3.48)	3.38	5.8	3.8	A			
	7	12	14	-	2.12	3.17	3.80	-	9.20 (3.3 - 10.3)	2.62 (0.87 - 3.48)	3.51	5.8	3.8	A			
	7	12	18	-	2.08	2.97	4.45	-	9.50 (3.3 - 11.4)	2.44 (0.87 - 3.47)	3.89	5.8	3.8	A			
	7	12	24	-	1.88	2.69	5.03	-	9.60 (3.3 - 11.7)	2.45 (0.87 - 3.56)	3.92	5.8	3.8	A			
	7	14	14	-	2.10	3.60	3.60	-	9.30 (3.3 - 10.6)	2.59 (0.87 - 3.48)	3.59	5.8	3.8	A			
	7	14	18	-	1.96	3.35	4.19	-	9.50 (3.7 - 11.5)	2.42 (0.97 - 3.52)	3.93	5.8	3.8	A			
	7	14	24	-	1.78	3.05	4.77	-	9.60 (3.3 - 11.7)	2.45 (0.87 - 3.56)	3.92	5.8	3.8	A			
	7	18	18	-	1.82	3.89	3.89	-	9.60 (3.7 - 12.0)	2.40 (0.97 - 3.52)	4.00	5.8	3.8	A			
	7	18	24	-	1.62	4.53	4.42	-	9.60 (4.3 - 12.0)	2.40 (1.12 - 3.52)	4.00	5.8	3.8	A			
	9	9	9	-	3.00	3.00	3.00	-	9.00 (3.3 - 10.0)	2.69 (0.87 - 3.51)	3.35	5.8	3.8	A			
	9	9	12	-	2.80	2.80	3.39	-	9.00 (3.3 - 10.1)	2.67 (0.87 - 3.48)	3.37	5.8	3.8	A			
	9	9	14	-	2.66	2.66	3.87	-	9.20 (3.3 - 10.3)	2.63 (0.87 - 3.48)	3.50	5.8	3.8	A			
	9	9	18	-	2.49	2.49	4.52	-	9.50 (3.7 - 11.4)	2.44 (0.97 - 3.48)	3.89	5.8	3.8	A			
	9	9	24	-	2.25	2.25	5.11	-	9.60 (3.7 - 11.7)	2.45 (0.97 - 3.57)	3.92	5.8	3.8	A			
	9	12	12	-	2.65	3.22	3.22	-	9.10 (3.3 - 10.3)	2.65 (0.87 - 3.52)	3.43	5.8	3.8	A			
	9	12	14	-	2.53	3.07	3.69	-	9.30 (3.3 - 10.5)	2.61 (0.87 - 3.52)	3.56	5.8	3.8	A			
	9	12	18	-	2.36	4.26	4.29	-	9.50 (3.7 - 11.4)	2.43 (0.97 - 3.47)	3.91	5.8	3.8	A			
	9	12	24	-	2.16	2.59	4.86	-	9.60 (3.7 - 11.8)	2.44 (0.97 - 3.55)	3.93	5.8	3.8	A			
	9	14	14	-	2.38	3.46	3.46	-	9.30 (3.7 - 10.7)	2.58 (0.97 - 3.46)	3.60	5.8	3.8	A			
	9	14	18	-	2.22	3.23	4.04	-	9.50 (3.7 - 11.6)	2.41 (0.97 - 3.51)	3.94	5.8	3.8	A			
	9	14	24	-	2.03	2.95	4.62	-	9.60 (4.3 - 11.9)	2.42 (1.12 - 3.57)	3.97	5.8	3.8	A			
	9	18	18	-	2.07	3.76	3.76	-	9.60 (4.3 - 12.0)	2.40 (1.12 - 3.52)	4.00	5.8	3.8	A			
	12	12	12	-	3.07	3.07	3.07	-	9.20 (3.3 - 10.3)	2.63 (0.87 - 3.49)	3.50	5.8	3.8	A			
	12	12	14	-	2.91	2.91	3.49	-	9.30 (3.3 - 10.6)	2.59 (0.87 - 3.49)	3.59	5.8	3.8	A			
	12	12	18	-	2.71	2.71	4.07	-	9.50 (3.7 - 11.6)	2.42 (0.97 - 3.52)	3.93	5.8	3.8	A			
	12	12	24	-	2.48	2.48	4.65	-	9.60 (3.7 - 11.8)	2.43 (0.97 - 3.56)	3.95	5.8	3.8	A			
	12	14	14	-	2.76	3.32	3.32	-	9.40 (3.7 - 10.8)	2.40 (0.97 - 3.50)	3.92	5.8	3.8	A			
	12	14	18	-	2.57	3.08	3.85	-	9.50 (3.7 - 11.6)	2.40 (0.97 - 3.49)	3.96	5.8	3.8	A			
	12	18	18	-	2.40	3.60	3.60	-	9.60 (4.3 - 12.0)	2.40 (1.12 - 3.52)	4.00	5.8	3.8	A			
7	7	7	7	2.35	2.35	2.35	2.35	9.40 (1.8 - 10.8)	2.43 (0.58 - 3.47)	3.87	6.2	4.0	A+				
7	7	7	9	2.27	2.27	2.27	2.68	9.50 (1.8 - 10.9)	2.42 (0.58 - 3.51)	3.88	6.2	4.0	A+				
7	7	7	12	2.14	2.14	2.14	3.06	9.50 (1.8 - 11.1)	2.41 (0.58 - 3.55)	3.94	6.2	4.0	A+				
7	7	7	14	2.04	2.04	2.04	3.49	9.60 (3.3 - 11.3)	2.38 (0.87 - 3.56)	4.03	6.2	4.0	A+				
7	7	7	18	1.87	1.87	1.87	4.00	9.60 (3.3 - 12.0)	2.27 (0.87 - 3.56)	4.23	6.2	4.0	A+				
7	7	9	9	2.18	2.18	2.57	2.57	9.50 (3.3 - 10.9)	2.41 (0.87 - 3.44)	3.94	6.2	4.0	A+				
7	7	9	12	2.06	2.06	2.43	2.95	9.50 (3.3 - 11.1)	2.40 (0.87 - 3.54)	3.96	6.2	4.0	A+				
7	7	9	14	1.96	1.96	2.31	3.36	9.60 (3.3 - 11.4)	2.38 (0.87 - 3.54)	4.03	6.2	4.0	A+				
7	7	9	18	1.80	1.80	2.13	3.87	9.60 (3.7 - 12.0)	2.27 (0.97 - 3.55)	4.23	6.2	4.0	A+				
7	7	12	12	1.98	1.98	2.82	2.82	9.60 (3.3 - 11.3)	2.39 (0.87 - 3.57)	4.02	6.2	4.0	A+				
7	7	12	14	1.87	1.87	2.67	3.20	9.60 (3.3 - 11.5)	2.36 (0.87 - 3.58)	4.07	6.2	4.0	A+				
7	7	12	18	1.72	1.72	2.46	3.69	9.60 (3.7 - 11.6)	2.27 (0.97 - 3.58)	4.23	6.2	4.0	A+				
7	7	14	14	1.77	1.77	3.03	3.03	9.60 (3.7 - 11.8)	2.34 (0.97 - 3.58)	4.10	6.2	4.0	A+				
7	7	14	18	1.64	1.64	2.81	3.51	9.60 (3.7 - 12.0)	2.27 (0.97 - 3.56)	4.23	6.2	4.0	A+				
7	9	9	9	2.09	2.47	2.47	2.47	9.50 (3.3 - 11.2)	2.40 (0.87 - 3.54)	4.00	6.2	4.0	A+				
7	9	9	12	2.01	2.36	2.36	2.87	9.60 (3.3 - 11.3)	2.39 (0.87 - 3.58)	4.02	6.2	4.0	A+				
7	9	9	14	1.89	2.23	2.23	3.25	9.60 (3.7 - 11.5)	2.37 (0.97 - 3.58)	4.05	6.2	4.0	A+				
7	9	9	18	1.75	2.06	2.06	3.76	9.60 (3.7 - 12.0)	2.27 (0.97 - 3.58)	4.23	6.2	4.0	A+				
7	9	12	12	1.91	2.25	2.72	2.72	9.60 (3.3 - 11.4)	2.38 (0.87 - 3.58)	4.03	6.2	4.0	A+				
7	9	12	14	1.80	2.13	2.58	3.09	9.60 (3.7 - 11.6)	2.27 (0.97 - 3.58)	4.09	6.2	4.0	A+				
7	9	12	18	1.67	1.97	2.39	3.58	9.60 (3.7 - 12.0)	2.27 (0.97 - 3.58)	4.23	6.2	4.0	A+				
7	9	14	14	1.71	2.02	2.94	2.94	9.60 (3.7 - 11.8)	2.33 (0.97 - 3.58)	4.12	6.2	4.0	A+				
7	9	14	18	1.59	1.87	2.73	3.41	9.60 (4.3 - 12.0)	2.27 (1.12 - 3.58)	4.23	6.2	4.0	A+				
7	12	12	12	1.81	2.59	2.59	2.59	9.60 (3.3 - 11.5)	2.37 (0.87 - 3.58)	4.05	6.2	4.0	A+				
7	12	12	14	1.72	2.46	2.46	2.95	9.60 (3.7 - 11.7)	2.34 (0.97 - 3.58)	4.10	6.2	4.0	A+				
7	12	12	18	1.60	2.29	2.29	3.43	9.60 (3.7 - 12.0)	2.27 (0.97 - 3.56)	4.23	6.2	4.0	A+				
7	12	14	14	1.64	2.34	2.81	2.81	9.60 (3.7 - 11.9)	2.32 (0.87 - 3.58)	4.14	6.2	4.0	A+				
9	9	9	9	2.40	2.40	2.40	2.40	9.60 (3.7 - 11.5)	2.40 (0.97 - 3.58)	4.00	6.2	4.0	A+				
9	9	9	12	2.28	2.28	2.28	2.76	9.60 (3.7 - 11.4)	2.38 (0.97 - 3.58)	4.03	6.2	4.0	A+				
9	9	9	14	2.16	2.16	2.16	3.14	9.60 (3.7 - 11.6)	2.36 (0.97 - 3.58)	4.07	6.2	4.0	A+				
9	9	9	18*	1.99	1.99	1.99	3.62	9.60 (4.3 - 12.0)	2.27 (1.12 - 3.58)	4.23	6.2	4.0	A+				
9	9	12	12	2.17	2.17	2.63	2.63	9.60 (3.7 - 11.5)	2.37 (0.97 - 3.58)	4.05	6.2	4.0	A+				
9	9	12	14	2.06	2.06	2.49	2.99	9.60 (3.7 - 11.7)	2.35 (0.97 - 3.58)	4.09	6.2	4.0	A+				
9	9	12	18**	1.91	1.91	2.31	3.47	9.60 (4.3 - 12.0)	2.27 (1.12 - 3.58)	4.23	6.2	4.0	A+				
9	9	14	14	1.96	1.96	2.84	2.84	9.60 (4.3 - 11.9)	2.32 (1.12 - 3.58)	4.12	6.2	4.0	A+				
9	12	12	12	2.07	2.51	2.51	2.51	9.60 (3.7 - 11.6)	2.36 (0.97 - 3.58)	4.07	6.2	4.0	A+				
9	12	12	14	1.97	2.39	2.39	2.87	9.60 (3.7 - 11.8)	2.34 (0.97 - 3.58)	4.10	6.2	4.0	A+				
9	12	14	14	1.87	2.27	2.73	2.73	9.60 (4.3 - 11.9)	2.31 (1.12 - 3.58)	4.16	6.2	4.0	A+				
12	12	12	12	2.40	2.40	2.40	2.40	9.60 (3.7 - 11.6)	2.35 (0.97 - 3.58)	4.09	6.2	4.0	A+				

8 Rooms Multi cooling

AOYG45LBT8		Combination of Indoor Unit							COOLING OPERATION										Input power	
									Cooling Capacity								Total			
									Room 1	Room 2	Room 3	Room 4	Room 5	Room 6	Room 7	Room 8				
									kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	
2 Room	24	24	-	-	-	-	-	7.03	7.03	-	-	-	-	-	-	-	14.06	5.20		
	18	24	-	-	-	-	-	5.27	7.03	-	-	-	-	-	-	-	12.30	4.24		
	18	18	24	-	-	-	-	4.63	4.63	6.18	-	-	-	-	-	-	15.45	5.89		
	18	18	18	-	-	-	-	5.01	5.01	5.01	-	-	-	-	-	-	15.03	5.90		
	14	24	24	-	-	-	-	3.54	6.07	6.07	-	-	-	-	-	-	15.68	5.87		
	14	18	24	-	-	-	-	3.84	4.94	6.59	-	-	-	-	-	-	15.37	5.90		
	14	18	18	-	-	-	-	4.10	5.27	5.27	-	-	-	-	-	-	14.64	5.50		
	14	14	24	-	-	-	-	4.10	4.10	7.03	-	-	-	-	-	-	15.23	5.79		
	14	14	18	-	-	-	-	4.10	4.10	5.27	-	-	-	-	-	-	13.47	4.89		
	14*	14*	14*	-	-	-	-	4.10	4.10	4.10	-	-	-	-	-	-	12.30	4.24		
3 Room	12	24	24	-	-	-	-	3.09	6.18	6.18	-	-	-	-	-	-	15.45	5.89		
	12	18	24	-	-	-	-	3.35	5.01	6.68	-	-	-	-	-	-	15.04	5.90		
	12	18	18	-	-	-	-	3.52	5.27	5.27	-	-	-	-	-	-	14.06	5.20		
	12	14	24	-	-	-	-	3.52	4.10	7.03	-	-	-	-	-	-	14.65	5.50		
	12	14	18	-	-	-	-	3.52	4.10	5.27	-	-	-	-	-	-	12.89	4.57		
	12**	14**	14**	-	-	-	-	3.52	4.10	4.10	-	-	-	-	-	-	11.72	3.91		
	12	12	24	-	-	-	-	3.52	3.52	7.03	-	-	-	-	-	-	14.07	5.20		
	12	12	18	-	-	-	-	3.52	3.52	5.27	-	-	-	-	-	-	12.31	4.24		
	9	24	24	-	-	-	-	2.64	6.54	6.54	-	-	-	-	-	-	15.54	5.90		
	9	18	24	-	-	-	-	2.64	5.27	7.03	-	-	-	-	-	-	14.94	5.65		
	9	18	18	-	-	-	-	2.64	5.27	5.27	-	-	-	-	-	-	13.18	4.73		
	9	14	24	-	-	-	-	2.64	4.10	7.03	-	-	-	-	-	-	13.77	5.05		
	9	14	18	-	-	-	-	2.64	4.10	5.27	-	-	-	-	-	-	12.01	4.08		
	9	12	24	-	-	-	-	2.64	3.52	7.03	-	-	-	-	-	-	13.19	4.73		
	9	12	18	-	-	-	-	2.64	3.52	5.27	-	-	-	-	-	-	11.43	3.74		
	9	9	24	-	-	-	-	2.64	2.64	7.03	-	-	-	-	-	-	12.31	4.24		
	7	24	24	-	-	-	-	1.93	6.64	6.64	-	-	-	-	-	-	15.21	5.90		
	7	18	24	-	-	-	-	2.05	5.27	7.03	-	-	-	-	-	-	14.35	5.35		
	7	18	18	-	-	-	-	2.05	5.27	5.27	-	-	-	-	-	-	12.59	4.41		
	7	14	24	-	-	-	-	2.05	4.10	7.03	-	-	-	-	-	-	13.18	4.73		
	7	14	18	-	-	-	-	2.05	4.10	5.27	-	-	-	-	-	-	11.42	3.74		
	7	12	24	-	-	-	-	2.05	3.52	7.03	-	-	-	-	-	-	12.60	4.41		
	7	9	24	-	-	-	-	2.05	2.64	7.03	-	-	-	-	-	-	11.72	3.91		
	4 Room	14	14	14	-	-	-	-	3.60	3.60	3.60	4.63	-	-	-	-	-	15.45	5.89	
		14	14	14	-	-	-	-	3.84	3.84	3.84	3.84	-	-	-	-	-	15.37	5.90	
		12	14	18	-	-	-	-	3.04	3.54	4.55	4.55	-	-	-	-	-	15.68	5.87	
		12	14	14	-	-	-	-	3.15	3.67	3.67	4.72	-	-	-	-	-	15.21	5.90	
		12	14	14	-	-	-	-	3.35	3.90	3.90	3.90	-	-	-	-	-	15.04	5.90	
		12	12	18	-	-	-	-	3.09	3.09	4.63	4.63	-	-	-	-	-	15.45	5.89	
		12	12	14	-	-	-	-	3.04	3.04	3.54	6.07	-	-	-	-	-	15.69	5.87	
		12	12	14	-	-	-	-	3.30	3.30	3.84	4.94	-	-	-	-	-	15.38	5.90	
		12	12	14	-	-	-	-	3.52	3.52	4.10	4.10	-	-	-	-	-	15.24	5.79	
		12	12	12	-	-	-	-	3.09	3.09	3.09	6.18	-	-	-	-	-	15.45	5.89	
		12	12	12	-	-	-	-	3.35	3.35	3.35	5.01	-	-	-	-	-	15.05	5.90	
		12	12	12	-	-	-	-	3.52	3.52	3.52	4.10	-	-	-	-	-	14.66	5.50	
		12	12	12	-	-	-	-	3.52	3.52	3.52	3.52	-	-	-	-	-	14.08	5.20	
		9	14	18	-	-	-	-	2.34	3.64	4.67	4.67	-	-	-	-	-	15.33	5.89	
		9	14	14	-	-	-	-	2.30	3.57	3.57	6.12	-	-	-	-	-	15.57	5.88	
		9	14	14	-	-	-	-	2.49	3.87	3.87	4.97	-	-	-	-	-	15.21	5.90	
		9	14	14	-	-	-	-	2.64	4.10	4.10	4.10	-	-	-	-	-	14.94	5.65	
		9	12	18	-	-	-	-	2.46	3.28	4.90	4.90	-	-	-	-	-	15.54	5.90	
		9	12	14	-	-	-	-	2.34	3.12	3.64	6.23	-	-	-	-	-	15.33	5.89	
		9	12	14	-	-	-	-	2.53	3.37	3.93	5.05	-	-	-	-	-	14.87	5.90	
		9	12	14	-	-	-	-	2.64	3.52	4.10	4.10	-	-	-	-	-	14.36	5.35	
		9	12	12	-	-	-	-	2.46	3.28	3.28	6.54	-	-	-	-	-	15.55	5.90	
		9	12	12	-	-	-	-	2.64	3.52	3.52	5.27	-	-	-	-	-	14.95	5.65	
		9	12	12	-	-	-	-	2.64	3.52	3.52	4.10	-	-	-	-	-	13.78	5.05	
		9	12	12	-	-	-	-	2.64	3.52	3.52	3.52	-	-	-	-	-	13.20	4.73	
		9	9	18	-	-	-	-	2.32	2.32	4.63	6.18	-	-	-	-	-	15.45	5.89	
		9	9	18	-	-	-	-	2.51	2.51	5.01	5.01	-	-	-	-	-	15.04	5.90	
9		9	14	-	-	-	-	2.47	2.47	3.84	6.59	-	-	-	-	-	15.38	5.90		
9		9	14	-	-	-	-	2.64	2.64	4.10	5.27	-	-	-	-	-	14.65	5.50		
9		9	14	-	-	-	-	2.64	2.64	4.10	4.10	-	-	-	-	-	13.48	4.89		
9		9	12	-	-	-	-	2.51	2.51	3.35	6.68	-	-	-	-	-	15.05	5.90		
9		9	12	-	-	-	-	2.64	2.64	3.52	5.27	-	-	-	-	-	14.07	5.20		
9		9	12	-	-	-	-	2.64	2.64	3.52	4.10	-	-	-	-	-	12.90	4.57		
9		9	12	-	-	-	-	2.64	2.64	3.52	3.52	-	-	-	-	-	12.32	4.24		
9		9	9	-	-	-	-	2.64	2.64	2.64	7.03	-	-	-	-	-	14.95	5.65		
9		9	9	-	-	-	-	2.64	2.64	2.64	5.27	-	-	-	-	-	13.19	4.73		
9		9	9	-	-	-	-	2.64	2.64	2.64	4.10	-	-	-	-	-	12.02	4.08		
9		9	9	-	-	-	-	2.64	2.64	2.64	3.52	-	-	-	-	-	11.44	3.74		
7		18	18	-	-	-	-	1.79	4.59	4.59	4.59	-	-	-	-	-	15.56	5.88		
7		14	18	-	-	-	-	1.91	3.82	4.91	4.91	-	-	-	-	-	15.54	5.90		
7		14	14	-	-	-	-	1.82	3.64	3.64	6.24	-	-	-	-	-	15.33	5.89		
7		14	14	-	-	-	-	1.96	3.93	3.93	5.05	-	-	-	-	-	14.87	5.90		
7		14	14	-	-	-	-	2.05	4.10	4.10	4.10	-	-	-	-	-	14.35	5.35		
7		12	18	-	-	-	-	1.79	3.07	4.59	6.12	-	-	-	-	-	15.57	5.88		
7		12	18	-	-	-	-	1.93	3.32	4.97	4.97	-	-	-	-	-	15.21	5.90		
7		12	14	-	-	-	-	1.91	3.28	3.82	6.54	-	-	-	-	-	15.54	5.90		
7		12	14	-	-	-	-	2.05	3.52	4.10	5.27	-	-	-	-	-	14.94	5.65		
7		12	14	-	-	-	-	2.05	3.52	4.10	4.10	-	-	-	-	-	13.77	5.05		
7		12	12	-	-	-	-	1.93	3.32	3.32	6.63	-	-	-	-	-	15.21	5.90		
7		12	12	-	-	-	-	2.05	3.52	3.52	5.27	-	-	-	-	-	14.36	5.35		
7	12	12	-	-	-	-	2.05	3.52	3.52	4.10	-	-	-	-	-	13.19	4.73			
7	12	12	-	-	-	-	2.05	3.52	3.52	3.52	-	-	-	-	-	12.61	4.41			
7	9	18	-	-	-	-	1.84	2.36	4.72	6.29	-	-	-	-	-	15.21	5.90			
7	9	18	-	-	-	-	2.05	2.64	5.27	5.27	-	-	-	-	-	15.23	5.79			
7	9	14	-	-	-	-	1.95	2.51	3.90	6.68	-	-	-	-	-	15.04	5.90			
7	9	14	-	-	-	-	2.05	2.64	4.10	5.27	-	-	-	-	-	14.06	5.20			
7	9	12	-	-	-	-	2.05	2.64	3.52	7.03	-									

8 Rooms Multi cooling

AOYG45LBT8	Combination of Indoor Unit								COOLING OPERATION									
									Cooling Capacity								Input power	
									Room 1	Room 2	Room 3	Room 4	Room 5	Room 6	Room 7	Room 8	Total	
									kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
6 Room	7	9	9	9	9	18	-	-	1.79	2.30	2.30	2.30	2.30	4.59	-	-	15.57	5.88
	7	9	9	9	9	12	-	-	1.93	2.49	2.49	2.49	2.49	3.32	-	-	15.22	5.90
	7	9	9	9	9	9	-	-	2.05	2.64	2.64	2.64	2.64	2.64	-	-	15.25	5.79
	7	7	12	12	12	12	-	-	1.77	1.77	3.04	3.04	3.04	3.04	-	-	15.69	5.87
	7	7	9	12	12	14	-	-	1.79	1.79	2.30	3.07	3.07	3.57	-	-	15.57	5.88
	7	7	9	12	12	12	-	-	1.82	1.82	2.34	3.12	3.12	3.12	-	-	15.34	5.89
	7	7	9	9	14	14	-	-	1.80	1.80	2.32	2.32	3.60	3.60	-	-	15.45	5.89
	7	7	9	9	12	18	-	-	1.77	1.77	2.28	2.28	3.04	4.55	-	-	15.69	5.87
	7	7	9	9	12	14	-	-	1.83	1.83	2.36	2.36	3.15	3.67	-	-	15.21	5.90
	7	7	9	9	12	12	-	-	1.92	1.92	2.47	2.47	3.30	3.30	-	-	15.38	5.90
	7	7	9	9	9	18	-	-	1.82	1.82	2.34	2.34	2.34	4.67	-	-	15.33	5.89
	7	7	9	9	9	14	-	-	1.93	1.93	2.49	2.49	2.49	3.87	-	-	15.21	5.90
	7	7	9	9	9	12	-	-	1.96	1.96	2.53	2.53	2.53	3.37	-	-	14.88	5.90
	7	7	9	9	9	9	-	-	2.05	2.05	2.64	2.64	2.64	2.64	-	-	14.66	5.50
	7	7	7	12	14	14	-	-	1.79	1.79	1.79	3.07	3.57	3.57	-	-	15.57	5.88
	7	7	7	12	12	14	-	-	1.82	1.82	1.82	3.12	3.12	3.64	-	-	15.33	5.89
	7	7	7	12	12	12	-	-	1.91	1.91	1.91	3.28	3.28	3.28	-	-	15.55	5.90
	7	7	7	9	14	18	-	-	1.77	1.77	1.77	2.28	3.54	4.55	-	-	15.68	5.87
	7	7	7	9	14	14	-	-	1.84	1.84	1.84	2.36	3.67	3.67	-	-	15.21	5.90
	7	7	7	9	12	18	-	-	1.80	1.80	1.80	2.32	3.09	4.63	-	-	15.45	5.89
	7	7	7	9	12	14	-	-	1.92	1.92	1.92	2.47	3.30	3.84	-	-	15.38	5.90
	7	7	7	9	12	12	-	-	1.95	1.95	1.95	2.51	3.35	3.35	-	-	15.05	5.90
	7	7	7	9	9	18	-	-	1.91	1.91	1.91	2.46	2.46	4.90	-	-	15.54	5.90
	7	7	7	9	9	14	-	-	1.96	1.96	1.96	2.53	2.53	3.93	-	-	14.87	5.90
	7	7	7	9	9	12	-	-	2.05	2.05	2.05	2.64	2.64	3.52	-	-	14.95	5.65
	7	7	7	9	9	9	-	-	2.05	2.05	2.05	2.64	2.64	2.64	-	-	14.07	5.20
	7	7	7	7	14	18	-	-	1.80	1.80	1.80	1.80	3.60	4.63	-	-	15.45	5.89
	7	7	7	7	14	14	-	-	1.92	1.92	1.92	3.84	3.84	-	-	-	15.37	5.90
	7	7	7	7	12	18	-	-	1.84	1.84	1.84	1.84	3.15	4.72	-	-	15.21	5.90
	7	7	7	7	12	14	-	-	1.95	1.95	1.95	1.95	3.35	3.90	-	-	15.04	5.90
	7	7	7	7	12	12	-	-	2.05	2.05	2.05	2.05	3.52	3.52	-	-	15.24	5.79
	7	7	7	7	9	24	-	-	1.79	1.79	1.79	1.79	2.30	6.12	-	-	15.57	5.88
	7	7	7	7	9	18	-	-	1.93	1.93	1.93	1.93	2.49	4.97	-	-	15.21	5.90
	7	7	7	7	9	14	-	-	2.05	2.05	2.05	2.05	2.64	4.10	-	-	14.94	5.65
	7	7	7	7	9	12	-	-	2.05	2.05	2.05	2.05	2.64	3.52	-	-	14.36	5.35
	7	7	7	7	9	9	-	-	2.05	2.05	2.05	2.05	2.64	2.64	-	-	13.48	4.89
	7	7	7	7	7	24	-	-	1.82	1.82	1.82	1.82	6.24	-	-	-	15.33	5.89
	7	7	7	7	7	18	-	-	1.96	1.96	1.96	1.96	1.96	5.05	-	-	14.87	5.90
	7	7	7	7	7	14	-	-	2.05	2.05	2.05	2.05	2.05	4.10	-	-	14.35	5.35
	7	7	7	7	7	12	-	-	2.05	2.05	2.05	2.05	2.05	3.52	-	-	13.77	5.05
	7	7	7	7	7	9	-	-	2.05	2.05	2.05	2.05	2.05	2.64	-	-	12.89	4.57
	7	7	7	7	7	7	-	-	2.05	2.05	2.05	2.05	2.05	2.05	-	-	12.30	4.24
7 Room	7	9	9	9	9	9	-	-	1.78	2.30	2.30	2.30	2.30	2.30	2.30	-	15.57	5.88
	7	9	9	9	9	9	-	-	1.77	1.77	2.28	2.28	2.28	3.04	-	-	15.69	5.87
	7	7	9	9	9	9	-	-	1.82	1.82	2.34	2.34	2.34	2.34	-	-	15.34	5.89
	7	7	7	9	9	9	14	-	1.77	1.77	1.77	2.28	2.28	3.54	-	-	15.69	5.87
	7	7	7	9	9	9	12	-	1.80	1.80	1.80	2.32	2.32	2.32	3.09	-	15.45	5.89
	7	7	7	9	9	9	9	-	1.91	1.91	1.91	2.46	2.46	2.46	2.46	-	15.55	5.90
	7	7	7	7	9	12	12	-	1.79	1.79	1.79	1.79	2.30	3.07	3.07	-	15.57	5.88
	7	7	7	7	9	9	14	-	1.80	1.80	1.80	1.80	2.32	2.32	3.60	-	15.45	5.89
	7	7	7	7	9	9	12	-	1.83	1.83	1.83	1.83	2.36	2.36	3.15	-	15.21	5.90
	7	7	7	7	9	9	9	-	1.93	1.93	1.93	1.93	2.49	2.49	2.49	-	15.21	5.90
	7	7	7	7	7	12	14	-	1.79	1.79	1.79	1.79	3.07	3.57	-	-	15.57	5.88
	7	7	7	7	7	12	12	-	1.82	1.82	1.82	1.82	3.12	3.12	-	-	15.33	5.89
	7	7	7	7	7	9	18	-	1.77	1.77	1.77	1.77	2.28	4.55	-	-	15.68	5.87
	7	7	7	7	7	9	14	-	1.84	1.84	1.84	1.84	1.84	2.36	3.67	-	15.21	5.90
	7	7	7	7	7	9	12	-	1.92	1.92	1.92	1.92	2.47	3.30	-	-	15.38	5.90
	7	7	7	7	7	9	9	-	1.96	1.96	1.96	1.96	1.96	2.53	2.53	-	14.87	5.90
	7	7	7	7	7	7	18	-	1.80	1.80	1.80	1.80	1.80	4.63	-	-	15.45	5.89
	7	7	7	7	7	7	14	-	1.92	1.92	1.92	1.92	1.92	3.84	-	-	15.37	5.90
	7	7	7	7	7	7	12	-	1.95	1.95	1.95	1.95	1.95	3.35	-	-	15.04	5.90
	7	7	7	7	7	7	9	-	2.05	2.05	2.05	2.05	2.05	2.64	-	-	14.94	5.65
	7	7	7	7	7	7	9	-	2.05	2.05	2.05	2.05	2.05	2.64	-	-	14.36	5.35
	7	7	7	7	7	7	7	-	2.05	2.05	2.05	2.05	2.05	2.05	-	-	14.35	5.35
8 Room	7	7	7	7	7	9	9	9	1.77	1.77	1.77	1.77	1.77	2.28	2.28	2.28	15.69	5.87
	7	7	7	7	7	7	9	9	1.80	1.80	1.80	1.80	1.80	2.32	2.32	2.32	15.45	5.89
	7	7	7	7	7	7	7	12	1.79	1.79	1.79	1.79	1.79	3.07	3.07	3.07	15.57	5.88
	7	7	7	7	7	7	7	9	1.84	1.84	1.84	1.84	1.84	1.84	1.84	2.36	15.21	5.90
	7	7	7	7	7	7	7	7	1.92	1.92	1.92	1.92	1.92	1.92	1.92	1.92	15.37	5.90

Note: •Cooling capacity is based on 27°CDB/19°CWB(indoor temperature),35°CDB(outdoor temperature)
•Pipe Length: 5 m (Outdoor unit to Branch box), 3 m (Branch box to Indoor unit)
•Height difference: 0 m (Outdoor unit to Indoor unit)
•The values in this table should be used only as a guide. These values are calculated at standard conditions.
To fix your selection of models, select them according to "Model Selection" in the D&T manual.

8 Rooms Multi heating

AOYG45LBT8	Combination of Indoor Unit								HEATING OPERATION									
									Heating Capacity								Input power	
									Room 1	Room 2	Room 3	Room 4	Room 5	Room 6	Room 7	Room 8	Total	

8 Rooms Multi heating

AOYG45LBT8	Combination of Indoor Unit								HEATING OPERATION										Input power
									Room 1	Room 2	Room 3	Room 4	Room 5	Room 6	Room 7	Room 8	Total		
									kW	kW	kW	kW	kW	kW	kW	kW	kW		
4 Room	7	7	14	18	-	-	-	-	2.37	2.37	4.80	5.86	-	-	-	-	-	15.40	4.75
	7	7	14	14	-	-	-	-	2.37	2.37	4.80	4.80	-	-	-	-	-	14.34	4.21
	7	7	12	24	-	-	-	-	2.36	2.36	3.94	7.87	-	-	-	-	-	16.53	5.11
	7	7	12	18	-	-	-	-	2.37	2.37	3.96	5.86	-	-	-	-	-	14.56	4.46
	7	7	12	14	-	-	-	-	2.37	2.37	3.96	4.80	-	-	-	-	-	13.50	4.00
	7	7	9	24	-	-	-	-	2.37	2.37	2.99	7.91	-	-	-	-	-	15.64	4.91
	7	7	9	18	-	-	-	-	2.37	2.37	2.99	5.86	-	-	-	-	-	13.59	4.10
	7	7	7	24	-	-	-	-	2.37	2.37	2.37	7.91	-	-	-	-	-	15.02	4.60
	7	7	18	14	-	-	-	-	2.37	2.37	3.96	5.86	-	-	-	-	-	12.57	3.90
	12	12	12	12	14	-	-	-	3.51	3.51	3.51	3.51	4.26	-	-	-	-	18.32	5.98
	12	12	12	12	12	-	-	-	3.58	3.58	3.58	3.58	3.58	-	-	-	-	17.90	5.98
	9	12	12	14	14	-	-	-	2.66	3.52	3.52	4.27	4.27	-	-	-	-	18.26	5.98
9	12	12	12	14	-	-	-	2.71	3.59	3.59	3.59	4.35	-	-	-	-	17.84	5.98	
9	12	12	12	12	-	-	-	2.85	3.77	3.77	3.77	3.77	-	-	-	-	17.95	5.87	
9	9	14	14	14	-	-	-	2.67	2.67	4.28	4.28	4.28	-	-	-	-	18.19	5.98	
9	9	12	14	14	-	-	-	2.66	2.66	3.52	4.26	5.21	-	-	-	-	18.30	5.98	
9	9	12	14	14	-	-	-	2.72	2.72	3.60	4.37	4.37	-	-	-	-	17.77	5.98	
9	9	12	12	18	-	-	-	2.71	2.71	3.58	3.58	5.30	-	-	-	-	17.88	5.98	
9	9	12	12	14	-	-	-	2.86	2.86	3.78	3.78	4.58	-	-	-	-	17.86	5.70	
9	9	12	12	12	-	-	-	2.89	2.89	3.83	3.83	3.83	-	-	-	-	17.28	5.43	
9	9	9	14	18	-	-	-	2.71	2.71	2.71	4.36	5.32	-	-	-	-	17.82	5.98	
9	9	9	14	14	-	-	-	2.86	2.86	2.86	4.59	4.59	-	-	-	-	17.77	5.56	
9	9	9	12	18	-	-	-	2.85	2.85	2.85	3.78	5.59	-	-	-	-	17.92	5.87	
9	9	9	12	14	-	-	-	2.90	2.90	2.90	3.84	4.65	-	-	-	-	17.19	5.32	
9	9	9	9	12	-	-	-	2.97	2.97	2.97	3.93	3.93	-	-	-	-	16.78	5.13	
9	9	9	9	24	-	-	-	2.70	2.70	2.70	2.70	2.14	-	-	-	-	17.94	5.98	
9	9	9	9	18	-	-	-	2.89	2.89	2.89	2.89	5.67	-	-	-	-	17.25	5.43	
9	9	9	9	14	-	-	-	2.97	2.97	2.97	2.97	4.77	-	-	-	-	16.67	5.11	
9	9	9	9	12	-	-	-	2.99	2.99	2.99	2.99	3.96	-	-	-	-	15.92	5.07	
9	9	9	9	9	-	-	-	2.99	2.99	2.99	2.99	2.99	-	-	-	-	14.95	4.60	
7	12	14	14	14	-	-	-	2.10	3.51	4.25	4.25	4.25	-	-	-	-	18.37	5.98	
7	12	12	14	14	-	-	-	2.14	3.57	3.57	4.33	4.33	-	-	-	-	17.55	5.98	
7	12	12	12	18	-	-	-	2.13	3.56	3.56	3.56	3.56	-	-	-	-	18.06	5.98	
7	12	12	12	14	-	-	-	2.25	3.76	3.76	3.76	4.56	-	-	-	-	18.10	5.87	
7	12	12	12	12	-	-	-	2.28	3.81	3.81	3.81	3.81	-	-	-	-	17.52	5.56	
7	9	14	14	18	-	-	-	2.09	2.64	4.24	4.24	5.18	-	-	-	-	18.40	5.98	
7	9	14	14	14	-	-	-	2.14	2.71	4.34	4.34	4.34	-	-	-	-	17.88	5.98	
7	9	12	14	18	-	-	-	2.13	2.69	3.57	4.32	5.28	-	-	-	-	17.99	5.98	
7	9	12	14	14	-	-	-	2.26	2.85	3.77	4.57	4.57	-	-	-	-	18.01	5.70	
7	9	12	12	18	-	-	-	2.25	2.84	3.76	3.76	5.56	-	-	-	-	18.16	5.98	
7	9	12	12	14	-	-	-	2.28	2.88	3.82	3.82	4.63	-	-	-	-	17.43	5.43	
7	9	12	12	12	-	-	-	2.35	2.96	3.92	3.92	3.92	-	-	-	-	17.09	5.23	
7	9	9	18	18	-	-	-	2.13	2.69	2.69	5.27	5.27	-	-	-	-	18.04	5.98	
7	9	9	14	18	-	-	-	2.25	2.84	2.84	4.56	5.57	-	-	-	-	18.07	5.87	
7	9	9	14	14	-	-	-	2.29	2.89	2.89	4.64	4.64	-	-	-	-	17.34	5.32	
7	9	9	12	24	-	-	-	2.12	2.68	2.68	3.55	7.08	-	-	-	-	18.11	5.98	
7	9	9	12	18	-	-	-	2.28	2.88	2.88	3.81	5.64	-	-	-	-	17.49	5.56	
7	9	9	12	14	-	-	-	2.35	2.97	2.97	3.93	4.76	-	-	-	-	16.97	5.16	
7	9	9	12	12	-	-	-	2.37	2.98	2.98	3.95	3.95	-	-	-	-	16.24	5.08	
7	9	9	9	24	-	-	-	2.17	2.74	2.74	2.74	7.24	-	-	-	-	17.63	5.98	
7	9	9	9	18	-	-	-	2.35	2.96	2.96	2.96	5.81	-	-	-	-	17.05	5.23	
7	9	9	9	14	-	-	-	2.37	2.99	2.99	2.99	4.79	-	-	-	-	16.12	5.07	
7	9	9	9	12	-	-	-	2.37	2.99	2.99	2.99	3.96	-	-	-	-	15.30	4.75	
7	9	9	9	9	-	-	-	2.37	2.99	2.99	2.99	2.99	-	-	-	-	14.33	4.33	
7	7	14	14	18	-	-	-	2.12	2.12	4.30	4.30	5.25	-	-	-	-	18.10	5.98	
7	7	14	14	14	-	-	-	2.25	2.25	4.55	4.55	4.55	-	-	-	-	18.16	5.70	
7	7	12	18	18	-	-	-	2.11	2.53	2.11	2.11	5.23	-	-	-	-	17.51	5.98	
7	7	12	14	18	-	-	-	2.16	2.16	3.62	4.38	5.35	-	-	-	-	17.68	5.98	
7	7	12	14	14	-	-	-	2.28	2.28	3.80	4.61	4.61	-	-	-	-	17.58	5.43	
7	7	12	12	24	-	-	-	2.11	2.11	3.52	3.52	7.03	-	-	-	-	18.29	5.98	
7	7	12	12	14	-	-	-	2.35	2.35	3.92	3.92	4.75	-	-	-	-	17.28	5.23	
7	7	12	12	12	-	-	-	2.36	2.36	3.94	3.94	3.94	-	-	-	-	16.54	5.11	
7	7	9	18	18	-	-	-	2.16	2.16	2.72	5.34	5.34	-	-	-	-	17.73	5.98	
7	7	9	14	24	-	-	-	2.11	2.11	2.67	4.28	6.05	-	-	-	-	18.22	5.98	
7	7	9	14	18	-	-	-	2.27	2.27	2.67	4.61	5.62	-	-	-	-	17.64	5.58	
7	7	9	14	14	-	-	-	2.35	2.35	2.96	4.75	4.75	-	-	-	-	17.16	5.16	
7	7	9	12	24	-	-	-	2.15	2.15	2.72	3.60	7.18	-	-	-	-	17.80	5.98	
7	7	9	12	18	-	-	-	2.34	2.34	2.96	3.92	5.80	-	-	-	-	17.36	5.32	
7	7	9	12	14	-	-	-	2.36	2.36	2.98	3.95	4.78	-	-	-	-	16.43	5.08	
7	7	9	12	12	-	-	-	2.37	2.37	2.99	3.96	3.96	-	-	-	-	15.65	4.91	
7	7	9	9	24	-	-	-	2.27	2.27	2.86	2.86	7.56	-	-	-	-	17.81	5.70	
7	7	9	9	18	-	-	-	2.36	2.36	2.98	2.98	4.83	-	-	-	-	16.51	5.11	
7	7	9	9	14	-	-	-	2.37	2.37	2.99	2.99	4.80	-	-	-	-	15.52	4.75	
7	7	9	9	12	-	-	-	2.37	2.37	2.99	2.99	3.96	-	-	-	-	14.68	4.46	
7	7	9	9	9	-	-	-	2.37	2.37	2.99	2.99	2.99	-	-	-	-	13.71	4.10	
7	7	7	18	18	-	-	-	2.26	2.26	2.26	5.58	5.58	-	-	-	-	17.95	5.87	
7	7	7	14	24	-	-	-	2.14	2.14	2.14	4.34	7.15	-	-	-	-	17.91	5.98	
7	7	7	14	18	-	-	-	2.30	2.30	2.30	4.65	5.68	-	-	-	-	17.22	5.32	
7	7	7	14	14	-	-	-	2.36	2.36	2.36	4.77	4.77	-	-	-	-	16.62	5.08	
7	7	7	12	24	-	-	-	2.25	2.25	2.25	3.77	7.52	-	-	-	-	18.05	5.87	
7	7	7	12	18	-	-	-	2.35	2.35	3.93	3.93	5.82	-	-	-	-	16.81	5.16	
7	7	7	12	14	-	-	-	2.37	2.37	2.37	3.96	4.80	-	-	-	-	15.87	4.91	
7	7	7	12	12	-	-	-	2.37	2.37	2.37	3.96	3.96	-	-	-	-	15.03	4.60	
7	7	7	9	24	-	-	-	2.29	2.29	2.29	2.89	7.63	-	-	-	-	17.38	5.43	
7	7	7	9	18	-	-	-	2.37	2.37	2.37	2.99	5.86	-	-	-	-	15.96	5.07	
7	7	7	9	14	-	-	-	2.37	2.37	2.37	2.99	4.80	-	-	-	-	14.90	4.46	
7	7	7	9	12	-	-	-	2.37	2.37	2.37	2.99	3.96	-	-	-	-	14.06	4.21	
7	7	7	9	9	-	-	-	2.37	2.37	2.37	2.99	2.99	-	-	-	-	13.09	3.90	
7	7	7	7	24	-	-	-	2.35	2.35	2.35	2.35	7.83	-	-	-	-	17.22	5.23	
7	7	7	7	18	-	-	-	2.37	2.37	2.37	2.37	5.86	-	-	-	-	15.34	4.75	
7	7	7	7	14	-	-	-	2.37	2.37</										





































Note: •Heating capacity is based on 20°CDB(indoor temperature), 7°CDB/6°CWB(outdoor temperature)
•Pipe Length: 5 m (Outdoor unit to Branch box), 3 m (Branch box to Indoor unit)
•Height difference: 0 m (Outdoor unit to Indoor unit)
•The values in this table should be used only as a guide. These values are calculated at standard conditions.
To fix your selection of models, select them according to "Model Selection" in the D&T manual.

8 Rooms Multi heating

























AOYG45LBT8	Combination of Indoor Unit								HEATING OPERATION											Input power																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
									Heating Capacity																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
									Room 1	Room 2	Room 3	Room 4	Room 5	Room 6	Room 7	Room 8	Total																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																										
																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											</

Note: •Heating capacity is based on 20°CDB(indoor temperature), 7°CDB/6°CWB(outdoor temperature)
•Pipe Length: 5 m (Outdoor unit to Branch box), 3 m (Branch box to Indoor unit)
•Height difference: 0 m (Outdoor unit to Indoor unit)
•The values in this table should be used only as a guide. These values are calculated at standard conditions.
To fix your selection of models, select them according to "Model Selection" in the D&T manual.

OPTIONAL PARTS FOR SPLIT & MULTI SPLIT

Type			Wall Mounted						Duct						Cassette				Floor	Ceiling/Floor	Ceiling		
			Compact			Large			Slim		Medium static	Medium static	High static		Compact		Large						
			ASIG 09/12/LCA	ASIG 07/09/12/14/LUCA	ASIG 07/09/12/14/LMCA	ASIG 07/09/12/LUCC	ASIG 18/30/LCA 24/LCC	ASIG 30/36/LMTA	ARIG 07/09/LTA 12/14/LTB	ARIG 18/LTB	ARIG 22/24/36/45/LMLA 30/36/LMLE	ARIG 12/14/18/24/30/45/54/LHTBP	ARIG 45/54/LHTA	ARIG 60/LHTA	ARIG 72/90/LHTA	AUIG 07/09/LVA 12/14/LVB	AUIG 22/24/LVA	AUIG 30/36/LRLE 36/45/54/LRLA				AUIG 18/24/30/36/45/54/LRLB	AGIG 09/12/14/LVCA
Controllers	Wired Remote Controller																						
																							
																							
																							
Simple Remote Controller																							
	For 8 Rooms Multi																						
Others	IR Receiver Kit with Wireless Remote Controller																						
																							
																							
		For Duct For Cassette																					
Human Sensor Kit																							
	Remote Sensor Unit																						
Others	Auto Louver Grille Kit																						
																							
																							
																							
Others	Long Life Filter																						
																							
																							
																							
Others	Flange																						
																							
																							
																							
Others	Drain Pump Unit																						
																							
																							
																							
Others	Wide Panel																						
																							
																							
																							
Others	Panel Spacer																						
																							
																							
																							
Others	Fresh Air Intake Kit																						
																							
Others	Air Outlet Shutter Plate																						
Others	Insulation for High Humidity																						
Others	Half Concealed Kit																						
Others	Remote controller holder																						

Optional parts list (Interface /Communication Kit/External Connect Kit)

Type			Indoor unit																		Outdoor unit				
			Wall Mounted			Duct					Cassette			Floor	Ceiling/Floor	Ceiling	Single-phase		3-phase		Single Split	Single Split	Small Multi	Medium Multi	Large Multi
			Compact	Large		Slim	Medium static	High static			Compact	Large					Single Split	Single Split	Single Split	Single Split					
Interface	Wireless LAN Interface		● UTY-TFNXZ1			● UTY-TFNXZ1					● UTY-TFNXZ1			● UTY-TFNXZ1	● UTY-TFNXZ1	● UTY-TFNXZ1									
			● FJ-RC-WIFI-1			● FJ-RC-WIFI-1					● FJ-RC-WIFI-1			● FJ-RC-WIFI-1	● FJ-RC-WIFI-1	● FJ-RC-WIFI-1									
	KNX Interface		● FJ-RC-KNX-Ti			● FJ-RC-KNX-Ti					● FJ-RC-KNX-Ti			● FJ-RC-KNX-Ti	● FJ-RC-KNX-Ti	● FJ-RC-KNX-Ti									
													● UTY-VMSX												
Communication Kit	Modbus Converter												● UTY-VMSX												
			● FJ-RC-MBS-1	● FJ-RC-MBS-1		● FJ-RC-MBS-1					● FJ-RC-MBS-1			● FJ-RC-MBS-1	● FJ-RC-MBS-1	● FJ-RC-MBS-1									
	MODBUS Interface		● FJ-RC-MBS-1	● FJ-RC-MBS-1		● FJ-RC-MBS-1					● FJ-RC-MBS-1			● FJ-RC-MBS-1	● FJ-RC-MBS-1	● FJ-RC-MBS-1									
																									
External Connect Kit	Communication Kit		● UTY-TWBXF	● UTY-XCBXZ2		● UTY-TWRX																			
						● UTY-XWNX																			
	External input and output PCB					● UTY-XCSXZ1		● UTY-XCSX								● UTY-XCSX									
						● UTZ-GXXB										● UTZ-GKRA									
External Control Set	External input and output PCB Bracket							● UTZ-GXNA								● UTY-KWZXZG									
								● UTY-KWZXZG																	
	For Indoor Unit *Duct type is excluded.					● UTY-XWZX										● UTY-XWZX	● UTY-XWZX	● UTY-XWZX	● UTY-XWZX						
						● UTY-XWZXZ5																			
External Control Set	For Outdoor Unit																								
																									
	For Outdoor Unit																								
																									
External Control Set	For Indoor Unit (Duct type only) Use to connect with various peripheral devices and air conditioner PC board.							● UTD-ECSSA			● UTD-ECSSA			● UTD-ECSSA											
																									
	For Outdoor Unit																								
																									

NEW

Wired Remote Controller (Touch Panel)

UTY-RNRYZ1

Max. Controllable
16 indoor units

Features

Easy operation by high-definition large STN-LCD touch panel screen

- Easy finger touch operation with LCD panel
- Built-in weekly/Daily timer(ON/OFF,Temp.,Mode)
- Backlight enables easy operation in a darkened room
- Room temperature display
- Control up to 16 indoor units
- Corresponds to 12 different languages (English, Chinese, French, German, Spanish, Russian, Polish, Italian, Greek, Portuguese, Turkish and Dutch)
- 2-wire type


High performance and compact size

In addition to the individual control, weekly timer, and various energy saving controls can be realized using one remote controller only.



Accurate and comfortable control


Indoor temperature can be detected accurately by the inclusion of a thermo sensor in the body of the wired controller.



Various energy saving control

Auto OFF timer

- The indoor unit automatically is turned off when it reaches to the preset operating time frame.
- The time frame of the "Auto off timer" can be flexibly scheduled.
- Can be set off time 30 to 240 minutes



Ex.) At interval time hour (17:00 to 24:00) to prevent forgetting to turn off
Set off time : 1 hour

2 schedules Weekly Timer

Set Temperature Auto Return

Set Temperature Upper and Lower Limit Setting

Specifications

Model name	UTY-RNRYZ1
Power Source	DC 12 V
Dimensions (H × W × D) (mm)	120 × 120 × 20.4
Weight (g)	220

DC12 V is supplied by the indoor unit.

Function list

External Control		Input					Output					
		Start/Stop	Peak cut	Low noise	Priority	Emergency stop	Operation status	Error status	Fresh Air	Auxiliary Heater	Base heater	Preparation
Wall Mounted												
Compact	ASYG09/12LTCA (A*)	●2					●2	●2				
	ASYG07/09/12/14LUCA (A*)	●2					●2	●2				
	ASYG07/09/12/14LMCA (B*)	●2					●2	●2				
Large	ASYG18/30LFCA	●1					●1					
	ASYG24LFCC	●1					●1	●3				
	ASYG30/36LMTA (C*)	●1					●1	●3				
Duct												
Slim	ARYG07/09LLTA	●4					●4		●4	●4		
	ARYG12/14/18LLTB	●4					●4		●4	●4		
	ARYG24/36/45LMLA	●4					●4		●4	●4		
Medium Static	ARYG30/36LMLE	●4					●4		●4	●4		
	ARYG12/14/18/24/30/36/45/54LHTBP (D*)	●0*					●3	●3	●3	●3		
	ARYG45/54LHTA	●4					●4		●4	●4		
High Static	ARYG60LHTA	●4					●4	●4	●4	●4		
	ARYC72/90LHTA	●4					●4	●4	●4	●4		
Cassette												
Compact	AUYG07/09LVLA	●4					●4		●0*			
	AUYG12/14/18LVLB	●4					●4		●0*			
	AUYG24LVLA	●4					●4		●0*			
Large	AUYG30/36LRLE	●4					●4		●0*			
	AUYG36/45/54LRLA	●4					●4		●0*			
	AUXG18/24/30/36/45/54LRLB (E*)	●0*					●3	●3	●3	●3		
Floor												
	AGYG09/12/14LVCA	●1					●1					
Floor Ceiling												
	ABYG14LVTB	●1					●1					
	ABYG18LVTB	●1					●1					
	ABYG24LVTB	●1					●1					
Ceiling												
	ABYG30/36LRTE	●1					●1		●4			
	ABYG36/45/54LRTA	●1					●1		●4			
Single phase												
Single Split	AOYG45/54LETL		●6	●6			●6	●6			●7	
8 Rooms Multi	AOYG45LBTB		●6	●6	●6		●6	●6				
Simultaneous Multi	AOYG36/45LBTB		●6	●6			●6	●6				
3Phase												
Single Split	AOYG36/45/54/60LATT		●5	●5			●5	●5				
	AOYA72/90LALT		●5	●5			●5	●5			●7	
Simultaneous Multi	AOYG36/45/54LATT		●5	●5			●5	●5				

A* : UTY-TWBXF Communication Kit required

B* : UTY-XCBXZ2 Communication Kit required

C* : UTY-XCSXZ1 External input and output PCB/UTZ-GXXB External input and output PCB Box required

D* : UTY-XCSX External input and output PCB/UTZ-GXNA External input and output PCB Bracket required

E* : UTY-XCSX External input and output PCB/UTZ-GXRA External input and output PCB Box required

0* : Optional part is not required

Communication Kit



UTY-TWBXF/UTY-XCBXZ2

External input and output PCB




UTY-XCSXZ1



UTY-XCSX

External input and output PCB Box



UTZ-GXXB




UTZ-GXRA

External input and output PCB Bracket




UTZ-GXNA

External Connect Kit For Indoor Unit



1=UTY-XWZX



2=UTY-XWZXZ5



3=UTY-XWZXZG

External Control Set For Indoor Unit



4=UTD-ECS5A


External Connect Kit For Outdoor unit



5=UTY-XWZXZ2



6=UTY-XWZXZ3



7=UTY-XWZXZ4

Wired Remote Controller

UTY-RVNYM



Features


Hi-grade individual control using various functions.

- 3.7-inch LCD backlight screen.
- Supporting various Energy Saving functions with simple operation.
- Multiple Language Support.
(English, German, French, Spanish, Russian, Portuguese, Italian, Greek, and Turkish)

Max. Controllable
16 indoor units

High visibility and Easy operation

- Icon display of effectual functions.
- Main functions in large icons: "Mode", "Set Temp", and "Fan".
- Easy to operate by Control guide display.
- Simple operation with easy 4-way navigation pad.



High performance and compact size


- In addition to the individual control, various energy saving controls can be realized using only one remote controller.



Various energy saving control

Weekly Timer function

- Can be set up to 8 times per day (On/Off, mode, Temp)
- 2 pattern settings (i.e. Summer/Winter setting) are available.



Auto OFF Timer

Set Temperature Auto Return

Set Temperature Upper and Lower Limit Setting

Specifications

Model name	UTY-RVNYM
Power Source	DC 12 V
Dimensions (H × W × D) (mm)	120 × 120 × 21.3
Weight (g)	220

DC12 V is supplied by the indoor unit.

NEW

Wired Remote Controller

UTY-RLRY




Features

- Various timer setup (ON / OFF / WEEKLY) are possible.
- The room temperature can be controlled by detecting the temperature accurately with Built-in thermo sensor.
- When a failure occurs, the error code is displayed.
- Error history. (Last 16 error codes can be accessed.)
- 2-wire type

Max. Controllable
16 indoor units

High visibility and easy operation

- "Mode", "Set Temp", and "Fan" are displayed at large size on the top screen.
- Each function to be set is indicated by an icon.
- Control guide is displayed and operation is simple and straightforward.



High performance and compact size

- In addition to the individual control, weekly timer, and various energy saving controls can be realized using only one remote controller.



Various energy saving control


Auto-off timer

- The indoor unit automatically turns off after a set time has passed.

Weekly timer function

Set temperature auto return

Set temperature upper and lower limit setting



Specifications

Model name	UTY-RLRY
Power Source	DC 12 V
Dimensions (H × W × D) (mm)	120 × 120 × 17
Weight (g)	170

DC12 V is supplied by the indoor unit.


Wireless LAN Interface

UTY-TFNXZ1




Features

- It is the most advanced solution to remotely manage an Air Conditioning system using all sort of mobile devices such as Smartphones, and tablets.
- No separate external power supply required
- Can be used for single indoor units and multi system indoor units




Basic control

- Turning the units on and off
- Mode control (Heat, Cool, Dry, Auto, Fan)
- Fan speed setting
- Louver position (Airflow direction setting)
- Room temperature setting
- Timer operation setting (Weekly timer)
- Economy mode setting




Multiple air conditioning management

- Multiple air conditioning management at difference locations.



Error display & E-mail notification

- Alerts e-mail notification
- Air conditioning malfunction display
- It enables rapid service response when error occurs.



Specifications

Model name	UTY-TFNXZ1
Dimensions (H × W × D) (mm)	71×38×15
Weight (g)	85

Wireless LAN Interface


FJ-RC-WIFI-1



Features




- It is the most advanced solution to remotely manage an Air Conditioning system using all sort of mobile devices such as Smartphones, Tablets and PC
- No separate external power supply required
- Can be used for single indoor units and group controlled (up to 16) indoor units



Basic control

- Turning the units on and off
- Mode control (Heat, Cool, Dry, Auto, Fan)
- Fan speed setting
- Louver position (Airflow direction setting)
- Room temperature display
- Set temperature control
- Multi Language
- One Scene and Timer



Advanced control (Optional functions)

- Climate working modes (ECO, Comfort, Powerful) (future release)
- Schedulable functionalities (ON/OFF, Modes, Set point temperature, Fan Speed, Louver position)
- Set temperature limitation (future release)
- Multiple Scenes & Timers and Calendar function

Notifications and history

- Alerts e-mail notification (future release)
- Air conditioning malfunction alerts
- Connectivity monitoring and alerts
- History (future release)

Specifications

Model name	FJ-RC-WIFI-1
Dimensions (H × W × D) (mm)	70×108×28
Weight (g)	80

MODBUS® Convertor for Indoor Unit

UTY-VMSX




Max. Connectable
1 Single indoor unit

Features

The MODBUS Convertor allows a complete integration of air conditioners into MODBUS Networks.

- Simple installation due to small and compact size.
- No separate external power supply required.
- The MODBUS Convertor must be connected one by one in the indoor unit.
- The MODBUS Controller permits central monitoring and control of air conditioners from BMS/Central/Home Controller.




Basic control

- Turning the units on and off
- Mode control (Heat, Cool, Dry, Auto, Fan)
- Fan speed setting
- Louver position (Airflow direction setting)
- Room temperature setting and display
- Economy mode setting
- Error status

Easy Installation

Flexible installation locations with neat wirings are feasible since no power supply cable is used in the convertor.



Specifications

Model name		UTY-VMSX	
Power supply		AC220/240V 50/60Hz AC208/230V 60Hz	
Input Power		W	Max. 1.2
Temperature		Operating / Packaged °C (°F)	0~46(32~114) / -10~60(14~140)
Humidity		Operating / Packaged %	0~95 / 0~95
Dimensions (H×W×D)(in.)		mm (in.)	43 × 117 × 140
Weight(oz)		g (oz)	200(7)
Maximum Connectable indoor unit number per 1 MODBUS Convertor			1

MODBUS® Interface


FJ-RC-MBS-1



Features

The MODBUS Interface allows a complete integration of air conditioners into MODBUS Networks.

- Simple installation due to small and compact size.
- No separate external power supply required.
- The MODBUS Interface permits central monitoring and control of air conditioners from BMS.



KNX® Interface


FJ-RC-KNX-1i



Features

The KNX Interface allows a complete integration of air conditioners with KNX Network systems.

- Simple installation due to small and compact size.
- No separate external power supply required (just KNX bus power).
- Can be used for single indoor units and group controlled (up to 16) indoor units.



Specifications

Model name	FJ-RC-MBS-1	FJ-RC-KNX-1i
Dimensions (H × W × D) (mm)	93×53×58	70×70×28
Weight (g)	85	70

Auto Louver Grille Kit

UTD-GXTA-W / UTD-GXTB-W / UTD-GXTC-W




Features

Simple flat Auto Louver will provide comfort airflow and harmonize with luxury interior.




Flexible Control

- **Operation with indoor unit**
Auto Louver can be operated by synchronizing remote controller of indoor unit.
- **UP and Down auto swing**
 - Auto airflow direction and auto swing
 - 4 steps selectable
- **Auto-closing louver**
When operation of indoor unit is stopped, the louver will automatically close.



Dimensions



Model Name	W1	W2	H1	H2	D1	D2
UTD-GXTA-W	683	645	180	148	9	84
UTD-GXTB-W	883	845				
UTD-GXTC-W	1,083	1,045				

Unit:mm

Specifications

Model name			UTD-GXTA-W	UTD-GXTB-W	UTD-GXTC-W
Applicable Indoor Unit			ARYG07/09LLTA ARYG12/14LLTB ARXD04/07/09/12/14GALH (For VRF) ARXK07/09/12/14GCLH (For VRF)	ARYG18LLTB ARXD18GALH (For VRF) ARXK18GCLH (For VRF)	ARXD24GALH (For VRF) ARXK24GCLH (For VRF)
Power Supply			Connecting with Control box of indoor unit		
Fixing of Auto Louver Grille			Screw fixing to Flange or Square Duct		
Extension Square Duct Limit			1.0m (Max. duct length between indoor unit and Grille)		
Net Dimension (H × W × D)		mm (inch)	180×683×(84+9) [7-3/32×26-7/8×(3-5/16+11/32)]	180×883×(84+9) [7-3/32×34-3/4×(3-5/16+11/32)]	180×1083×(84+9) [7-3/32×42-5/8×(3-5/16+11/32)]
Weight	Net	kg (lb.)	2.0 (4.4)	2.5 (5.6)	3.0 (6.7)
	Gross		3.0 (6.7)	3.5 (7.8)	4.0 (8.9)
Color			White		
Louver Motor			Stepping Motor		
Accessories			Fitting Flame, etc.		
Operation range	Cooling	°C (°F)	18 to 32 (64 to 90)		
		% RH	80% or less		
	Heating	°C (°F)	16 to 30 (60 to 88)		

REFRIGERANT PIPING PARTS

Connection Units

Separation Tube

UTP-SX236A / UTP-SX254A
For 3-phase simultaneous multi




UTP-SX354A

For 3-phase simultaneous multi



UTP-SX248A

For 8 Rooms Multi



Branch Box

UTP-PY03A / UTP-PY02A
For 8 Rooms Multi



3 zones type



2 zones type

OPTIONAL PARTS

Controllers

For Individual & Centralized Control

Wired Remote Controller
UTY-RNRYZ1 **NEW**



Wired Remote Controller
UTY-RLRY **NEW**



Wired Remote Controller
UTY-RVNYM



Wired Remote Controller
UTY-RNNYM







Simple Remote Controller
UTY-RSNYM







Central Remote Controller
UTY-DMMYM
For 8 Rooms Multi










Communication devices









Interface			
Wireless LAN Interface UTY-TFNXZ1 NEW	Wireless LAN Interface FJ-RC-WIFI-1	MODBUS® Convertor UTY-VMSX NEW	MODBUS® Interface FJ-RC-MBS-1
			



KNX® Interface FJ-RC-KNX-1i





Communication Kit/External input and output PCB/Box/Bracket			
Communication Kit UTY-TWBXF/UTY-XCBXZ2/UTY-TWRX For Compact Wall Mounted	External input and output PCB UTY-XCSXZ1 NEW	External input and output PCB Box UTZ-GXXB NEW	External input and output PCB Bracket UTZ-GXNA NEW
			

Others

For Duct type			
IR Receiver Kit UTY-LRHYM	IR Receiver Kit UTY-LBTYM NEW	Remote Sensor Unit UTY-XSZX New amenity space can be offered byinstalling the Remote sensor.	Auto Louver Grille Kit UTD-GXTA-W/UTD-GXTB-W For Slim Duct
			
Long Life Filter UTD-LF25NA/ UTD-LFNA/UTD-LFNB/ UTD-LFNC/UTDLF60KA	Flange UTD-RF204 (Round) UTD-SF045T (Square)	Drain Pump Unit UTZ-PX1NBA For Medium Static Pressure Duct	
			

For Cassette type			
IR Receiver Kit UTY-LRHYA2	IR Receiver Kit UTY-LBTYC NEW	Human Sensor Kit UTY-SHZXC NEW	Wide Panel UTG-AKXA-W
			
Panel Spacer UTG-BKXA-W	Fresh Air Intake Kit UTZ-VXAA For Compact Cassette	Fresh Air Intake Kit UTZ-VXRA For Cassette	Air Outlet Shutter Plate UTR-YDZB For Compact Cassette
			 Shuts the air outlet when only using as 3 blow out.

Air Outlet Shutter Plate UTR-YDZK	Insulation for High Humidity UTZ-KXGC/UTZ-KXRA For Compact Cassette type / Cassette type
 Shuts the air outlet when only using as 3 blow out.	

For Ceiling type	For Floor type	For Wall Mounted type
Drain Pump Unit UTR-DPB24T	Half Concealed Kit UTR-STA This kit is used to half conceal floor type indoor unit into the wall.	Remote controller holder UTZ-RXLA For ASYG07/09/12LLCC
		

VRF



AIRSTAGE™ VRF Systems can be designed to create an air conditioning solution to suit most buildings requirements.

AIRSTAGE™ VRF Systems can be designed to effectively provide an air conditioning solution from a large domestic residence through to a large scale commercial building.



- 130 All Type Lineup
- 132 AIRSTAGE™ Outline
- 134 AIRSTAGE™ series Common Features
- 141 AIRSTAGE™ Outdoor Units
 - AIRSTAGE™ VR-II Heat Recovery Modular Type
 - AIRSTAGE™ V-III Heat Pump Modular Type
 - AIRSTAGE™ V-II Heat Pump Modular Type
 - **NEW** AIRSTAGE™ J-III Heat pump type
 - AIRSTAGE™ J-IIS Heat pump type
- 170 Indoor Unit Lineup
- 176 Controller
- 200 VENTILATION
- 208 Optional Parts for VRF

All Type Lineup

Outdoor units		Capacity (kW)	12.1	14.0	15.1-15.5	22.4	28.0	33.5	40.0	45.0	50.4	55.9	61.5	67.0	73.5	78.5	85.0	90.0	95.0	100.5	107.0	112.0	118.5	123.5	130.0	135.0	140.0	145.0	150.0
HP			4	5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50	52	54
VR-II series	Space saving Page 142 ~																												
	Set Model				AJYA72GALH	AJYA90GALH	AJY108GALH	AJY126GALH	AJY144GALH	AJY162GALH	AJY180GALH	AJY198GALH	AJY216GALH	AJY234GALH		AJY252GALH	AJY270GALH	AJY288GALH	AJY306GALH	AJY324GALH	AJY342GALH	AJY360GALH	AJY378GALH	AJY396GALH	AJY414GALH	AJY432GALH			
	Energy efficiency Page 142 ~																												
	Set Model								AJY144GALHH				AJY198GALHH	AJY216GALHH	AJY234GALHH		AJY252GALHH	AJY270GALHH	AJY288GALHH	AJY306GALHH	AJY324GALHH	AJY342GALHH	AJY360GALHH	AJY378GALHH	AJY396GALHH				
V-III series	Space saving Page 150 ~																												
	Set Model				AJY072LALBH	AJY090LALBH	AJY108LALBH	AJY126LALBH	AJY144LALBH	AJY162LALBH	AJY180LALBH	AJY198LALBH	AJY216LALBH	AJY234LALBH		AJY252LALBH	AJY270LALBH	AJY288LALBH	AJY306LALBH	AJY324LALBH	AJY342LALBH	AJY360LALBH	AJY378LALBH	AJY396LALBH	AJY414LALBH	AJY432LALBH	AJY450LALBH	AJY468LALBH	AJY486LALBH
	Energy efficiency Page 150 ~																												
	Set Model								AJY144LALBHH	AJY162LALBHH	AJY180LALBHH		AJY216LALBHH	AJY234LALBHH		AJY252LALBHH	AJY270LALBHH	AJY288LALBHH	AJY306LALBHH	AJY324LALBHH	AJY342LALBHH	AJY360LALBHH	AJY378LALBHH	AJY396LALBHH	AJY414LALBHH				
V-II series	Space saving Page 156 ~																												
	Set Model				AJYA72LALH	AJYA90LALH	AJY108LALH	AJY126LALH	AJY144LALH	AJY162LALH	AJY180LALH	AJY198LALH	AJY216LALH	AJY234LALH		AJY252LALH	AJY270LALH	AJY288LALH	AJY306LALH	AJY324LALH	AJY342LALH	AJY360LALH	AJY378LALH	AJY396LALH	AJY414LALH	AJY432LALH			
	Energy efficiency Page 156 ~																												
	Set Model								AJY144LALHH				AJY198LALHH	AJY216LALHH	AJY234LALHH		AJY252LALHH	AJY270LALHH	AJY288LALHH	AJY306LALHH	AJY324LALHH		AJY360LALHH	AJY378LALHH	AJY396LALHH				
NEW J-III series Heat Pump Page 162 ~																													
		AJY040LBLAH AJY040LELAH	AJY045LBLAH AJY045LELAH	AJY054LBLAH AJY054LELAH																									
J-IIS series Heat Pump Page 166 ~																													
		AJY040LCLAH	AJY045LCLAH	AJY054LCLAH																									

* Production by order
V-III tropical series: Possible to operate up to 52°C outdoor temperature. Heavy anti-corrosion treatment design.
Capacity range 8 HP (AJY072LNLBH) to 54 HP (AJY486LNLBH). 39 models

Indoor units & Ventilations



Compact Cassette



Cassette



Mini Duct



Slim Duct
(With drain pump)



Medium Static Pressure
Duct



High
Static Pressure Duct



Floor/Ceiling



Ceiling



Wall Mounted
(EEV internal/EEV external)



Wall Mounted

Indoor units
Capacity range 1.1 kW to 28.0 kW
(J-III & J-IIS can be connected up to 14.0 kW.)



Energy Recovery Ventilator
5 models




Outdoor Air Unit
3 models

Ventilations
2 type 8 models

Controllers



Wireless
Remote Controller




Simple
Remote Controller




Wired
Remote Controller




Wired Remote Controller
(Touch Panel)




Group
Remote Controller



Central
Remote Controller



Touch Panel
Controller



System Controller
System Controller Lite
(Software)

Various Easy-To-Use Controllers
User's needs are supported by offering a variety of controls, such as individual control, central control, and building management control options.

AIRSTAGE™ SERIES Outline



Systems for Large Offices, Hotels, and Large Composite Facilities

Heat Recovery Modular type
for simultaneous heating and
cooling operation



AIRSTAGE™ VR-II

- 8 HP - 48 HP 34 Models**
- Space saving combination: 8 HP to 48 HP/ 21 models
 - Energy efficiency combination: 16 HP to 44 HP/ 13 model

Heat Pump Modular type
for heating or
cooling operation



AIRSTAGE™ V-III

- 8 HP - 54 HP 39 Models**
- Space saving combination: 8 HP to 54 HP/ 24 models
 - Energy efficiency combination: 16 HP to 46 HP/ 15 models



AIRSTAGE™ V-II

- 8 HP - 48 HP 33 Models**
- Space saving combination: 8 HP to 48 HP/ 21 models
 - Energy efficiency combination: 16 HP to 44 HP/ 12 models

Systems for Large Homes to Medium-sized Offices, Shops

Heat Pump type for
heating or
cooling operation



AIRSTAGE™ J-III

- 4 HP, 5 HP, 6 HP 6 Models**
- Single phase, 3 phase



AIRSTAGE™ J-IIS

- 4 HP, 5 HP, 6 HP 3 Models**

AIRSTAGE™ series Common Features

- 134 Highly Energy Efficiency
- 135 Energy Saving Function
- 135 More Comfort
- 136 Design Flexibility
- 138 High Reliability
- 139 Easy Installation
- 140 Easy Service & Maintenance


Common Features

Common Features

Energy Saving Function


Economy operation

Economy operation can be set by remote controller. The temperature setting is offset automatically over a certain period of time.




Room temperature set point limitation

The minimum and maximum temperature ranges can be limited, which provide further energy saving while maintaining the comfort of the occupants.



Auto-off timer

- The indoor unit automatically is turned off when it reaches to the preset operating time frame.
- The time frame of the "Auto off timer" can be flexibly scheduled.




Capacity save operation

Operation capacity can be set in 5 steps for rated capability. The power consumption at peak is cut down and the maximum load is suppressed.

High Energy Efficiency

Efficiency is improved significantly by using DC twin rotary compressor, inverter technology, and large heat exchanger



Heat Pump (6HP)



Heat Pump (8HP)



Heat Recovery (10HP)

More Comfort

Precision refrigerant flow control



Precise and smooth refrigerant flow control is achieved by using a DC Inverter control in conjunction with individual indoor unit electronic expansion valve control. This allows high precision comfortable temperature control of $\pm 0.5^{\circ}\text{C}$.

Auto changeover function

At Auto setting, the cooling/heating mode is automatically switched according to the set temperature and room temperature.

Quiet operation


Two low noise modes can be selected automatically by quiet priority setting and capacity priority setting depending on the indoor environment and outside temperature load. This feature can be controlled via outdoor unit external input and/or system controller.



Design Flexibility

Overall piping length Max. 1,000 m


World's top class overall piping length of 1,000 m allows for application in a wide variety of buildings.



High static pressure

The outdoor unit can have a condenser hood easily connected with a static pressure of 82 Pa^{*4} standard. This allows outdoor units to be installed within plant rooms in high rise buildings.

Large diameter fan and DC motor has been utilized allowing an external static pressure of 82 Pa^{*4}. This is approximately 2.6 times greater than the previous model.



High capacity connection

^{*5}: Conditions of maximum connectable indoor unit capacity ratio is as the chart above.

^{*6}: Max. capacities in the combinations including the 18 HP outdoor unit fall below 150%.


^{*7}: Only 4 HP is 46%

Series	Connectable indoor unit capacity range	Connectable indoor unit number
AIRSTAGE™ VR-II series Heat Recovery Modular type	50% to 150% ^{*5}	up to 64
AIRSTAGE™ V-II series Heat Pump Modular type		up to 48
AIRSTAGE™ V-III series Heat Pump Modular type	50% to 150% ^{*6}	up to 64
AIRSTAGE™ J-III series Heat Pump type	50% to 150% ^{*5}	up to 13
AIRSTAGE™ J-IIS series Heat Pump type	50% ^{*7} to 130% ^{*5}	up to 8

Wide operating range

Installation in extreme temperature conditions is possible due to an increase in operational range.


^{*8}: Note: When a multiple outdoor unit connection is used, operating range is from -5°C to 46°C in cooling.



High Reliability


Life-extending operation*1

The compressor starting order is rotated so that the running time is shared.
Note: Rotational operation is alternated by the start / stop timing of the compressor.




Liquid flow back protection

By adopting a large sized accumulator, not completely vapourised refrigerant stays inside of the accumulator to ensure no liquid refrigerant is being fed into the compressor.




Adoption of blue fin heat exchanger

Corrosion resistant of the heat exchanger has been improved by the introduction of blue fin treatment to the outdoor unit's heat exchanger.




Backup operation*1

If one compressor fails, backup operation will be performed by the remaining compressors.*2



Advanced refrigerant control*1

Innovative compressor control logic has been introduced in order to balance the refrigerant mass flow rate of each outdoor unit by controlling the inverter speed.



*1: Not available for AIRSTAGE™ J-III and J-IIS series *2: Note: Backup operation may not be possible depending on the trouble state.

Easy Installation


Easily transported

- **Easily craned using lifting belt hooks:** Design of outdoor unit allows for lifting straps to be used.
- **Transporting by forklift:** Transport with forklift is possible.
- Can be transported in a small elevator




Easy access

By adopting a L-Shape front panel that can be removed, the work space for installation and service has been significantly expanded by this new design.
For multiple installations, work is performed easily and efficiently even in a narrow space.




Simple wiring work

Installation of the wiring systems is made easier as the communication wiring can be installed continuously between the indoor, outdoor and RB units.
Note: Serial connection can't use the automatic address setting in a multiple refrigerant system.



Automatic address setting

The address of the indoor unit, RB unit and signal amplifier through the automatic function setting on the outdoor unit PCB.



Easy Service & Maintenance

Design for easy maintenance


Easy to read 7-segment LED :

Confirm detailed operational and error status without using any specific equipment.

- Operation mode status
- Discharge temperature/Pressure status
- Compressor operation indication
- Address/type/number of outdoor unit


Movable PCB panel:

Easier for maintenance work behind the PCB



Error status can be checked easily via the indoor unit wired controller


An error code is displayed on a liquid crystal screen.



Error diagnosis by Service Tool

Connection to Service Tool


- Detail operation status and recent error history can be checked and analyzed by using the Service Tool.
- Last 5 min. operation memory can be also be recorded.



Remote monitoring

The Web Monitoring system allows you to view system operation anytime over the internet, ensuring issue free operation.

The operating VRF network system in the building can be monitored real time over the Internet.



OUTDOOR UNITS

Heat Recovery Modular type

142 **AIRSTAGE[™] VR-II**

Heat Pump Modular type

150 **AIRSTAGE™ V-III**156 **AIRSTAGE[®] V-II**

Heat Pump for Small Capacity type

162 **NEW** *AIRSTAGE™ J-III*166 **AIRSTAGE™ J-IIS**

Heat Recovery Modular Type

AIRSTAGE™ VR-II

Smart and cutting edge design
Extensive lineup from 8HP to 48HP in 2HP increment
Connectable indoor unit capacity ratio up to 150%

System Outline

Simultaneous cooling and heating operation using 1 refrigerant system

Cooling and heating can be freely selected for each indoor unit to provide simultaneous cooling and heating in the rooms with large temperature differences, etc.

Annual cooling operation

Use annual cooling operation for the rooms and other spaces that require constant temperature control throughout the year.

Handles changes in the temperature difference


The operation mode can be freely changed when there are large temperature differences during the day, such as between seasons.



Features

High Operating Energy Efficiency

Our Heat recovery systems achieve high operating energy efficiency by drawing heat from the room to be cooled and transferring it as energy for rooms that are to be heated.



Energy saving technology that boosted operation efficiency

Powerful large propeller fan

By using CFD*1 technology, a newly designed fan achieves high performance and low noise operation.

*1. CFD = Computational Fluid Dynamics

Sine-wave DC inverter control

High efficiency is realized by adoption of reduced switching loss IPM.

Subcool heat exchanger

High Heat Exchange efficiency is achieved by using an internal projection shape double pipe construction.

High efficient and large capacity DC inverter compressor

Large capacity high efficient DC twin rotary compressor with excellent intermediate capability.

3 phase DC fan motor




Efficiency is substantially improved by high efficient motor with sophisticated driver control. In addition, low noise is realized by DC fan motor.

4-face heat exchanger

Heat exchange efficiency is significantly improved by the introduction of a new 4-face heat exchanger that increases effective surface area.

Front intake port (corner cut air inhaling structure)

In multiple outdoor unit installations, the unique front intake design improves airflow into the Heat Exchanger.



All inverter compressor


Large capacity DC inverter compressor
Large capacity high efficient DC twin rotary compressor with excellent intermediate capability.

High efficient compressor speed control
Comfortable space with small room temperature changes and little energy loss is created by 0.1Hz steps compressor speed control.




Ideal heat exchanger path control

Heat exchanger is split into top and bottom. Heat exchange efficiency is improved by optimum heat exchanger path refrigerant control. Refrigerant is more distributed at the top side heat exchanger with a large intake airflow.




Sophisticated operation control

When multiple outdoor units are connected, sophisticated operation is performed by each compressor. Efficiency is improved by all compressors at part load and distributing refrigerant to all of the heat exchangers rather than to one compressor.




Flexible piping connection

A more flexible refrigerant piping work is possible by the use of various piping and RB Unit connections, for adjustments to the floor layout and building structure.






Flexible installation of RB unit

- Small & slim design saves space. Height 198 mm
- A drain pipe is not required
- The control box position can be changed to meet the installation conditions
- Small design saves space
- A drain pipe is not required
- Simple installation series connection design





































Easy to maintenance in a narrow space



Outdoor units lineup

• Combinations other than the followings are not recommended.

Space saving combination				
22.4 kW (8HP)  AJYA72GALH UNIT : AJYA72GALH	28.0 kW (10HP)  AJYA90GALH UNIT : AJYA90GALH	33.5 kW (12HP)  AJY108GALH UNIT : AJY108GALH	40.0 kW (14HP)  AJY126GALH UNIT : AJY126GALH	45.0 kW (16HP)  AJY144GALH UNIT : AJY144GALH
50.4 kW (18HP)  AJY162GALH UNIT : AJYA90/A72GALH	56.0 kW (20HP)  AJY180GALH UNIT : AJYA90/A90GALH	61.5 kW (22HP)  AJY198GALH UNIT : AJY108/A90GALH	67.0 kW (24HP)  AJY216GALH UNIT : AJY108/108GALH	73.0 kW (26HP)  AJY234GALH UNIT : AJY144/A90GALH
78.5 kW (28HP)  AJY252GALH UNIT : AJY144/108GALH	85.0 kW (30HP)  AJY270GALH UNIT : AJY144/126GALH	90.0 kW (32HP)  AJY288GALH UNIT : AJY144/144GALH	95.0 kW (34HP)  AJY306GALH UNIT : AJY108/108/A90GALH	100.5 kW (36HP)  AJY324GALH UNIT : AJY108/108/108GALH
106.5 kW (38HP)  AJY342GALH UNIT : AJY144/108/A90GALH	112.0 kW (40HP)  AJY360GALH UNIT : AJY144/108/108GALH	118.0 kW (42HP)  AJY378GALH UNIT : AJY144/144/A90GALH	123.5 kW (44HP)  AJY396GALH UNIT : AJY144/144/108GALH	130.0 kW (46HP)  AJY414GALH UNIT : AJY144/144/126GALH
135.0 kW (48HP)  AJY432GALH UNIT : AJY144/144/144GALH				

Energy efficiency combination				
44.8 kW (16HP)  AJY144GALHH UNIT : AJYA72/A72GALH	62.4 kW (22HP)  AJY198GALHH UNIT : AJY126/A72GALH	67.2 kW (24HP)  AJY216GALHH UNIT : AJYA72/A72/A72GALH	72.8 kW (26HP)  AJY234GALHH UNIT : AJYA90/A72/A72GALH	78.4 kW (28HP)  AJY252GALHH UNIT : AJYA90/A90/A72GALH
84.0 kW (30HP)  AJY270GALHH UNIT : AJYA90/A90/A90GALH	90.4 kW (32HP)  AJY288GALHH UNIT : AJY126/A90/A72GALH	96.0 kW (34HP)  AJY306GALHH UNIT : AJY126/A90/A90GALH	102.4 kW (36HP)  AJY324GALHH UNIT : AJY126/126/A72GALH	108.0 kW (38HP)  AJY342GALHH UNIT : AJY126/126/A90GALH
113.0 kW (40HP)  AJY360GALHH UNIT : AJY144/126/A90GALH	120.0 kW (42HP)  AJY378GALHH UNIT : AJY126/126/126GALH	125.0 kW (44HP)  AJY396GALHH UNIT : AJY144/126/126GALH		


8,10,12HP : AJYA72GALH / AJYA90GALH / AJY108GALH
14,16HP : AJY126GALH / AJY144GALH





8, 10, 12 HP 14, 16 HP

Dimensions
(Unit : mm)










8, 10, 12 HP









14, 16 HP



Space Saving Combination

Rating Capacity range		HP	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	
																								
Set Model name			AJYA72GALH	AJYA90GALH	AJY108GALH	AJY126GALH	AJY144GALH	AJY162GALH	AJY180GALH	AJY198GALH	AJY216GALH	AJY234GALH	AJY252GALH	AJY270GALH	AJY288GALH	AJY306GALH	AJY324GALH	AJY342GALH	AJY360GALH	AJY378GALH	AJY396GALH	AJY414GALH	AJY432GALH	
Unit 1 Unit 2 Unit 3			AJYA72GALH	AJYA90GALH	AJY108GALH	AJY126GALH	AJY144GALH	AJYA90GALH AJYA72GALH	AJYA90GALH AJYA90GALH	AJY108GALH AJYA90GALH	AJY108GALH AJY108GALH	AJY144GALH AJYA90GALH	AJY144GALH AJY108GALH	AJY144GALH AJY126GALH	AJY144GALH AJY144GALH	AJY108GALH AJY108GALH AJYA90GALH	AJY108GALH AJY108GALH AJY108GALH	AJY144GALH AJY108GALH AJYA90GALH	AJY144GALH AJY108GALH AJY108GALH	AJY144GALH AJY144GALH AJY108GALH	AJY144GALH AJY144GALH AJYA90GALH	AJY144GALH AJY144GALH AJY108GALH	AJY144GALH AJY144GALH AJY126GALH	AJY144GALH AJY144GALH AJY144GALH
Maximum Connectable Indoor Unit*1			15	16	17	21	24	27	30	32	35	39	42	45	48	50	53	57	60	63	64	64	64	
Indoor unit connectable capacity		kW	11.2-33.6	14.0-42.0	16.8-50.2	20.0-60.0	22.5-67.5	25.2-75.6	28.0-84.0	30.8-92.2	33.5-100.5	36.5-109.5	39.3-117.7	42.5-127.5	45.0-135.0	47.5-142.5	50.3-150.7	53.3-159.7	56.0-168.0	59.0-177.0	61.8-185.2	65.0-195.0	67.5-202.5	
Power source			3-phase 4 wire , 400 V, 50Hz												3-phase 4 wire , 400 V, 50Hz									
Capacity	Cooling	kW	22.4	28.0	33.5	40.0	45.0	50.4	56.0	61.5	67.0	73.0	78.5	85.0	90.0	95.0	100.5	106.5	112.0	118.0	123.5	130.0	135.0	
	Heating		25.0	31.5	37.5	45.0	50.0	56.5	63.0	69.0	75.0	81.5	87.5	95.0	100.0	106.5	112.5	119.0	125.0	131.5	137.5	145.0	150.0	
Input power	Cooling	kW	5.45	7.11	9.75	11.34	13.61	12.56	14.22	16.86	19.50	20.72	23.36	24.95	27.22	26.61	29.25	30.47	33.11	34.33	36.97	38.56	40.83	
	Heating		5.70	7.33	9.62	10.90	12.77	13.03	14.66	16.95	19.24	20.10	22.39	23.67	25.54	26.57	28.86	29.72	32.01	32.87	35.16	36.44	38.31	
EER	Cooling	W/W	4.11	3.94	3.44	3.53	3.31	4.01	3.94	3.65	3.44	3.52	3.36	3.41	3.31	3.57	3.44	3.50	3.38	3.44	3.34	3.37	3.31	
COP	Heating	W/W	4.39	4.30	3.90	4.13	3.92	4.34	4.30	4.07	3.90	4.05	3.91	4.01	3.92	4.01	3.90	4.00	3.91	4.00	3.91	3.98	3.92	
Air flow late		m³/h	11,100	11,100	11,100	13,000	13,000	11,100×2	11,100×2	11,100×2	11,100×2	13,000+11,100	13,000+11,100	13,000×2	13,000×2	11,100×3	11,100×3	13,000+11,100×2	13,000+11,100×2	13,000×2+11,100	13,000×2+11,100	13,000×3	13,000×3	
Sound pressure level*2	Cooling	dB(A)	56	58	59	60	61	60	61	62	62	63	63	64	64	63	64	65	65	65	65	65	66	
	Heating		58	59	61	61	61	62	62	63	64	63	64	64	64	65	66	65	66	65	66	66	66	
Maximum external static pressure		Pa	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	
Compressor motor output		kW	7.5	7.5	7.5	11.0	11.0	7.5×2	7.5×2	7.5×2	7.5×2	11.0×7.5	11.0×7.5	11.0×2	11.0×2	7.5×3	7.5×3	11.0×7.5×2	11.0×7.5×2	11.0×7.5×2	11.0×7.5×2	11.0×3	11.0×3	
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	
Net Dimensions	Height	mm	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	
	Width		930	930	930	1,240	1,240	930×2	930×2	930×2	930×2	1,240×930	1,240×930	1,240×2	1,240×2	930×3	930×3	1,240×930×2	1,240×930×2	1,240×2+930	1,240×2+930	1,240×3	1,240×3	
	Depth		765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	
Weight		kg	262	262	262	286	286	262×2	262×2	262×2	262×2	286+262	286+262	286×2	286×2	286×3	286×3	286+262×2	286+262×2	286×2+262	286×2+262	286×3	286×3	
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	
	Charge	kg	11.8	11.8	11.8	11.8	11.8	11.8×2	11.8×2	11.8×2	11.8×2	11.8×2	11.8×2	11.8×2	11.8×2	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	
Connection pipe diameter	Liquid	mm	12.70	12.70	12.70	12.70	12.70	15.88	15.88	15.88	15.88	15.88	15.88	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	
	Discharge Gas		15.88	19.05	19.05	22.22	22.22	22.22	22.22	28.58	28.58	28.58	28.58	28.58	28.58	28.58	34.92	34.92	34.92	34.92	34.92	34.92	34.92	
	Suction Gas		22.22	22.22	28.58	28.58	28.58	28.58	28.58	34.92	34.92	34.92	34.92	34.92	34.92	34.92	41.27	41.27	41.27	41.27	41.27	41.27	41.27	
Operation range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	
	Heating		-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	
	Cooling/Heating		-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	

Energy Efficiency Combination

Rating Capacity range		HP	16	22	24	26	28	30	32	34	36	38	40	42	44	
																
Set Model name			AJY144GALHH	AJY198GALHH	AJY216GALHH	AJY234GALHH	AJY252GALHH	AJY270GALHH	AJY288GALHH	AJY306GALHH	AJY324GALHH	AJY342GALHH	AJY360GALHH	AJY378GALHH	AJY396GALHH	
Unit 1 Unit 2 Unit 3			AJYA72GALH AJYA72GALH	AJY126GALH AJYA72GALH	AJYA72GALH AJYA72GALH AJYA72GALH	AJYA90GALH AJYA72GALH AJYA72GALH	AJYA90GALH AJYA90GALH AJYA72GALH	AJYA90GALH AJYA90GALH AJYA90GALH	AJY126GALH AJYA90GALH AJYA72GALH	AJY126GALH AJYA90GALH AJYA90GALH	AJY126GALH AJY126GALH AJYA72GALH	AJY126GALH AJY126GALH AJYA90GALH	AJY144GALH AJY126GALH AJYA90GALH	AJY126GALH AJY126GALH AJY126GALH	AJY144GALH AJY126GALH AJY126GALH	
Maximum Connectable Indoor Unit*1			24	33	36	39	42	45	48	51	54	57	60	64	64	
Indoor unit connectable capacity		kW	22.4-67.2	31.2-93.6	33.6-100.8	36.4-109.2	39.2-117.6	42.0-126.0	45.2-135.6	48.0-144.0	51.2-153.6	54.0-162.0	56.5-169.5	60.0-180.0	62.5-187.5	
Power source			3-phase 4 wire , 400 V, 50Hz												3-phase 4 wire , 400 V, 50Hz	
Capacity	Cooling	kW	44.8	62.4	67.2	72.8	78.4	84.0	90.4	96.0	102.4	108.0	113.0	120.0	125.0	
	Heating		50.0	70.0	75.0	81.5	88.0	94.5	101.5	108.0	115.0	121.5	126.5	135.0	140.0	
Input power	Cooling	kW	10.90	16.79	16.35	18.01	19.67	21.33	23.90	25.56	28.13	29.79	32.06	34.02	36.29	
	Heating		11.40	16.60	17.10	18.73	20.36	21.99	23.93	25.56	27.50	29.13	31.00	32.70	34.57	
EER	Cooling	W/W	4.11	3.72	4.11	4.04	3.99	3.94	3.78	3.76	3.64	3.63	3.52	3.53	3.44	
COP	Heating	W/W	4.39	4.22	4.39	4.35	4.32	4.30	4.24	4.23	4.18	4.17	4.08	4.13	4.05	
Air flow late		m³/h	11,100×2	13,000+11,100	11,100×3	11,100×3	11,100×3	11,100×3	13,000+11,100×2	13,000+11,100×2	13,000×2+11,100	13,000×2+11,100	13,000×2+11,100	13,000×3	13,000×3	
Sound pressure level*2	Cooling	dB(A)	59	61	61	62	62	63	63	64	64	65	65	65	65	
	Heating		61	63	63	63	63	64	64	65	65	65	65	66	66	
Maximum external static pressure		Pa	80	80	80	80	80	80	80	80	80	80	80	80	80	
Compressor motor output		kW	7.5×2	11.0+7.5	7.5×3	7.5×3	7.5×3	7.5×3	11.0+7.5×2	11.0+7.5×2	11.0×2+7.5	11.0×2+7.5	11.0×2+7.5	11.0×3	11.0×3	
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	
Net Dimensions	Height	mm	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	
	Width		930×2	1,240+930	930×3	930×3	930×3	930×3	930×3	1,240+930×2	1,240+930×2	1,240×2+930	1,240×2+930	1,240×2+930	1,240×3	1,240×3
	Depth		765	765	765	765	765	765	765	765	765	765	765	765	765	765
Weight		kg	262×2	286+262	262×3	262×3	262×3	262×3	286+262×2	286+262×2	286×2+262	286×2+262	286×2+262	286×3	286×3	
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	
	Charge	kg	11.8×2	11.8×2	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	
Connection pipe diameter	Liquid	mm	12.70	15.88	15.88	15.88	15.88	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	
	Discharge Gas		22.22	28.58	28.58	28.58	28.58	28.58	28.58	28.58	28.58	34.92	34.92	34.92	34.92	
	Suction Gas		28.58	34.92	34.92	34.92	34.92	34.92	34.92	34.92	34.92	41.27	41.27	41.27	41.27	
Operation range	Cooling	°CDB	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	-10 to 46	
	Heating		-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	
	Cooling/Heating		-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21	-10 to 21

Heat Pump Modular Type

AIRSTAGE™ V-III

Smart and cutting edge design
Extensive lineup from 8HP to 48HP in 2HP increment
Connectable indoor unit capacity ratio up to 150%

System Outline

Excellent energy saving

Heat pump inverter type realizes the highly energy saving air conditioning for individual cooling and heating operation by all inverter technology for seasonal efficiency.

High design flexibility for various building air conditioning

High design flexibly meets the various needs of high-rise building air conditioning such as outdoor unit roof top concentrated installation and each floor installation by large capacity combination, sufficient connection capacity, and high static pressure design.

Easy installation and maintenance


The flexible communication method and piping connections makes installation and maintenance easy even for large systems.



Features

Efficiency in actual operation

Top class high COP is achieved for all combinations by our unique heat exchanger structure, high efficient DC twin compressor, and our own technologies.



Energy saving technology that boosted operation efficiency



Powerful large propeller fan

By using CFD*1 technology, a newly designed fan achieves high performance and low noise operation.
*1. CFD = Computational Fluid Dynamics



3 phase DC fan motor

Efficiency is substantially improved by high efficient motor with sophisticated driver control. In addition, low noise is realized by DC fan motor.



Subcool heat exchanger

High Heat Exchange efficiency is achieved by using an internal projection shape double pipe construction.



Sine-wave DC inverter control

High efficiency is realized by adoption of reduced switching loss IPM.




High efficient and large capacity DC inverter compressor

Large capacity high efficient DC twin rotary compressor with excellent intermediate capability.



4-face heat exchanger

Heat exchange efficiency is significantly improved by the introduction of a new 4-face heat exchanger that increases effective surface area.



























Front intake port (corner cut air inhaling structure)
















In multiple outdoor unit installations, the unique front intake design improves airflow into the Heat Exchanger.



Outdoor units lineup

• Combinations other than the followings are not recommended.

Space saving combination				
22.4 kW (8HP)  AJY072LALBH UNIT : AJY072LALBH	28.0 kW (10HP)  AJY090LALBH UNIT : AJY090LALBH	33.5 kW (12HP)  AJY108LALBH UNIT : AJY108LALBH	40.0 kW (14HP)  AJY126LALBH UNIT : AJY126LALBH	45.0 kW (16HP)  AJY144LALBH UNIT : AJY144LALBH
50.0 kW (18HP)  AJY162LALBH UNIT : AJY162LALBH	56.0 kW (20HP)  AJY180LALBH UNIT : AJY090/090LALBH	62.4 kW (22HP)  AJY198LALBH UNIT : AJY126/072LALBH	68.0 kW (24HP)  AJY216LALBH UNIT : AJY126/090LALBH	73.0 kW (26HP)  AJY234LALBH UNIT : AJY144/090LALBH
78.0 kW (28HP)  AJY252LALBH UNIT : AJY162/090LALBH	85.0 kW (30HP))  AJY270LALBH UNIT : AJY144/126LALBH	90.0 kW (32HP)  AJY288LALBH UNIT : AJY144/144LALBH	95.0 kW (34HP)  AJY306LALBH UNIT : AJY162/144LALBH	100.0 kW (36HP)  AJY324LALBH UNIT : AJY162/162LALBH
106.0 kW (38HP)  AJY342LALBH UNIT : AJY162/090/090LALBH	113.0 kW (40HP)  AJY360LALBH UNIT : AJY144/126/090LALBH	118.0 kW (42HP)  AJY378LALBH UNIT : AJY144/144/090LALBH	123.0 kW (44HP)  AJY396LALBH UNIT : AJY162/144/090LALBH	128.0 kW (46HP)  AJY414LALBH UNIT : AJY162/162/090LALBH
135.0 kW (48HP)  AJY432LALBH UNIT : AJY144/144/144LALBH	140.0 kW (50HP)  AJY450LALBH UNIT : AJY162/144/144LALBH	145.0 kW (52HP)  AJY468LALBH UNIT : AJY162/162/144LALBH	150.0 kW (54HP)  AJY486LALBH UNIT : AJY162/162/162LALBH	


Energy efficiency combination				
44.8 kW (16HP)  AJY144LALBHH UNIT : AJY072/072LALBH	50.4kW (18HP)  AJY162LALBHH UNIT : AJY090/072LALBH	55.9 kW (20HP)  AJY180LALBHH UNIT : AJY108/072LALBH	67.2 kW (24HP)  AJY216LALBHH UNIT : AJY072/072/072LALBH	72.8 kW (26HP)  AJY234LALBHH UNIT : AJY090/072/072LALBH
78.3 kW (28HP)  AJY252LALBHH UNIT : AJY108/072/072LALBH	84.8 kW (30HP)  AJY270LALBHH UNIT : AJY126/072/072LALBH	89.4 kW (32HP)  AJY288LALBHH UNIT : AJY108/108/072LALBH	95.9 kW (34HP)  AJY306LALBHH UNIT : AJY126/108/072LALBH	100.5 kW (36HP)  AJY324LALBHH UNIT : AJY108/108/108LALBH
107.0 kW (38HP)  AJY342LALBHH UNIT : AJY126/108/108LALBH	113.5 kW (40HP)  AJY360LALBHH UNIT : AJY126/126/108LALBH	120.0 kW (42HP)  AJY378LALBHH UNIT : AJY126/126/126LALBH	125.0 kW (44HP)  AJY396LALBHH UNIT : AJY144/126/126LALBH	130.0 kW (46HP)  AJY414LALBHH UNIT : AJY144/144/126LALBH

8,10HP : AJY072LALBH / AJY090LALBH
12,14,16HP : AJY108LALBH / AJY126LALBH / AJY144LALBH / AJY162LALBH





Dimensions
(Unit : mm)













8, 10 HP










12, 14, 16 HP



Space Saving Combination

Rating Capacity range		HP	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50	52	54
																										
Set Model name			AJY072LALBH	AJY090LALBH	AJY108LALBH	AJY126LALBH	AJY144LALBH	AJY162LALBH	AJY180LALBH	AJY198LALBH	AJY216LALBH	AJY234LALBH	AJY252LALBH	AJY270LALBH	AJY288LALBH	AJY306LALBH	AJY324LALBH	AJY342LALBH	AJY360LALBH	AJY378LALBH	AJY396LALBH	AJY414LALBH	AJY432LALBH	AJY450LALBH	AJY468LALBH	AJY486LALBH
Unit 1 Unit 2 Unit 3			AJY072LALBH	AJY090LALBH	AJY108LALBH	AJY126LALBH	AJY144LALBH	AJY162LALBH	AJY090LALBH AJY090LALBH	AJY126LALBH AJY072LALBH	AJY126LALBH AJY090LALBH	AJY144LALBH AJY090ALBH	AJY162LALBH AJY090LALBH	AJY144LALBH AJY126LALBH	AJY144LALBH	AJY162LALBH AJY144LALBH	AJY162LALBH	AJY162LALBH AJY090LALBH AJY090LALBH	AJY144LALBH AJY126LALBH AJY090LALBH	AJY144LALBH AJY144LALBH AJY090LALBH	AJY162LALBH AJY144LALBH AJY090LALBH	AJY162LALBH AJY162LALBH AJY144LALBH	AJY144LALBH AJY144LALBH AJY144LALBH	AJY162LALBH AJY144LALBH AJY162LALBH	AJY162LALBH AJY162LALBH AJY162LALBH	AJY162LALBH AJY162LALBH AJY162LALBH
Maximum Connectable Indoor Unit*1			17	21	26	30	34	39	43	47	52	56	60	64	64	64	64	64	64	64	64	64	64	64	64	64
Indoor unit connectable capacity		kW	11.2-33.6	14.0-42.0	16.8-50.2	20.0-60.0	22.5-67.5	25.0-67.5	28.0-84.0	31.2-93.6	34.0-102.0	36.5-109.5	39.0-109.5	42.5-127.5	45.0-135.0	47.5-135.0	50.0-135.0	53.0-151.5	56.5-169.5	59.0-177.0	61.5-177.0	64.0-177.0	67.5-202.5	70.0-202.5	72.5-202.5	75.0-202.5
Power source			3-phase 4 wire, 400 V, 50Hz												3-phase 4 wire, 400 V, 50Hz											
Capacity	Cooling	kW	22.4	28.0	33.5	40.0	45.0	50.0	56.0	62.4	68.0	73.0	78.0	85.0	90.0	95.0	100.0	106.0	113.0	118.0	123.0	128.0	135.0	140.0	145.0	150.0
	Heating		25.0	31.5	37.5	45.0	50.0	50.0	63.0	70.0	76.5	81.5	81.5	95.0	100.0	100.0	100.0	113.0	126.5	131.5	131.5	131.5	150.0	150.0	150.0	150.0
Input power	Cooling	kW	5.20	7.28	8.96	10.96	13.01	16.56	14.56	16.16	18.24	20.29	23.84	23.97	26.02	29.57	33.12	31.12	31.25	33.30	36.85	40.40	39.03	42.58	46.13	49.68
	Heating		5.17	7.25	8.65	11.17	13.63	13.63	14.50	16.34	18.42	20.88	20.88	24.80	27.26	27.26	27.26	28.13	32.05	34.51	34.51	34.51	40.89	40.89	40.89	40.89
EER	Cooling	W/W	4.31	3.85	3.74	3.65	3.46	3.02	3.85	3.86	3.73	3.60	3.27	3.55	3.46	3.21	3.02	3.41	3.62	3.54	3.34	3.17	3.46	3.29	3.14	3.02
COP	Heating	W/W	4.84	4.35	4.34	4.03	3.67	3.67	4.34	4.28	4.15	3.90	3.90	3.83	3.67	3.67	3.67	4.02	3.95	3.81	3.81	3.81	3.67	3.67	3.67	3.67
Air flow late	High	m³/h	11,100	11,100	13,000	13,000	13,700	13,700	11,100×2	13,000+11,100	13,000+11,100	13,000+11,100	13,700+11,100	13,700+13,000	13,700×2	13,700×2	13,700×2	13,700×2	13,700+11,100×2	13,700+13,000+11,100	13,700×2+11,100	13,700×2+11,100	13,700×2+11,100	13,700×3	13,700×3	13,700×3
Sound pressure level*2	Cooling	dB(A)	56	58	57	60	62	63	61	61	62	63	64	64	65	66	66	65	65	66	66	66	67	67	67	68
	Heating		58	59	60	62	64	64	62	63	64	65	65	66	67	67	67	66	67	68	68	68	69	69	69	69
Maximum external static pressure		Pa	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82
Compressor motor output		kW	7.5	7.5	11.0	11.0	11.0	11.0	7.5×2	11.0+7.5	11.0+7.5	11.0+7.5	11.0+7.5	11.0×2	11.0×2	11.0×2	11.0×2	11.0×2	11.0+2×7.5	11.0×2+7.5	11.0×2+7.5	11.0×2+7.5	11.0×3	11.0×3	11.0×3	11.0×3
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin
Net Dimensions	Height	mm	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690
	Width		930	930	1,240	1,240	1,240	1,240	930×2	1,240+930	1,240+930	1,240+930	1,240+930	1,240×2	1,240×2	1,240×2	1,240×2	1,240×2	1,240+930×2	1,240×2+930	1,240×2+930	1,240×2+930	1,240×3	1,240×3	1,240×3	1,240×3
	Depth		765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765
Weight		kg	252	252	275	275	275	275	252×2	275+252	275+252	275+252	275+252	275×2	275×2	275×2	275×2	275×2	275+252×2	275×2+252	275×2+252	275×2+252	275×2+252	275×3	275×3	275×3
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
	Charge	kg	11.7	11.7	11.8	11.8	11.8	11.8	11.7×2	11.8+11.7	11.8+11.7	11.8+11.7	11.8+11.7	11.8×2	11.8×2	11.8×2	11.8×2	11.8+11.7×2	11.8×2+11.7	11.8×2+11.7	11.8×2+11.7	11.8×2+11.7	11.8×3	11.8×3	11.8×3	11.8×3
Connection pipe diameter	Liquid	mm	12.70	12.70	12.70	12.70	12.70	15.88	15.88	15.88	15.88	15.88	15.88	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05
	Gas		22.22	22.22	28.58	28.58	28.58	28.58	28.58	34.92	34.92	34.92	34.92	34.92	34.92	34.92	34.92	41.27	41.27	41.27	41.27	41.27	41.27	41.27	41.27	41.27
Operation range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46
	Heating		-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21

Energy Efficiency Combination

Rating Capacity range		HP	16	18	20	24	26	28	30	32	34	36	38	40	42	44	46
																	
Set Model name			AJY144LALBHH	AJY162LALBHH	AJY180LALBHH	AJY216LALBHH	AJY234LALBHH	AJY252LALBHH	AJY270LALBHH	AJY288LALBHH	AJY306LALBHH	AJY324LALBHH	AJY342LALBHH	AJY360LALBHH	AJY378LALBHH	AJY396LALBHH	AJY414LALBHH
Unit 1 Unit 2 Unit 3			AJY072LALBH AJY072LALBH	AJY090LALBH AJY072LALBH	AJY108LALBH AJY072LALBH	AJY072LALBH AJY072LALBH AJY072LALBH	AJY090LALBH AJY072LALBH AJY072LALBH	AJY108LALBH AJY072LALBH AJY072LALBH	AJY126LALBH AJY072LALBH AJY072LALBH	AJY108LALBH AJY108LALBH AJY072LALBH	AJY126LALBH AJY108LALBH AJY072LALBH	AJY108LALBH AJY108LALBH AJY08LALBH	AJY126LALBH AJY108LALBH AJY108LALBH	AJY126LALBH AJY126LALBH AJY108LALBH	AJY126LALBH AJY126LALBH AJY126LALBH	AJY144LALBH AJY126LALBH AJY126LALBH	AJY144LALBH AJY144LALBH AJY126LALBH
Maximum Connectable Indoor Unit*1			34	39	43	52	56	60	64	64	64			64	64	64	64
Indoor unit connectable capacity		kW	22.4-67.2	25.2-75.6	28.0-83.8	33.6-100.8	36.4-109.2	39.2-117.4	42.4-127.2	44.7-134.1	48.0-143.8	50.3-150.7	53.5-160.5	56.8-170.2	60.0-180.0	62.5-187.5	65.0-195.0
Power source			3-phase 4 wire, 400 V, 50Hz												3-phase 4 wire, 400 V, 50Hz		
Capacity	Cooling	kW	44.8	50.4	55.9	67.2	72.8	78.3	84.8	89.4	95.9	100.5	107.0	113.5	120.0	125.0	130.0
	Heating		50.0	56.5	62.5	75.0	81.5	87.5	95.0	100.0	107.5	112.5	120.0	127.5	135.0	140.0	145.0
Input power	Cooling	kW	10.40	12.48	14.16	15.60	17.68	19.36	21.36	23.12	25.12	26.88	28.88	30.88	32.88	34.93	36.98
	Heating		10.34	12.42	13.82	15.51	17.59	18.99	21.51	22.47	24.99	25.95	28.47	30.99	33.51	35.97	38.43
EER	Cooling	W/W	4.31	4.04	3.95	4.31	4.12	4.04	3.97	3.87	3.82	3.74	3.70	3.68	3.65	3.58	3.52
COP	Heating	W/W	4.84	4.55	4.52	4.84	4.63	4.61	4.42	4.45	4.30	4.34	4.21	4.11	4.03	3.89	3.77
Air flow late	High	m³/h	11,100×2	11,100×2	13,000+11,100	11,100×3	11,000×3	13,000+11,100×2	13,000+11,100×2	13,000×2+11,100	13,000×2+11,100	13,000×3	13,000×3	13,000×3	13,000×3	13,700+13,000×2	13,700×2+13,000
Sound pressure level*2	Cooling	dB(A)	59	60	60	61	62	61	63	61	63	63	64	64	65	66	66
	Heating		61	62	62	63	63	64	65	64	65	65	65	66	67	68	68
Maximum external static pressure		Pa	82	82	82	82	82	82	82	82	82	82	82	82	82	82	82
Compressor motor output		kW	7.5×2	7.5×2	11.0×7.5	7.5×3	7.5×3	11.0×7.5×2	11.0×7.5×2	11.0×2+7.5	11.0×2+7.5	11.0×3	11.0×3	11.0×3	11.0×3	11.0×3	11.0×3
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin
Net Dimensions	Height	mm	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690
	Width		930×2	930×2	1,240+930	930×3	930×3	1,240+930×2	1,240+930×2	1,240×2+930	1,240×2+930	1,240×3	1,240×3	1,240×3	1,240×3	1,240×3	1,240×3
	Depth		765	765	765	765	765	765	765	765	765	765	765	765	765	765	765
Weight		kg	252×2	252×2	275+252	252×3	252×3	275+252×2	275+252×2	275×2+252	275×2+252	275×3	275×3	275×3	275×3	275×3	275×3
Refrigerant		Type (Global Warming Potential)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
Connection pipe diameter	Charge	kg	11.7×2	11.7×2	11.8+11.7	11.7×3	11.7×3	11.8+11.7×2	11.8+11.7×2	11.8×2+11.7	11.8×2+11.7	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3	11.8×3
	Liquid	mm	12.70	15.88	15.88	15.88	15.88	15.88	15.88	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05
	Gas		28.58	28.58	28.58	34.92	34.92	34.92	34.92	34.92	34.92	41.27	41.27	41.27	41.27	41.27	41.27
Operation range	Cooling	°CDB	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46
	Heating		-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21

Heat Pump Modular Type

AIRSTAGE™ V-II

Smart and cutting edge design
Extensive lineup from 8HP to 48HP in 2HP increment
Connectable indoor unit capacity ratio up to 150%

System Outline

Excellent energy savings

Heat pump type inverter control is used to achieve economic cooling and heating operation for individual air conditioning to entire air conditioning.

High design flexibility for various building air conditioning

The high static pressure design flexibly meets the needs of high rise buildings including easy installation on each floor.

Easy installation and maintenanc


The flexible communication method and piping connections makes installation and maintenance easy even for large systems.



Features

Efficiency in actual operation

Top class high COP is achieved for all combinations by our unique heat exchanger structure, high efficient DC twin compressor, and our own technologies.



Energy saving technology that boosted operation efficiency

**Powerful large propeller fan**

By using CFD*1 technology, a newly designed fan achieves high performance and low noise operation.
*1. CFD = Computational Fluid Dynamics

**DC fan motor**


Power consumption has been reduced by 25% compared to previous models by using a compact and high performance DC fan motor.

**Subcool heat exchanger**

High Heat Exchange efficiency is achieved by using an internal projection shape double pipe construction.

**Sine-wave DC inverter control**



High efficiency operation is realized by using a sine wave DC inverter control.

**DC twin rotary compressor**

Significantly greater efficiency is realized by use of a large capacity DC twin rotary compressor with substantially increased refrigerant intake and compression efficiency.

**4-face heat exchanger**






















Heat exchange efficiency is significantly improved by the introduction of a new 4-face heat exchanger that increases effective surface area.

**Front intake port (corner cut air inhaling structure)**

In multiple outdoor unit installations, the unique front intake design improves airflow into the Heat Exchanger.

Outdoor units lineup

• Combinations other than the followings are not recommended.

Space saving combination				
22.4 kW (8HP)  AJYA72LALH UNIT : AJYA72LALH	28.0 kW (10HP)  AJYA90LALH UNIT : AJYA90LALH	33.5 kW (12HP)  AJY108LALH UNIT : AJY108LALH	40.0 kW (14HP)  AJY126LALH UNIT : AJY126LALH	45.0 kW (16HP)  AJY144LALH UNIT : AJY144LALH
50.4 kW (18HP)  AJY162LALH UNIT : AJYA90/A72LALH	56.9 kW (20HP)  AJY180LALH UNIT : AJY108/A72LALH	61.5 kW (22HP)  AJY198LALH UNIT : AJY108/A90LALH	67.0 kW (24HP)  AJY216LALH UNIT : AJY108/108LALH	73.5 kW (26HP)  AJY234LALH UNIT : AJY126/108LALH
78.5 kW (28HP)  AJY252LALH UNIT : AJY144/108LALH	85.0 kW (30HP)  AJY270LALH UNIT : AJY144/126LALH	90.0 kW (32HP)  AJY288LALH UNIT : AJY144/144LALH	95.0 kW (34HP)  AJY306LALH UNIT : AJY108/108/A90LALH	100.5 kW (36HP)  AJY324LALH UNIT : AJY108/108/108LALH
107.0 kW (38HP)  AJY342LALH UNIT : AJY126/108/108LALH	112.0 kW (40HP)  AJY360LALH UNIT : AJY144/108/108LALH	118.5 kW (42HP)  AJY378LALH UNIT : AJY144/126/108LALH	123.5 kW (44HP)  AJY396LALH UNIT : AJY144/144/108LALH	130.0 kW (46HP)  AJY414LALH UNIT : AJY144/144/126LALH
135.0 kW (48HP)  AJY432LALH UNIT : AJY144/144/144LALH				


Energy efficiency combination				
44.8 kW (16HP)  AJY144LALHH UNIT : AJYA72/A72LALH	62.4 kW (22HP)  AJY198LALHH UNIT : AJY126/A72LALH	67.2 kW (24HP)  AJY216LALHH UNIT : AJYA72/A72/A72LALH	72.8 kW (26HP)  AJY234LALHH UNIT : AJYA90/A72/A72LALH	78.4 kW (28HP)  AJY252LALHH UNIT : AJY108/A72/A72LALH
84.8 kW (30HP)  AJY270LALHH UNIT : AJY126/A72/A72LALH	89.8 kW (32HP)  AJY288LALHH UNIT : AJY108/108/A72LALH	95.9 kW (34HP)  AJY306LALHH UNIT : AJY126/108/A72LALH	102.4 kW (36HP)  AJY324LALHH UNIT : AJY126/126/A72LALH	113.5 kW (40HP)  AJY360LALHH UNIT : AJY126/126/108LALH
120.0 kW (42HP)  AJY378LALHH UNIT : AJY126/126/126LALH	125.0 kW (44HP)  AJY396LALHH UNIT : AJY144/126/126LALH			

8,10,12HP : AJYA72LALH / AJYA90LALH / AJY108LALH
14,16HP : AJY126LALH / AJY144LALH





Dimensions
(Unit : mm)










8, 10, 12 HP















14, 16 HP



Space Saving Combination

Rating Capacity range		HP	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	
																								
Set Model name			AJYA72LALH	AJYA90LALH	AJY108LALH	AJY126LALH	AJY144LALH	AJY162LALH	AJY180LALH	AJY198LALH	AJY216LALH	AJY234LALH	AJY252LALH	AJY270LALH	AJY288LALH	AJY306LALH	AJY324LALH	AJY342LALH	AJY360LALH	AJY378LALH	AJY396LALH	AJY414LALH	AJY432LALH	
Unit 1 Unit 2 Unit 3			AJYA72LALH	AJYA90LALH	AJY108LALH	AJY126LALH	AJY144LALH	AJYA90LALH AJYA72LALH	AJY108LALH AJYA72LALH	AJY108LALH AJYA90LALH	AJY108LALH AJY108LALH	AJY126LALH AJY108LALH	AJY144LALH AJY108LALH	AJY144LALH AJY144LALH	AJY108LALH AJY126LALH	AJY108LALH AJYA90LALH	AJY108LALH AJY108LALH	AJY126LALH AJY108LALH	AJY144LALH AJY108LALH	AJY144LALH AJY108LALH	AJY144LALH AJY108LALH	AJY144LALH AJY126LALH	AJY144LALH AJY126LALH	AJY144LALH AJY144LALH
Maximum Connectable Indoor Unit*1			15	16	17	21	24	32	32	32	35	39	42	45	48	48	48	48	48	48	48	48	48	
Indoor unit connectable capacity			kW	11.2-33.6	14.0-42.0	16.8-50.2	20.0-60.0	22.5-67.5	25.2-75.6	28.0-83.8	30.8-92.2	33.5-100.5	36.8-110.2	39.3-117.7	42.5-127.5	45.0-135.0	47.5-142.5	50.3-150.7	53.5-160.5	56.0-168.0	59.3-177.7	61.8-185.2	65.0-195.0	67.5-202.5
Power source			3-phase 4 wire, 400 V, 50Hz										3-phase 4 wire, 400 V, 50Hz											
Capacity	Cooling	kW	22.4	28.0	33.5	40.0	45.0	50.4	55.9	61.5	67.0	73.5	78.5	85.0	90.0	95.0	100.5	107.0	112.0	118.5	123.5	130.0	135.0	
	Heating		25.0	31.5	37.5	45.0	50.0	56.5	62.5	69.0	75.0	82.5	87.5	95.0	100.0	106.5	112.5	120.0	125.0	132.5	137.5	145.0	150.0	
Input power	Cooling	kW	5.51	7.73	9.62	11.53	14.17	13.24	15.13	17.35	19.24	21.15	23.79	25.70	28.34	26.97	28.86	30.77	33.41	35.32	37.96	39.87	42.51	
	Heating		5.72	7.83	9.28	11.45	12.60	13.55	15.00	17.11	18.56	20.73	21.88	24.05	25.20	26.39	27.84	30.01	31.16	33.33	34.48	36.65	37.80	
EER	Cooling	W/W	4.07	3.62	3.48	3.47	3.18	3.81	3.69	3.54	3.48	3.48	3.30	3.31	3.18	3.52	3.48	3.48	3.35	3.36	3.25	3.26	3.18	
COP	Heating	W/W	4.37	4.02	4.04	3.93	3.97	4.17	4.17	4.03	4.04	3.98	4.00	3.95	3.97	4.04	4.04	4.00	4.01	3.98	3.99	3.96	3.97	
Air flow late	High	m³/h	11,100	11,100	11,100	13,000	13,000	11,100 × 2	11,100 × 2	11,100 × 2	11,100 × 2	13,000 + 11,100	13,000 + 11,100	13,000 × 2	13,000 × 2	11,100 × 3	11,100 × 3	13,000 + 11,100 × 2	13,000 + 11,100 × 2	13,000 × 2 + 11,100	13,000 × 2 + 11,100	13,000 × 3	13,000 × 3	
Sound pressure level*2	Cooling	dB(A)	56	58	58	60	61	60	60	61	61	62	63	64	64	64	63	64	64	65	65	65	66	
	Heating		58	59	60	61	61	62	62	63	63	64	64	64	64	64	65	65	65	65	65	66	66	
Maximum external static pressure			Pa	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	
Compressor motor output			kW	3.9	3.9	3.9 + 4.5	3.9 + 4.5	3.9 + 4.5	3.9 × 2	3.9 × 2 + 4.5	3.9 × 2 + 4.5	3.9 × 2 + 4.5 × 2	3.9 × 2 + 4.5 × 2	3.9 × 2 + 4.5 × 2	3.9 × 2 + 4.5 × 2	3.9 × 2 + 4.5 × 2	3.9 × 3 + 4.5 × 2	3.9 × 3 + 4.5 × 3	3.9 × 3 + 4.5 × 3	3.9 × 3 + 4.5 × 3	3.9 × 3 + 4.5 × 3	3.9 × 3 + 4.5 × 3	3.9 × 3 + 4.5 × 3	
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	
Net Dimensions	Height	mm	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	
	Width		930	930	930	1,240	1,240	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	930 × 2	
	Depth		765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	765	
Weight			kg	220	220	275	303	303	220 + 220	275 + 220	275 + 220	275 + 275	303 + 275	303 + 275	303 + 303	296 + 296	275 + 275 + 220	275 + 275 + 275	303 + 275 + 275	303 + 275 + 275	303 + 303 + 275	303 + 303 + 275	303 + 303 + 303	303 + 303 + 303
Refrigerant			Type (Global Warming Potential)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	
Connection pipe diameter	Charge	kg	11.2	11.2	11.8	11.8	11.8	11.2 × 2	11.8 + 11.2	11.8 + 11.2	11.8 × 2	11.8 × 2	11.8 × 2	11.8 × 2	11.8 × 2	11.8 × 2 + 11.2	11.8 × 3	11.8 × 3	11.8 × 3	11.8 × 3	11.8 × 3	11.8 × 3	11.8 × 3	
	Liquid		12.70	12.70	12.70	12.70	12.70	15.88	15.88	15.88	15.88	15.88	15.88	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05		
	Gas		22.22	22.22	28.58	28.58	28.58	28.58	34.92	34.92	34.92	34.92	34.92	34.92	34.92	34.92	41.27	41.27	41.27	41.27	41.27	41.27	41.27	
Operation range	Cooling	°CDB	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-15 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46		
	Heating		-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21		

Energy Efficiency Combination

Rating Capacity range		HP	16	22	24	26	28	30	32	34	36	40	42	44
														
Set Model name			AJY144LALHH	AJY198LALHH	AJY216LALHH	AJY234LALHH	AJY252LALHH	AJY270LALHH	AJY288LALHH	AJY306LALHH	AJY324LALHH	AJY360LALHH	AJY378LALHH	AJY396LALHH
Unit 1 Unit 2 Unit 3			AJYA72LALH AJYA72LALH	AJY126LALH AJYA72LALH	AJYA72LALH AJYA72LALH AJYA72LALH	AJYA90LALH AJYA72LALH AJYA72LALH	AJY108LALH AJYA72LALH AJYA72LALH	AJY126LALH AJYA72LALH AJYA72LALH	AJY108LALH AJY108LALH AJYA72LALH	AJY126LALH AJY108LALH AJYA72LALH	AJY126LALH AJY108LALH AJYA72LALH	AJY126LALH AJY126LALH AJY108LALH	AJY126LALH AJY126LALH AJY126LALH	AJY144LALH AJY126LALH AJY126LALH
Maximum Connectable Indoor Unit**1			30	33	36	39	42	45	48	48	48	48	48	48
Indoor unit connectable capacity		kW	22.4-67.2	31.2-93.6	33.6-100.8	36.4-109.2	39.2-117.4	42.4-127.2	44.7-134.1	48.0-143.8	51.2-153.6	56.8-170.2	60.0-180.0	62.5-187.5
Power source			3-phase 4 wire, 400 V, 50Hz										3-phase 4 wire, 400 V, 50Hz	
Capacity	Cooling	kW	44.8	62.4	67.2	72.8	78.3	84.8	89.4	95.9	102.4	113.5	120.0	125.0
	Heating		50.0	70.0	75.0	81.5	87.5	95.0	100.0	107.5	115.0	127.5	135.0	140.0
Input power	Cooling	kW	11.02	17.04	16.53	18.75	20.64	22.55	24.75	26.66	28.57	32.68	34.59	37.23
	Heating		11.44	17.17	17.16	19.27	20.72	22.89	24.28	26.45	28.62	32.18	34.35	35.50
EER	Cooling	W/W	4.07	3.66	4.07	3.88	3.79	3.76	3.61	3.60	3.58	3.47	3.47	3.36
COP	Heating	W/W	4.37	4.08	4.37	4.23	4.22	4.15	4.12	4.06	4.02	3.96	3.93	3.94
Air flow late	High	m³/h	11,100 × 2	13,000 + 11,100	11,100 × 3	11,100 × 3	11,100 × 3	13,000 + 11,000 × 2	11,100 × 3	13,000 + 11,100 × 2	13,000 × 2 + 11,100	13,000 × 2 + 11,100	13,000 × 3	13,000 × 3
Sound pressure level**2	Cooling	dB(A)	59	61	61	62	62	63	62	63	64	64	65	65
	Heating		59	62	61	62	63	63	64	64	65	65	66	66
Maximum external static pressure		Pa	80	80	80	80	80	80	80	80	80	80	80	80
Compressor motor output		kW	3.9 × 2	3.9 × 2 + 4.5	3.9 × 3	3.9 × 3	3.9 × 3 + 4.5	3.9 × 3 + 4.5	3.9 × 3 + 4.5 × 2	3.9 × 3 + 4.5 × 2	3.9 × 3 + 4.5 × 2	3.9 × 3 + 4.5 × 3	3.9 × 3 + 4.5 × 3	3.9 × 3 + 4.5 × 3
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin
Net Dimensions	Height	mm	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690	1,690
	Width		930 × 2	930 + 1,240	930 × 3	930 × 3	930 × 3	930 × 3	930 × 2 + 1,240	930 × 3	930 × 2 + 1,240	930 + 1,240 × 2	930 + 1,240 × 2	1,240 × 3
	Depth		765	765	765	765	765	765	765	765	765	765	765	765
Weight		kg	220 + 220	303 + 220	220 + 220 + 220	220 + 220 + 220	275 + 220 + 220	303 + 220 + 220	275 + 275 + 220	303 + 275 + 220	303 + 303 + 220	303 + 303 + 275	303 + 303 + 303	303 + 303 + 303
Refrigerant	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
Connection pipe diameter	Charge	kg	11.2 × 2	11.8 + 11.2	11.2 × 3	11.2 × 3	11.8 + 11.2 × 2	11.8 × 2 + 11.2 × 2	11.8 × 2 + 11.2	11.8 × 2 + 11.2	11.8 × 2 + 11.2	11.8 × 3	11.8 × 3	11.8 × 3
	Liquid	mm	12.70	15.88	15.88	15.88	15.88	19.05	19.05	19.05	19.05	19.05	19.05	19.05
	Gas		28.58	34.92	34.92	34.92	34.92	34.92	34.92	34.92	41.27	41.27	41.27	41.27
Operation range	Cooling	*CDB	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46
	Heating		-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21

Heat Pump for Small Capacity Type

AIRSTAGE™ J-III

Fujitsu General provides air conditioning systems for a wide range of applications from small office buildings and stores to large houses.

System Outline

High Energy Efficiency

Heat pump inverter control is used to achieve an efficient cooling and heating operation in any indoor unit combination.

Flexible systems for small- and medium-size buildings air conditioning

Space saving design and long piping design allow for flexible installation on the roofs or balconies of small and medium-size buildings. Multiple indoor units of various capacities and types can be connected.




Features


Efficiency in actual operation

Top class high COP is achieved for all models by large heat exchanger, high efficient DC twin compressor, and our own technologies.

High EER / COP




Advanced high efficiency technology




Long Piping Length

Our advanced refrigerant control technology allows us to achieve a total refrigerant piping length of 180 m. This opens up new possibilities in system design.




Non-stop oil recovery operation

A comfortable room condition is maintained during oil recovery mode because the product continues to operate without stopping the cooling or heating operation.



Easier Installation

Connection check function : Possible to confirm whether wiring connection and address setting are correct by a quick check run function.



4,5,6HP : AJY040LBLAH / AJY045LBLAH / AJY054LBLAH **NEW**
AJY040LELAH [3phase] / AJY045LELAH [3phase] / AJY054LELAH [3phase]




Specifications

Rating Capacity range		HP	4	5	6	4	5	6
Model name			AJY040LBLAH	AJY045LBLAH	AJY054LBLAH	AJY040LELAH	AJY045LELAH	AJY054LELAH
Maximum Connectable Indoor Unit			1-9	1-10	1-13	1-9	1-10	1-13
Power source			Single-phase, ~230V, 50Hz			3-phase, ~400V, 50Hz		
Capacity	Cooling	kW	12.1	14.0	15.5	12.1	14.0	15.5
	Heating	kW	13.6	16.0	18.0	13.6	16.0	18.0
Input power	Cooling	kW	2.90	3.57	4.18	2.79	3.46	3.99
	Heating	kW	2.80	3.55	4.26	2.71	3.40	4.08
EER	Cooling	W/W	4.17	3.92	3.71	4.33	4.05	3.88
COP	Heating	W/W	4.86	4.51	4.23	5.01	4.70	4.41
Air flow late		m³/h	6,200	6,400	6,900	6,200	6,400	6,900
Sound pressure level	Cooling	dB(A)	50	51	53	50	51	53
	Heating	dB(A)	52	53	55	52	53	55
Heat exchanger fin			Blue fin	Blue fin	Blue fin	Blue fin	Blue fin	Blue fin
Net Dimensions	Height	mm	1,334	1,334	1,334	1,334	1,334	1,334
	Width	mm	970	970	970	970	970	970
	Depth	mm	370	370	370	370	370	370
Weight		kg	117	117	119	119	119	119
	Type (Global Warming Potential)		R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)	R410A (2,088)
Refrigerant	Charge	kg	4.8	5.3	5.3	4.8	5.3	5.3
	Liquid	mm	9.52	9.52	9.52	9.52	9.52	9.52
Connection pipe diameter	Gas	mm	15.88	15.88	19.05	15.88	15.88	19.05
			180	180	180	180	180	180
Total pipe length		m	50/40 (Outdoor unit: Upper/Lower)			50/40 (Outdoor unit: Upper/Lower)		
Max. height difference			50/40 (Outdoor unit: Upper/Lower)			50/40 (Outdoor unit: Upper/Lower)		
Operation range	Cooling	°C	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46	-5 to 46
	Heating	°C	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21	-20 to 21

Note: Specifications are based on the following conditions.
Cooling: Indoor temperature of 27°CDB/19°CWB, and outdoor temperature of 35°CDB/24°CWB.
Heating: Indoor temperature of 20°CDB/(15°CWB), and outdoor temperature of 7°CDB/6°CWB.
Pipe length: 7.5 m; Height difference between outdoor unit and indoor unit: 0 m.
The protective function may work when using it outside the operation range.

Dimensions

(Unit : mm)



Heat Pump for Small Capacity Type

AIRSTAGE™ J-IIS

Fujitsu General provides air conditioning systems for a wide range of applications from small office buildings and stores to large houses.



System Outline

Space saving and low sound level design

Economical individual air conditioning is realized by ALL-DC technology, large capacity DC twin rotary compressor, and 3-row heat exchanger though the size is compact.

Flexible systems for homes, shops, small-size buildings air conditioning



Due to compact size design and flexible piping design, J-IIS series can be installed easily at the place where the installation space is limited such as homes, shops, and small offices. Multiple indoor units of various capacities and types can be connected.



Features

Small and light weight outdoor unit

This model is much more compact than conventional 6HP comparable outdoor units. Even when installed on the balcony it fits within the height of the fence. The compact size with a height of less than 1 m allows it to be installed under windows and in tight spaces



It Can be Easily Carried and Installed Obscure Place


Current model / 6HP class
Height:1334 mm
Weight:117 kg

Model / 6HP class

Height difference
998 mm
▲25%


Light weight
87 kg
▲26%

Advanced high efficiency technology



Long piping length

Our advanced refrigerant control technology allows us to achieve a total refrigerant piping length of 80 m. This opens up new possibilities in system design.



4,5,6HP : AJY040LCLAH / AJY045LCLAH / AJY054LCLAH




Specifications

Rating Capacity range	HP	4	5	6
Model name		AJY040LCLAH	AJY045LCLAH	AJY054LCLAH
Maximum Connectable Indoor Unit		7	8	8
Power source		Single-phase, ~230V, 50Hz		
Capacity	Cooling	12.1		15.1
	Heating	13.6		16.5
Input power	Cooling	3.44		5.32
	Heating	3.09		4.26
EER	Cooling	3.52		2.84
COP	Heating	4.40		3.87
Air flow late		4,040		4,200
Sound pressure level	Cooling	51		54
	Heating	54		56
Heat exchanger fin	Height	Blue fin		Blue fin
	Width	998		998
Net Dimensions	Depth	970		970
	Weight	370		370
Refrigerant	Type (Global Warming Potential)	R410A (2,088)		R410A (2,088)
	Charge	kg		4.0
Connection pipe diameter	Liquid	9.52		9.52
	Gas	15.88		15.88
Total pipe length		80		80
Max. height difference		30		30
Operation range	Cooling	-5 to 46		-5 to 46
	Heating	-20 to 21		-20 to 21

Note : Specifications are based on the following conditions.
Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.
The protective function may work when using it outside the operation range.


Non-stop oil recovery operation

A comfortable room condition is maintained during oil recovery mode because the product continues to operate without stopping the cooling or heating operation.



Easier Installation


Connection check function : Possible to confirm whether wiring connection and address setting are correct by a quick check run function.



- Display connected indoor unit numbers
- Duplicately set address number of indoor unit can be displayed

Dimensions


















































































(Unit : mm)



Indoor units

Indoor Unit Lineup

12 Types, 66 Models, Capacity range from 1.1 kW to 28.0 kW

Capacity range (kW)		1.1	2.2	2.8	3.6	4.5	5.6	7.1	9.0	10.0	11.2	12.5	14.0	18.0	22.4	25.0	28.0
Model code		4	7	9	12	14	18	24	30	34	36	45	54	60	72	90	96
Cassette	4-way Compact Cassette	 AUXB04GALH	 AUXB07GALH	 AUXB09GALH	 AUXB12GALH	 AUXB14GALH	 AUXB18GALH	 AUXB24GALH									
	4-way Cassette						 AUXD18GALH	 AUXD24GALH									
							 AUXA18GALH	 AUXA24GALH	 AUXA30GALH	 AUXA34GALH	 AUXA36GALH	 AUXA45GALH	 AUXA54GALH				
	 Mini Duct (With drain pump)		 ARXK07GCLH	 ARXK09GCLH	 ARXK12GCLH	 ARXK14GCLH	 ARXK18GCLH	 ARXK24GCLH									
	Slim Duct (With drain pump)	 ARXD04GALH	 ARXD07GALH	 ARXD09GALH	 ARXD12GALH	 ARXD14GALH	 ARXD18GALH	 ARXD24GALH									
	Medium Static Pressure Duct							 ARXA24GBLH	 ARXA30GBLH		 ARXA36GBLH	 ARXA45GBLH					
	High Static Pressure Duct										 ARXC36GBTH	 ARXC45GBTH		 ARXC60GBTH*1	 ARXC72GBTH*1	 ARXC90GBTH*1	  ARXC96GBTH*1
	Large Airflow Duct						 ARXN18GATH*2	 ARXN24GATH*2	 ARXN30GATH*2	 ARXN34GATH*2	 ARXN36GATH*2	 ARXN45GATH*2					
Floor	Floor (*Same as Ceiling models)				 ABYA12GATH	 ABYA14GATH	 ABYA18GATH	 ABYA24GATH									
	Slim Concealed Floor (*Same as Slim Duct models)	 ARXD04GALH	 ARXD07GALH	 ARXD09GALH	 ARXD12GALH	 ARXD14GALH	 ARXD18GALH	 ARXD24GALH									
Ceiling	Ceiling				 ABYA12GATH	 ABYA14GATH	 ABYA18GATH	 ABYA24GATH	 ABYA30GATH		 ABYA36GATH	 ABYA45GATH	 ABYA54GATH				
Wall Mounted	Wall Mounted	 ASYA04GACH	 ASYA07GACH	 ASYA09GACH	 ASYA12GACH	 ASYA14GACH	 ASYA18GACH	 ASYA24GACH	 ASYA30GACH								
	Wall Mounted (EEV external)	 ASHE04GACH	 ASHE07GACH	 ASHE09GACH	 ASHE12GACH	 ASHE14GACH	With this model, connection of EV kit is necessary.										

*1: ARXC60/72/90G/96G cannot be connected to J-IIS and J-III series.
*2: Large Airflow Duct can be connected to V-III series only.

Indoor Units Specifications

4-way Compact Cassette



Model name			AUXB04GALH	AUXB07GALH	AUXB09GALH	AUXB12GALH	AUXB14GALH	AUXB18GALH	AUXB24GALH
Power source			Single-phase, ~230V, 50Hz						
Capacity	Cooling	kW	1.1	2.2	2.8	3.6	4.5	5.6	7.1
	Heating		1.3	2.8	3.2	4.1	5.0	6.3	8.0
Input power		W	23	25	25	29	35	36	84
Airflow rate	High	m³/h	530	540	550	600	680	710	1,030
	Med		420/450* ¹	450	450	530	590	580	830
	Low		300/350* ¹	350	350	390	390	400	450
Sound pressure level	High	dB(A)	34	34	35	37	38	41	50
	Med		28/30* ¹	30	30	34	34	35	44
	Low		21/25* ¹	25	25	27	27	27	30
Net Dimensions (H × W × D)			mm 245 × 570 × 570						
Weight			kg(lbs) 15 (33)						
Connection pipe diameter	Liquid (Flare)	mm	6.35						
	Gas (Flare)		12.70						
Drain hose diameter (I.D./O.D.)			25/32						
Cassette Grille	Model name	mm	UTG-UFYC-W						
	Net Dimensions (H×W×D)		50 × 700 × 700						
Weight			kg(lbs) 2.6 (6)						

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m. Voltage : 230 [V].
*1: This value is under cooling operation.

4-way Cassette



Model name			AUXD18GALH	AUXD24GALH	AUXA18GALH	AUXA24GALH	AUXA30GALH	AUXA34GALH	AUXA36GALH	AUXA45GALH	AUXA54GALH
Power source			Single-phase, ~230V, 50Hz								
Capacity	Cooling	kW	5.6	7.1	5.6	7.1	9.0	10.0	11.2	12.5	14.0
	Heating		6.3	8.0	6.3	8.0	10.0	11.2	12.5	14.0	16.0
Input power		W	39	46	51	51	59	77	80	99	119
Airflow rate	High	m³/h	1,150	1,280	1,420	1,420	1,600	1,750	1,800	1,900	2,000
	Med		940	1,040	1,230	1,230	1,300	1,300	1,300	1,370	1,370
	Low		870	870	1,100/1,000*1	1,100/1,000*1	1,100	1,100	1,100	1,100	1,100
Sound pressure level	High	dB(A)	36	38	40	40	40	43	44	46	47
	Med		30	33	36	36	38	38	38	39	39
	Low		29	29	33/31*1	33/31*1	33	33	33	33	33
Net Dimensions (H × W × D)		mm	246 × 840 × 840			288 × 840 × 840					
Weight		kg(lbs)	22 (48)			27 (59)					
Connection pipe diameter	Liquid (Flare)	mm					9.52				
	Gas (Flare)		15.88						19.05		
Drain hose diameter (I.D./O.D.)			25/32								
Cassette Grille	Model name		UTG-UGYA-W								
	Net Dimensions (H×W×D)		mm		50 × 950 × 950						
	Weight		kg(lbs)		5.5 (12)						

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m. Voltage : 230 [V].
*1: This value is "cooling operation / heating operation".

Mini Duct



Model name			ARXK07GCLH	ARXK09GCLH	ARXK12GCLH	ARXK14GCLH	ARXK18GCLH	ARXK24GCLH	
Power source			Single-phase, ~230V, 50Hz						
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.6	7.1	
	Heating		2.8	3.2	4.0	5.0	6.3	8.0	
Input power		W	28	28	35	66	73	80	
Airflow rate	High	m³/h	460	460	550	760	930	1,160	
	Med		420	420	480	560	740	960	
	Low		370	370	410	410	540	750	
Static pressure range		Pa	0 to 30	0 to 30	0 to 30	0 to 50	0 to 50	0 to 50	
Standard static pressure			10	10	10	15	15	15	
Sound pressure level	High	dB(A)	26	26	29	34	33	32	
	Me-Hi		25	25	27	31	30	30	
	Med		24	24	26	28	28	28	
	Lo-Hi		23	23	25	26	26	27	
	Low		22	22	24	24	24	25	
	Quiet		21	21	22	22	22	22	
Net Dimensions (H × W × D)		mm	198 × 700 × 450			198 × 900 × 450		198 × 1,100 × 450	
Weight		kg(lbs)	15.5 (34)			16 (35)		19 (42)	22.5 (50)
Connection pipe diameter	Liquid (Flare)	mm	6.35			9.52			
	Gas (Flare)		12.70			15.88			
Drain hose diameter (I.D./O.D.)			25/32						

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m. Voltage : 230 [V].

Slim Duct / Slim Concealed Floor



Model name			ARXD04GALH	ARXD07GALH	ARXD09GALH	ARXD12GALH	ARXD14GALH	ARXD18GALH	ARXD24GALH
Power source			Single-phase, ~230V, 50Hz						
Capacity	Cooling	kW	1.1	2.2	2.8	3.6	4.5	5.6	7.1
	Heating		1.3	2.8	3.2	4.0	5.0	6.3	8.0
Input power		W	40	44	50	54	92	83	122
Airflow rate	High	m³/h	510	550	600	600	800	940	1,330
	Med		400/470*¹	490	550	510	710	840	1,240
	Low		320/440*¹	440	480	450	610	750	1,100
Static pressure range		Pa	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 90	0 to 50
Standard static pressure			25	25	25	25	25	25	
Sound pressure level	High	dB(A)	26	28	29	30	34	34	35
	Med		21/25*¹	25	26	27	32	32	32
	Low		20/22*¹	22	24	24	28	28	29
Net Dimensions (H × W × D)		mm	198 × 700 × 620					198 × 900 × 620	198 × 1,100 × 620
Weight		kg(lbs)	17 (37)			18 (40)		22 (48)	26 (57)
Connection pipe diameter	Liquid (Flare)	mm	6.35					9.52	
	Gas (Flare)		12.70					15.88	
Drain hose diameter (I.D./O.D.)			25/32						

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m. Voltage : 230 [V].
*1: This value is under cooling operation.

Medium Static Pressure Duct



Model name			ARXA24GBLH	ARXA30GBLH	ARXA36GBLH	ARXA45GBLH
Power source			Single-phase, ~230V, 50Hz			
Capacity	Cooling	kW	7.1	9.0	11.2	12.5
	Heating		8.0	10.0	12.5	14.0
Input power		W	94	108	194	240
Airflow rate	High	m³/h	1,280	1,410	1,840	1,970
	Med		990	1,280	1,600	1,860
	Low		840	1,150	1,470	1,640
Static pressure range		Pa	0 to 150	0 to 150	0 to 150	0 to 150
Standard static pressure			40	50	50	60
Sound pressure level	High		31	34	37	41
	Med	27	32	35	38	
	Low	23	29	33	36	
Net Dimensions (H × W × D)		mm	270 × 1,135 × 700			
Weight		kg(lbs)	36 (79)	40 (88)		
Connection pipe diameter	Liquid (Flare)	mm	9.52			
	Gas (Flare)		15.88			
Drain hose diameter (I.D./O.D.)				25/32		
			19.05			

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m. Voltage : 230 [V].

High Static Pressure Duct



Model name			ARXC36GBTH	ARXC45GATH	ARXC60GATH*	ARXC72GBTH*	ARXC90GBTH*	ARXC96GATH*
Power source			Single-phase ~230V, 50Hz					
Capacity	Cooling	kW	11.2	12.5	18.0	22.4	25.0	28.0
	Heating		12.5	14.0	20.0	25.0	28.0	31.5
Input power		W	207	715	730	681	819	838
Airflow rate	High	m³/h	1,990	3,500	3,500	3,900	4,300	4,850
	Med		1,680	3,000	3,000	3,300	4,000	4,250
	Low		1,330	2,460	2,460	3,000	3,500	3,600
Static pressure range		Pa	0 to 200	100 to 250	100 to 250	0 to 300	0 to 300	0 to 300
Standard static pressure			100	100	100	150	150	150
Sound pressure level	High	dB(A)	42	49	49	47	48	48
	Med		36	45	45	43	46	45
	Low		32	42	42	40	44	42
Net Dimensions (H × W × D)		mm	400 × 1,050 × 500			450 × 1,587 × 700		550 × 1,587 × 700
Weight		kg(lbs)	40 (88)	46 (101)		84 (185)		105 (231)
Connection pipe diameter	Liquid	mm	9.52 (Flare)				12.70 (Brazing)	
	Gas		19.05 (Flare)				22.22 (Brazing)	
Drain hose diameter (I.D./O.D.)			25/32					

Indoor Units Specifications

Large Airflow Duct



Model name			ARXN18GATH	ARXN24GATH	ARXN30GATH	ARXN34GATH	ARXN36GATH	ARXN45GATH
Power source			Single-phase, ~230V, 50Hz					
Capacity	Cooling	kW	5.6	7.1	9.0	10.0	11.2	12.5
	Heating		6.3	8.0	10.0	11.2	12.5	14.0
Input power		W	154	205	306	432	572	572
Airflow rate	High	m³/h	2,280	2,640	3,200	3,720	4,120	4,120
	Med		—	—	—	—	—	—
	Low		—	—	—	—	—	—
Static pressure range		Pa	50 to 100	50 to 150	50 to 250	50 to 250	50 to 300	50 to 300
Standard static pressure			50	50	50	50	60	60
Sound pressure level	High	dB(A)	35	37	40	43	45	45
	Med		—	—	—	—	—	—
	Low		—	—	—	—	—	—
Net Dimensions (H × W × D)		mm	450 × 1,587 × 700					
Weight		kg(lbs)	84 (185)					
Connection pipe diameter	Liquid	mm	9.52 (Flare)					
	Gas		15.88 (Flare)					
Drain hose diameter (I.D./O.D.)				25/32				
			19.05 (Flare)					

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.
Voltage : 230 [V].

Floor / Ceiling



Model name			ABYA12GATH	ABYA14GATH	ABYA18GATH	ABYA24GATH
Power source			Single-phase, ~230V, 50Hz			
Capacity	Cooling	kW	3.6	4.5	5.6	7.1
	Heating		4.0	5.0	6.3	8.0
Input power		W	30	42	74	99
Airflow rate	High	m³/h	660	780	1,000	1,000
	Med		570	640	720	820
	Low		490	550	580	680
Sound pressure level	High	dB(A)	36	40	46	47
	Med		32	36	39	42
	Low		28	34	35	37
Net Dimensions (H × W × D)		mm	199 × 990 × 655			
Weight		kg(lbs)	25 (55)	26 (57)	26 (57)	27 (59)
Connection pipe diameter	Liquid (Flare)	mm	6.35		9.52	
	Gas (Flare)		12.70		15.88	
Drain hose diameter (I.D./O.D.)			25/32			

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.
Voltage : 230 [V].

Ceiling



Model name			ABYA30GATH	ABYA36GATH	ABYA45GATH	ABYA54GATH
Power source			Single-phase, ~230V, 50Hz			
Capacity	Cooling	kW	9.0	11.2	12.5	14.0
	Heating		10.0	12.5	14.0	16.0
Input power		W	66	85	131	180
Airflow rate	High	m³/h	1,630	1,690	2,010	2,270
	Med		1,370	1,400	1,600	1,780
	Low		1,140	1,170	1,230	1,280
Sound pressure level	High	dB(A)	42	45	48	51
	Med		38	38	42	45
	Low		33	34	35	36
Net Dimensions (H × W × D)		mm	240 × 1,660 × 700			
Weight		kg(lbs)	46 (101)		48 (106)	
Connection pipe diameter	Liquid (Flare)	mm	9.52		9.52	
	Gas (Flare)		15.88		19.05	
Drain hose diameter (I.D./O.D.)			25/32			

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.
Voltage : 230 [V].

Wall Mounted



Model name			ASYA04GACH	ASYA07GACH	ASYA09GACH	ASYA12GACH	ASYA14GACH	ASYE04GACH	ASYE07GACH	ASYE09GACH	ASYE12GACH	ASYE14GACH	
Power source			Single-phase, ~230V, 50Hz						Single-phase, ~230V, 50Hz				
Capacity	Cooling	kW	1.1	2.2	2.8	3.6	4.5	1.1	2.2	2.8	3.6	4.5	
	Heating		1.3	2.8	3.2	4.1	5.0	1.3	2.8	3.2	4.1	5.0	
Input power			W	13	17	18	22	34	12	15	16	21	34
Airflow rate	High	m³/h	450	490	500	560	670	450	490	500	560	680	
	Med		370/440*¹	450	450	480	490	370/440*¹	450	450	480	490	
	Low		320/420*¹	370/420*¹	370/420*¹	420	420	300/420*¹	370/420*¹	370/420*¹	420	420	
Sound pressure level	High	dB(A)	33	35	36	39	44	32	34	35	38	43	
	Med		27/32*¹	33	33	35	37	26/31*¹	32	32	34	35	
	Low		22/31*¹	27/31*¹	27/31*¹	31	32	19/30*¹	26/30*¹	26/30*¹	30	30	
Net Dimensions (H × W × D)			mm	275 × 790 × 215						275 × 790 × 215			
Weight			kg(lbs)	9 (20)						9 (20)			
Connection pipe diameter	Liquid (Flare)	mm	6.35						6.35				
	Gas (Flare)		12.70						12.70				
Drain hose diameter (I.D./O.D.)			13.8/15.8 to 16.7						13.8/15.8 to 16.7				
EV Kit (option)			-						UTR-EV09XB			UTR-EV14XB	

Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.
Voltage : 230 [V].
*1 : This value is under cooling operation.

Wall Mounted



Model name			ASYA18GACH		ASYA24GACH		ASYA30GACH	
Power source			Single-phase, ~230V, 50Hz					
Capacity	Cooling	kW	5.6	7.1		8.0		
	Heating		6.3	8.0		9.0		
Input power		W	32	60		91		
Airflow rate	High	m³/h	840	1,100		1,240		
	Med		770	910		980		
	Low		690	730		770		
Sound pressure level	High	dB(A)	41	48		52		
	Med		39	43		45		
	Low		35	35		35		
Net Dimensions (H × W × D)		mm	320 × 998 × 228					
Weight		kg(lbs)	15 (33)					
Connection pipe diameter	Liquid (Flare)	mm	9.52					
	Gas (Flare)		15.88					
Drain hose diameter (I.D./O.D.)			12/16					


Note : Specifications are based on the following conditions.

Cooling : Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating : Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length : 7.5 m; Height difference between outdoor unit and indoor unit : 0 m.
Voltage : 230 [V].

Controller

Control system overview

User's needs are supported by offering a variety of controls, such as individual control, central control and building management control options.



NEW

Wired Remote Controller (Touch Panel)

UTY-RNRYZ1



Max. Controllable
16 indoor units

Features

Easy operation by high-definition large STN-LCD touch panel screen

- Easy finger touch operation with LCD panel
- Built-in weekly/Daily timer(ON/OFF,Temp.,Mode)
- Backlight enables easy operation in a darkened room
- Room temperature display
- Control up to 16 indoor units
- Corresponds to 12 different languages (English, Chinese, French, German, Spanish, Russian, Polish, Italian, Greek, Portuguese, Turkish and Dutch)
- 2-wire type


High performance and compact size

In addition to the individual control, weekly timer, and various energy saving controls can be realized using one remote controller only.



Accurate and comfortable control


Indoor temperature can be detected accurately by the inclusion of a thermo sensor in the body of the wired controller.



Various energy saving control

Auto OFF timer

- The indoor unit automatically is turned off when it reaches to the preset operating time frame.
- The time frame of the "Auto off timer" can be flexibly scheduled.
- Can be set off time 30 to 240 minutes



Ex.) At interval time hour (17:00 to 24:00) to prevent forgetting to turn off
Set off time : 1 hour

2 schedules Weekly Timer

Set Temperature Auto Return

Set Temperature Upper and Lower Limit Setting

Specifications

Model name	UTY-RNRYZ1
Power Source	DC 12 V
Dimensions (H × W × D) (mm)	120 × 120 × 20.4
Weight (g)	220

DC12 V is supplied by the indoor unit.

Comparison table of Controllers

Item										
Model name	UTY-RNRYZ1	UTY-RLRY	UTY-RSKY	UTY-RHKY	UTY-LNHY	UTY-CGGY	UTY-DCGY	UTY-DTGYZ1	UTY-ALGX	UTY-APGX
Max. controllable remote controller groups	1	1	1	1	1	8	100	400	400	1600
Max. controllable indoor units	16	16	16	16	16	128	100	400	400	1600
Max. controllable groups	—	—	—	—	—	—	16	400	400	1600
Air conditioning control function	On / Off	●	●	●	●	●	●	●	●	●
	Operation mode setting	●	●	●	—	●	●	●	●	●
	Fan speed setting	●	●	●	●	●	●	●	●	●
	Room temp. setting	●	●	●	●	●	●	●	●	●
	Room temp. set point limitation	●	●	—	—	—	●	●	●	●
	Test operation	●	●	●	—	—	●	●	—	—
	Up/down air direction flap setting	●	●	—	—	●	●	●	●	●
	Right/left air direction flap setting	●	●	—	—	●	●	●	●	●
	Group setting	—	—	—	—	—	●	●	●	●
	RC prohibition	—	—	—	—	—	●	●	●	●
Display	Anti freeze setting	●	—	—	—	—	●	●	●	●
	Economy mode setting	●	●	—	—	—	●	●	●	●
	Error	●	●	●	●	—	●	●	●	●
	Defrosting	●	●	●	●	—	●	●	●	●
	Current time	●	●	—	—	●	●	●	●	●
	Day of week	●	●	—	—	—	●	—	●	●
	R.C. prohibition	●	●	●	●	—	●	●	●	●
	Cooling/heating priority	●	●	●	●	—	●	●	●	●
	Address display	●	●	●	●	—	●	●	●	●
	Room temp	●	—	—	—	—	—	—	—	—
Timer	Multi language	●	—	—	—	—	●	●	●	●
	Summer time	●	—	—	—	—	●	●	●	●
	Name registration	●	—	—	—	—	●	●	●	●
	Backlight	●	—	●	●	—	—	●	—	—
	2D floor layout / 3D building display	—	—	—	—	—	—	—	—	●
	Schedule timer	Period	Week	Week	—	—	Week	Week	Year	Year
		On/off, Temp, Mode, Times per day	8	4	—	—	4	20	20	144
	On/off timer	●	●	—	—	●	—	—	—	—
	Sleep timer	—	—	—	—	●	—	—	—	—
	Program timer	—	—	—	—	—	—	—	—	—
	Auto off timer	●	●	—	—	—	—	—	—	—
	Day off	●	●	—	—	—	●	●	●	●
	Min. unit of timer setting (Minutes)	10 × 30	30	—	—	5	10	10	10	10
Control	Status monitoring system	—	—	—	—	—	—	●	●	●
	Electricity charge apportionment	—	—	—	—	—	—	○	○	●
	Error history	●	●	—	—	—	●	●	●	●
	Emergency stop	—	—	—	—	—	●*2	●*2	—	—
	Remote management	—	—	—	—	—	—	●	○	●
	Energy saving management	—	—	—	—	—	—	—	○	○
	E-mail notification for malfunction	—	—	—	—	—	—	●	●	●
	Key lock	● Child lock	● Child lock	—	—	—	● Child lock	● Password setting	● Password setting	● Password setting

*1 "Operation mode" setting is not available for this model.

*2 This function is available only through external input control.

● : Supported ○ : Optional function
— : Not supported yet

Wired Remote Controller

UTY-RLRY



Features

- Various timer setup (ON / OFF / WEEKLY) are possible.
- The room temperature can be controlled by detecting the temperature accurately with Built-in thermo sensor.
- When a failure occurs, the error code is displayed.
- Error history. (Last 16 error codes can be accessed.)
- 2-wire type

Max. Controllable
16 indoor units


High performance and compact size

In addition to the individual control, weekly timer, and various energy saving controls can be realized using only one remote controller.




High visibility and easy operation

- "Mode", "Set Temp", and "Fan" are displayed at large size on the top screen.
- Each function to be set is indicated by an icon.
- Control guide is displayed and operation is simple and straightforward.




Auto-off timer

- The indoor unit automatically turns off after a set time has passed.



Weekly timer function

- Not only time setting On / Off, but also setting of the operation mode and set temperature can be set by Weekly timer function.



Various energy saving control

Set Temperature Auto Return

Set Temperature Upper and Lower Limit Setting

Specifications

Model name	UTY-RLRY
Power Source	DC 12 V
Dimensions (H × W × D) (mm)	120 × 120 × 17
Weight (g)	170

DC12 V is supplied by the indoor unit.

Simple Remote Controller

UTY-RSKY / UTY-RHKY (Without operation mode)



Features

Compact remote controller provides access to basic functions

- Up to 16 indoor units can be controlled with one remote controller.
- Suitable for hotels or offices as it is easily operated with no complex functions.
- 3-wire type

Max. Controllable
16 indoor units

Easy-to-use operation

- Provides access to basic operations, such as Start / Stop, Fan control, Operation mode switching, and Room temperature setting.
- A large On / Off button is provided in the centre of the remote controller for easy operation.
- Can be used jointly with other individual control unit.
- Following an error display, diagnostics can be carried out on the controller.


Backlight

- Backlight enables easy operation in a darkened room.
- Backlight activates during all button operations, and lasts 10 seconds in Operation mode and 5 seconds in stop mode after a button is pressed.



Simple installation

Can be mounted on the European Mounting Box (Installation dimension: 60mm) or the JIS Built-in Box (Installation dimension: 83.5mm).



Functions

Model	UTY-RSKY	UTY-RHKY
On / Off	●	●
Fan control	●	●
Operation mode	●	—*1
Room temp. setting	●	●

*1: "Operation mode" setting is not available. It is recommend to use together with other type controller.

Specifications

Model name	UTY-RSKY	UTY-RHKY
Power Source	DC 12 V	DC 12 V
Dimensions (H × W × D) (mm)	120 × 75 × 14	120 × 75 × 14
Weight (g)	90	90

DC12 V is supplied by the indoor unit.

Wireless Remote Controller

UTY-LNHY



Features

Simple and sophisticated operations with a choice of 4 daily timers

- A single controller controls up to 16 indoor units.

Built-in timers

4 timer programs: On / Off / Program / Sleep
Program timer: Operates ON/OFF timer once within 24 hours
Sleep timer: Corrects the set temperature automatically during sleep time

Easy installation and operation

Code selector switch prevents indoor unit mix-up (up to 4 codes)
Wide and precise transmitting range

Max. Controllable
16 indoor units
Selectable
4 daily timers

IR Receiver Unit

UTB-YWC



Features

Necessary to control for all Duct types* by Wireless Remote Controller

*Only Large Airflow Duct can not be connected to IR Receiver Unit.

IR Receiver Unit

UTY-LRHYB1



Features

Cassette type indoor unit can be controlled with Wireless Remote Controller


Specifications

Model name	UTY-LNHY	UTB-YWC	UTY-LRHYB1
Battery	1.5 V (R03 / LR03 / AAA) × 2	DC 5 V	DC 5 V
Dimensions (H × W × D) (mm)	170 × 56 × 19	145 × 90 × 30	193.9 × 193.9 × 31.2
Weight (g)	85	150	140

DC12 V is supplied by the indoor unit.

Group Remote Controller

UTY-CGGY



Features


Group control of indoor units with simple operation

- Up to 8 remote controller groups can be controlled by one Group Remote Controller.
- Up to 64 Group Remote Controllers can be connected in one VRF network system.
- Network Converter is required to connect Group Remote Controllers to a VRF network system. (Network Converter allows up to 4 Group Remote Controllers)
- 3-wire type

Max. Controllable
8 remote controller groups
Max. Controllable
64 group R.C. in a VRF network system

Control up to 8 remote controller groups

- Single Group Remote Controller controls and monitors up to 8 remote controller groups.



High performance and compact size

ON / OFF, Operating mode, Room temperature and Fan speed setting can be controlled / monitored centrally or individually.



Built-in weekly timers

The weekly timer is provided as a standard function.

Specifications

Model name	UTY-CGGY
Power Supply	DC 12 V
Dimensions (H × W × D) (mm)	120 × 120 × 18
Weight (g)	200

DC12 V is supplied by the indoor unit.

Central Remote Controller

UTY-DCGY



Max. Controllable
100 indoor units

Max. Controllable
16 groups


Features

For small- and medium-sized buildings and tenants

- Individual control and monitor of 100 indoor units
- 5 inch TFT color screen
- High visibility and easy operation
- External input / output contact
- Detachable power supply unit
- Corresponds to 7 different languages like English, Chinese, French, German, Spanish, Russian, Polish.

System overview


- It allows multiple indoor units grouping (Max.16 groups controlled)
- Interlock with external device




Easy Installation

- The control panel and power supply unit can be installed separately.
- For flexibility in installation, the Control panel can be built into the wall or fix on the wall.

Setting pattern 1



Setting pattern 2



Functions

- Diverse control of indoor units
- Weekly timer
- Automatic clock adjustment
- Error history

Specifications

Model name	UTY-DCGY	
	Control Panel	Power Supply Unit
Power Supply	DC 5 V	100-240 V, 50-60Hz, Single phase
Dimensions (H × W × D) (mm)	120 × 162 × 25.7	99 × 135 × 39.2
Weight (g)	308	355

<PACKING LIST>

Packing List	Control Panel / Power Supply Unit / Connecting cable, etc.
--------------	--

NEW

Touch Panel Controller

UTY-DTGYZ1



Max. Controllable
400 indoor units


Max. Controllable
100 outdoor units

Max. Controllable
400 groups

Features


- Large-sized 7.5-inch TFT color
- LCD Easy finger touch operation
- Stylish shape and design to suit all application
- No additional component is required for installation
- Up to 400 indoor units can be controlled
- Selectable 2 display types (Icon / List) in monitoring mode
- Corresponds to 7 different languages, English, Chinese, French, German, Spanish, Russian, Polish.

Diverse operation management




Remote monitoring and operation

- Air conditioner can be monitored and controlled via LAN from PC.
- Error contents are notified automatically by E-mail at error occurrence to handle the trouble promptly.



Electricity charge apportionment (Option: UTY-PTGXA)

- Electricity charge apportionment can be performed easily, when billing users for the air conditioning power consumed.



*: Electricity meter (1unit) can be connected to external input connector of the TPC unit. In this case, electricity meter cannot be connected to outdoor unit simultaneously.

Easy installation

- Touch Panel Controller is easily mounted to the wall.
- Flat back surface allows to be installed wherever it is needed.
- No additional component is required for installation.



Specifications

Model name	UTY-DTGYZ1	UTY-PTGXA
Power Supply	100-240 V 50/60Hz, Single phase	DC 5V (USB Bus power)
Dimensions (H × W × D) (mm)	260 × 246 × 54	62 × 17 × 10
Weight (g)	2,150	9
Interface	Transmission/LAN/USB/EXT IN/EXT OUT/Reset SW	USB

System Controller

UTY-APGX **Software**

Features


System Controller realizes the advanced integrated monitoring & control of VRF network system from small scale buildings to large scale buildings.

Max. Controllable
4 VRF network systems

Max. Controllable
400 outdoor units

Max. Controllable
1,600 indoor units

- Up to a maximum of 4 VRF network systems, 1600 indoor units, and 400 outdoor units can be controlled.
- In addition to air conditioning precision control function, central remote control, electricity charge calculation, schedule management, and energy saving functions are strengthened and building manager and owner needs are met.
- Corresponds to 7 different languages (English, Chinese, French, German, Spanish, Russian, Polish)



System Controller Lite

UTY-ALGX **Software**

Features

System Controller Lite has standard functions sufficient for air conditioner management in small and medium scale buildings .

Max. Controllable
1 VRF network systems

Max. Controllable
100 outdoor units

Max. Controllable
400 indoor units


- Up to a maximum of 1 VRF network system, 400 indoor units, and 100 outdoor units can be controlled.
- In addition to air conditioning precision control function, a variety of management software is available as an option to give customers a wide range of choice.
- Corresponds to 7 different languages (English, Chinese, French, German, Spanish, Russian, Polish)



High visibility and Easy operation

Click & Operate: The property is shown visually from the perspective most suitable for operation and operated accordingly (Click & Operate). You can select from among the 4 displays of site, building, floor, or list.

Freely define groups for batched control: Indoor units can be freely grouped for simple batched control from a tree menu. Grouping by hierarchal structure, such as by section, division or department is possible.




Diverse operation management & Data management

Standard for System Controller and System Controller Lite

Schedule management

- Annual schedules can be set for each remote controller group / user defined group.
- Start / stop, operating mode, remote controller prohibition, and temperature settings can be set up to 143 times per day at 10 minute intervals for up to 101 configurations for each remote controller group.
- Settings can be made for periods straddling midnight.
- Allows programming of special settings for holidays, including public holidays, for a complete year.
- Low noise operation of outdoor unit can be scheduled.



Diverse control of indoor unit and outdoor unit

- Indoor unit operation state, operation mode, etc. are displayed
- Indoor unit start / stop and operation mode switching
- Room temperature set point limitation
- Outdoor unit low noise setting

Remote controller prohibition

This prohibits changes to the operation mode, temperature, start/stop, etc.

Error display & E-mail notification

Error is notified with popup message, audible sound and E-mail real time when error occurs. Error for the past 1 year are logged and can be reviewed later.

Operating & control record

Displays the history of operation status and control.

Data base import/export

Imports/exports registration data, layout data, and image data. Only the administrator can make this setting.

Automatic clock adjustment

The time setting of each controller can be set in batch automatically.

Electricity charge apportionment



Standard for System Controller

Option for System Controller Lite UTY-PLGXA1

Electricity charge apportionment calculation framework

Suppose you want to find the power consumed by the air conditioners of each tenant from the electricity charge for each month. With electricity charge apportionment function, used energy apportionment ratio will be provided, calculating in detail the energy consumed by the units used by each tenant. This information is then used to calculate the charges for the electricity consumed for air conditioning by each tenant from the total electricity charges in the bill from the electric power company. (See figure at right)

The detailed calculation takes into consideration such things as unused rooms and nighttime electricity charges and shows them in a charges calculation sheet.




Remote management


- Standard for System Controller
- Option for System Controller Lite UTY-PLGXA1

System Controller may be used on site or remotely over various networks for remote central control. System Controller requires 2 softwares working together. VRF Controller runs on site and communicate with VRF system. VRF Explorer runs remotely and provides user interface and communicate with the VRF Controller. VRF Controller and VRF Explorer program may run in a single PC or in different PCs separated by network. By using VRF Explorer software, one PC can perform central control of 10 VRF system sites with max. 20 buildings per site.

On site central control




Remote central control



Energy saving management

- Option for System Controller UTY-PEGX
- Option for System Controller Lite UTY-PLGXE1

A variety of energy saving operations can be set and managed depending on the season, weather, and time period. Excellent energy saving operation is performed while keeping users comfortable.



Energy saving graph data: This graph compares the electricity consumption with the previous month and previous year to make it easy to analyze the energy saving effect.

Indoor unit rotation operation

The operation of indoor units can be automatically rotated within a group in accordance with the set annual schedule to reduce power consumption while maintaining comfort. The indoor unit operation stoppage rate can be selected.

Peak cut operation

A power meter is connected to detect the total power consumption while shifting the indoor unit set temperature, set the indoor unit forced thermostat off, and taking other measures to carefully control the power consumed while maintaining comfort and conducting control to maintain the target power consumption set for each time. The indoor units to be controlled can be freely grouped and the control level can be set.

Outdoor unit capacity save

Outdoor unit capacity save switches the outdoor unit capability upper limit to suppress power consumption during hot summers and cold winters by averaging the power saving effect of each refrigerant system. You can select from 50% or more of the capacity upper limit.

FUNCTIONS SUMMARY

Function	Type	System controller					
		UTY-APGX	Option UTY-PEGX	UTY-ALGX	Option UTY-PLGXR1	Option UTY-PLGXA1	Option UTY-PLGXE1
System specification	Max. VRF networks supported	4	-	1	-	-	-
	Max. indoor unit / remote controller groups per VRF network	400	-	400	-	-	-
	Max. outdoor units per System controller	100	-	100	-	-	-
	Max. indoor units / remote controller groups per System controller	1600	-	400	-	-	-
	Max. outdoor units per System controller	400	-	100	-	-	-
	Multi site display	10	-	10	-	-	-
Site supervision	Number of building / 1 site	20	-	-	-	-	-
	Number of floor per 1 site	200	-	-	-	-	-
	Number of floor per 1 building	50	-	-	-	-	-
	3D graphical layout view	○	-	-	-	-	-
	2D graphical layout view	○	-	-	-	-	-
	List display	○	-	○	-	-	-
	Tree display	○	-	○	-	-	-
	Group display	○	-	○	-	-	-
	Error notification	○	-	○	-	-	-
	Audible alarm	○	-	○	-	-	-
Error management	Error e-mail notification	○	-	○	-	-	-
	Error history	○	-	○	-	-	-
History	Operation history	○	-	○	-	-	-
	Control history	○	-	○	-	-	-
Operation control	Individual control	On/Off	○	○	-	-	-
		Operation mode	○	○	-	-	-
		Room temperature	○	○	-	-	-
		Fan speed	○	○	-	-	-
		Air flow direction	○	○	-	-	-
		Economy mode	○	○	-	-	-
		Room temperature set point limitation	○	○	-	-	-
		Test operation	○	○	-	-	-
		Antifreeze	○	○	-	-	-
		Outdoor unit low noise setting	○	○	-	-	-
		Remote control prohibition setting	○	○	-	-	-
		Temperature upper and lower limit setting	○	○	-	-	-
	Individual management	Filter sign reset	○	○	-	-	-
		Memory operation	○	○	-	-	-
	Other	Pattern operation	○	○	-	-	-
		Annual Schedule	○	○	-	-	-
Schedule	Special day setting	○	-	○	-	-	-
	On / off per day	72	-	72	-	-	-
	On / off per week	504	-	504	-	-	-
	Day off	○	-	○	-	-	-
	Min. unit of timer setting (Minutes)	10	-	10	-	-	-
	Low noise mode Weekly schedule	○	-	○	-	-	-
	Remote monitoring	○	-	-	○	-	-
	Remote operation control	○	-	-	○	-	-
Remote management	Remote function setting	○	-	-	○	-	-
	Apportionment charge/bill calculation	○	-	-	-	○	-
Electricity charge apportionment	Tenant (block) setting	○	-	-	-	○	-
	Common facilities apportionment setting	○	-	-	-	○	-
	Rated power consumption allotment setting	○	-	-	-	○	-
	Individual calculation at cooling and heating	-	○*	-	-	○	-
	Electricity meter supported	-	○	-	-	○	-
Energy saving management	Indoor unit rotation	-	○	-	-	-	○
	Peak cut control	-	○	-	-	-	○
	Outdoor unit capacity save	-	○	-	-	-	○
	Record of energy saving operation	-	○	-	-	-	○
	Energy saving information	-	○	-	-	-	○
	Power consumption monitor	-	○	-	-	-	○
	Electricity meter supported	-	○	-	-	-	○
	Database import/export	○	-	○	-	-	○
Others	Automatic clock adjustment	○	-	○	-	-	-
	Multi language	7 languages	-	7 languages	-	-	-

*:Power calculation application software is necessary, please contact the local FGL representative. ○: Available. - : Not available.

Personal computer system requirements

	System Controller	System Controller Lite
Operating system	• Microsoft® Windows Vista® Home Premium (32-bit) SP2, Windows Vista® Business (32-bit) SP2 • Microsoft® Windows® 7 Home Premium (32-bit or 64-bit) SP1, Windows® 7 Professional (32-bit or 64-bit) SP1 • Microsoft® Windows® 8 (32-bit or 64-bit), Windows® 8 Pro (32-bit or 64-bit) • Microsoft® Windows® 8.1 (32-bit or 64-bit), Windows® 8.1 Pro (32-bit or 64-bit) • Microsoft® Windows® 10 Home (32-bit or 64-bit), Windows® 10 Pro (32-bit or 64-bit) [Supported languages] English, Chinese, French, German, Russian, Spanish, and Polish	
CPU	Intel® Core™ i3 2 GHz or higher	
Memory	• 2 GB or more (for Windows Vista® and Windows® 7 [32-bit]) • 4 GB or more (for Windows® 7 [64-bit], Windows® 8, Windows® 8.1, and Windows® 10)	
HDD	40 GB or more of free space	
Display	1024 x 768 or higher resolution	
Interface	• Ethernet port (for getting access to the Internet using LAN) or Modem (for getting access to the Internet using Public Telephone Line) • USB ports (Maximum of 6 ports) (Required only for the Server PC that works as VRF Controller) - Maximum of 2 USB ports are required for WibuKey connection - Maximum of 4 USB ports are required for Echelon® U10 USB Network Interface * Maximum number of required USB port depends on the applicable system configuration.	• Ethernet port (for getting access to the Internet using LAN) or Modem (for getting access to the Internet using Public Telephone Line) • USB ports (Maximum of 5 ports) (Required only for the Server PC that works as VRF Controller) - Maximum of 4 USB ports are required for WibuKey connection - 1 USB port is required for Echelon® U10 USB Network Interface * The maximum number of required USB port depends on the applicable system configuration.
Graphic accelerator	Microsoft® DirectX® 9.0c compatible	
Software	Adobe® Reader® 9.0 or later	
Optical drive	DVD-ROM drive	

- Personal computer that satisfies the following system requirements
- Echelon® U10 USB Network Interface – TP/FT-10 Channel (Model number: 75010R) (Required for each VRF Network.)


PACKING LIST

Type	For System controller			For System controller Lite		
	System Controller	Option Energy manager	System Controller Lite	Remote access	Option Electricity charge apportionment	Option Energy saving
Model name	UTY-APGX	UTY-PEGX	UTY-ALGX	UTY-PLGXR1	UTY-PLGXA1	UTY-PLGXE1
DVD-ROM	1	1	1	—	—	—
WibuKey*1(Software protection key)	1	1	1	1	1	1

*1: Software protection key to be inserted in a USB slot running System Controller or System Controller Lite. System Controller or System Controller Lite may only run on a PC with Wibu Key. However, WibuKey is not required for remote VRF Explorer software.

BACnet® Gateway

UTY-ABGX Software




Features

- It is possible to connect medium to large sized BMS to VRF network system via BACnet®, a global standard for open networks.
- A maximum of 1600 indoor units with 4 VRF network systems (a maximum of 400 indoor units & 100 outdoor units for one network system) can be connected to one BACnet® Gateway.
- It is possible to control or monitor VRF network system from BMS via BACnet® Gateway.
- Compatible with BACnet® (ANSI / ASHRAE-135-2004) application specific controller (B-ASC).
- Compatible with BACnet®/IP over Ethernet.
- Scheduling function, Alarm & Event functions as well as Electricity Change Apportionment function are provided in BACnet® Gateway.
- Connection between VRF network system to personal computer is possible via small U10 USB interface. However, both U10 USB interface & personal computer are locally purchased items.
- Corresponds to 7 different languages, English, Chinese, French, German, Spanish, Russian, Polish.

Max. Controllable
4
VRF network
systems
Max. Controllable
400 outdoor units
Max. Controllable
1,600 indoor units

Installation example



Personal computer system requirements

	UTY-ABGX
Operating system	<ul style="list-style-type: none">• Microsoft® Windows Vista® Home Premium (32-bit) SP2, Windows Vista® Business (32-bit) SP2• Microsoft® Windows® 7 Home Premium (32-bit or 64-bit) SP1, Windows® 7 Professional (32-bit or 64-bit) SP1• Microsoft® Windows® 8 (32-bit or 64-bit), Windows® 8 Pro (32-bit or 64-bit)• Microsoft® Windows® 8.1 (32-bit or 64-bit), Windows® 8.1 Pro (32-bit or 64-bit)• Microsoft® Windows® 10 Home (32-bit or 64-bit), Windows® 10 Pro (32-bit or 64-bit) [Supported languages] English, Chinese, French, German, Russian, Spanish, and Polish
CPU	Intel® Core™ i3 2 GHz or higher
Memory	<ul style="list-style-type: none">• 2 GB or more (for Windows Vista® and Windows® 7 [32-bit])• 4 GB or more (for Windows® 7 [64-bit], Windows® 8, Windows® 8.1, and Windows® 10)
HDD	40 GB or more of free space
Display	1024 x 768 or higher resolution
Interface	<ul style="list-style-type: none">• Ethernet port (for getting access to the Internet using LAN)• USB ports (Maximum of 5 ports)<ul style="list-style-type: none">- 1 USB port is required for WibuKey connection- Maximum of 4 USB ports are required for Echelon® U10 USB Network Interface * Maximum number of required USB ports depends on the applicable system configurations.
Software	Adobe® Reader® 9.0 or later
Optical drive	DVD-ROM drive


<Packing list>

Name and shape	Quantity	Application
DVD-ROM	1	Includes the software and manuals for BACnet® Gateway.
WibuKey (Software protection key)	1	Software protection key to be connected to USB port on the BACnet®-installed PC. BACnet® Gateway runs only on a PC with WibuKey.

- Personal computer that satisfies the following system requirements
- Echelon® U10 USB Network Interface – TP/FT-10 Channel (Model number: 75010R) (Required for each VRF Network.)

Network Convertor for LONWORKS®

UTY-VLGX




Max. Controllable
4 units to BMS
Max. Controllable
100 outdoor units
Max. Controllable
128 indoor units

Features

- For connection between VRF network system and a LONWORKS® open network for management of small to medium-sized BMS and VRF network system.
- The UTY-VLGX permits central monitoring and control of a VRF network system from a BMS through a LONWORKS® interface.
- Up to 128 Indoor units can be connected to one Network Convertor for LONWORKS®

Installation example




Specifications

Model name	UTY-VLGX
Power Supply	208-240V 50/60Hz, Single phase
Power Consumption (W)	4.5
Dimensions (H × W × D) (mm)	67 × 288 × 211
Weight (g)	1,500

Transmission specifications (BMS side)


Transmission speed	78 kbps
Transceiver	FT-X1 (Echelon® Corporation)
Transmission way form	Free topology
Terminal resistor	None (It attaches at the terminal of a network.)

Dimensions



NEW MODBUS® Convertor

UTY-VMGX



Features


The MODBUS Convertor allows a complete integration of air conditioners into MODBUS Networks.

- Compact and lightweight design
- Direct connection to MODBUS Network
- Up to 128 indoor units can be controlled in one MODBUS Convertor
- The MODBUS Convertor permits central monitoring and control of air conditioners from BMS or Central Controller.

Max. Controllable
9 units to one VRF


Max. Controllable
100 outdoor units

Selectable
128 indoor units




Connectable MAX 9

Up to 9 convertors can be connected to a VRF network. The simultaneous controls such as ON/OFF or temperature settings can be done for each zone.



Traceability of sources of connection error

It is easy to locate the source of error if any connection errors should occur after completion of installation works.



Specifications

Model name	UTY-VMGX
Power Supply	AC220/240V 50/60Hz
Input power (W)	Max. 2
Dimensions (H × W × D) (mm)	54 × 260 × 150
Weight (g)	1,100

MODBUS® Interface


FJ-RC-MBS-1



Features

The MODBUS Interface allows a complete integration of air conditioners into MODBUS Networks.

- Simple installation due to small and compact size.
- No separate external power supply required.
- The MODBUS Interface permits central monitoring and control of air conditioners from BMS.



KNX® Interface


FJ-RC-KNX-1i



Features

The KNX Interface allows a complete integration of air conditioners with KNX Network systems.

- Simple installation due to small and compact size.
- No separate external power supply required (just KNX bus power).
- Can be used for single indoor units and group controlled (up to 16) indoor units.



Specifications

Model name	FJ-RC-MBS-1
Dimensions (H × W × D) (mm)	93×53×58
Weight (g)	85

Model name	FJ-RC-KNX-1i
Dimensions (H × W × D) (mm)	70×70×28
Weight (g)	70

Wireless LAN Interface


FJ-RC-WIFI-1



Features



- It is the most advanced solution to remotely manage an Air Conditioning system using all sort of mobile devices such as Smartphones, Tablets and PC
- No separate external power supply required
- Can be used for single indoor units and group controlled (up to 16) indoor units



Basic control

- Turning the units on and off
- Mode control (Heat, Cool, Dry, Auto, Fan)
- Fan speed setting
- Louver position (Airflow direction setting)
- Room temperature display
- Set temperature control
- Multi Language
- One Scene and Timer



(Application screen image)

Advanced control (Optional functions)

- Climate working modes (ECO, Comfort, Powerful) (future release)
- Schedulable functionalities (ON/OFF, Modes, Set point temperature, Fan Speed, Louver position)
- Set temperature limitation (future release)
- Multiple Scenes & Timers and Calendar function

Notifications and history


- Alerts e-mail notification (future release)
- Air conditioning malfunction alerts
- Connectivity monitoring and alerts
- History (future release)

Specifications

Model name	FJ-RC-WIFI-1
Dimensions (H × W × D) (mm)	70×108×28
Weight (g)	80

External Switch Controller

UTY-TEKX



Features



Air conditioner switching can be controlled by connecting other sensor switches

- In combination with a field supply Card-Key Switch or other sensor, the External Switch Controller allows control of the ON / OFF, Room temperature, Fan speed and Master control functions. This makes this product suitable for installations such as hotel rooms.
- Card-key or other sensor switches are available as a locally purchased parts.

Installation example

Auto mode operation, which switches the cooling and the heating automatically, is enabled by using the sensor switch and External Switch Controller.


Note: All indoor units will operate in the same mode.



- Note 1.
Please choose a thermosensor switch which can be set up for T1 and T2.
- Note 2.
The remote controller's operation is prior to the auto mode operation.

Signal Amplifier


UTY-VSGXZ1



Features

- Transmission Line length can be extended up to 3,600m with multiple Signal Amplifiers.
- Up to 8 signal amplifiers can be installed in a VRF network system.
- A signal amplifier is required,
(1) When the total wiring length of the transnission line exceeds 500m.
(2) When the total number of units on the transnission line exceeds 64.

Installation example



Specifications

Model name	UTY-TEKX
Power Supply	DC 12V
Dimensions (H × W × D) (mm)	120 × 75 × 30
Weight (g)	100

DC12V is supplied by the indoor unit.


Model name	UTY-VSGXZ1
Power Supply	208-240V 50/60Hz, Single phase
Power Consumption (W)	4.5
Dimensions (H × W × D) (mm)	67 × 288 × 211
Weight (g)	1,500

Network Converter for single split

UTY-VTGX / UTY-VTGXV



UTY-VTGX
DC power supply type



UTY-VTGXV
AC power supply type

Max. Controllable
16
single indoor units


Max. Controllable
100
Network Convertors

Features


- The network converters are required when connecting single split system to VRF network system.
- Compact and light weight design
- Connectable to both types of 2-wire and 3-wire remote controllers

Installation example.


- 2 types of 1 remote controller type and 2 remote controllers type are available.
- Power supply (AC220-240V, 50/60Hz) is required for 2 remote controllers type.



- 2-wire and 3-wire type of the wired remote controller can be connectable.



- A central control can be provided for the single split systems. (Up to 100 units of Network Converter is connectable in one VRF network system)




Specifications

Model name	UTY-VTGX		UTY-VTGXV
Power Supply	polar 3-wire DC12V	non-polar 2-wire DC12V	50/60Hz AC220/240V
Input power (W)	Max. 1.2		Max. 3
Dimensions (H × W × D) (mm)	43 × 117 × 140		54 × 260 × 150
Weight (g)	250		1,100

Network Converter for Group Remote Controller

UTY-VGGXZ1




Features

- This network converter is required when connecting Group Remote Controller to VRF network system.

Installation example

- 4 Group Remote Controllers can be connected to a single network converter.
- 2 refrigerant circuits can be covered by a single network converter.
- Up to a total of 16 network converters and central remote controller adaptors can be connected in a single VRF network system.



Max. Controllable
16
Network
Converter units

Max. Controllable
4
Group Remote
Controllers

Specifications

Model name	UTY-VGGXZ1
Power Supply	208-240V 50/60Hz, Single phase
Power Consumption (W)	6.5
Dimensions (H × W × D) (mm)	67 × 288 × 211
Weight (g)	1,500

Service Tool

UTY-ASGX Software



Max. Monitor and control
100
outdoor units


Max. Monitor and control
400
indoor units

Features

Extensive monitoring and analysis functions for installation and maintenance


- Operation status can be checked and analyzed to detect even the smallest abnormalities
- Storage of data on system operation status on a PC allows access even from off site.
- Up to 400 indoor units (a single VRF network system) can be controlled and monitored for large scale buildings or hotels
- This software can be connected to any point of transmission line with USB adaptor (locally purchased)

Wiring connection



Functions

•Equipment Detail (Diagram)



- Equipment Detail (List)
- Error History
- Remote File Download
- System List
- Commissioning Tool

Personal computer system requirements

	UTY-ASGX
Operating system	• Microsoft® Windows Vista® Home Premium (32-bit) SP2, Windows Vista® Business (32-bit) SP2 • Microsoft® Windows® 7 Professional (32-bit or 64-bit) SP1 • Microsoft® Windows® 8 Pro (32-bit or 64-bit) • Microsoft® Windows® 8.1 Pro (32-bit or 64-bit)
CPU	1 GHz or higher
Memory	• 1 GB or more (for Windows Vista®, Windows® 7 [32-bit], Windows® 8 [32-bit], and Windows® 8.1 [32-bit]) • 2 GB or more (for Windows® 7 [64-bit], Windows® 8 [64-bit], and Windows® 8.1 [64-bit])
HDD	10 GB or more of free space
Display	1024 x 768 or higher resolution
Interface	• 2 USB ports - 1 USB port is required for WibuKey connection - 1 USB port is required for Echelon® U10 USB Network Interface
Software	Internet Explorer® 8, 9, 10 or 11 / Adobe® Reader® 9.0 or later
Optical drive	DVD-ROM drive

<Packing list>

Name and shape	Quantity	Application
DVD-ROM	1	Includes the software and manuals
WibuKey (Software protection key)	1	Software protection key to be connected to USB port on the Service Tool-installed PC. These products runs only on a PC with WibuKey.

- Personal computer that satisfies the following system requirements
- Echelon® U10 USB Network Interface – TP/FT-10 Channel (Model number: 75010R) (Required for each VRF Network.)

Web Monitoring Tool

UTY-AMGX Software

VRF network system
can be supported

4

Max. Monitor and control
400
outdoor units

1,600
indoor units
can be supported


Features

Product features

- Troubleshooting is performed by monitoring each air conditioning unit remotely during periodical system checks.
- Error notification can be automatically transmitted to several locations using the internet*1.
- Requires either a dedicated internet connection or public telephone line.
- Determination of an error occurrence can be made through error warnings and equipment status information obtained from a remote location.
- The monitoring data in a remote side can be optionally downloaded. And, this data can be displayed in offline mode of the service tool.
- Monitoring side computer is not required to install special software, requires only general web browser.


*1: Use of internet mail system required.

Web Monitoring System



Support 4 VRF network systems

USB adaptor (max. 4 adaptors per PC) permit, monitoring of up to 1,600 indoor units. Suitable for large-scale buildings or hotels.



Personal computer system requirements

	UTY-AMGX
Operating system	• Microsoft® Windows Vista® Home Premium (32-bit) SP2, Windows Vista® Business (32-bit) SP2 • Microsoft® Windows® 7 Professional (32-bit or 64-bit) SP1 • Microsoft® Windows® 8 Pro (32-bit or 64-bit) • Microsoft® Windows® 8.1 Pro (32-bit or 64-bit)
CPU	1 GHz or higher
Memory	• 1 GB or more (for Windows Vista®, Windows® 7 [32-bit], Windows® 8 [32-bit], and Windows® 8.1 [32-bit]) • 2 GB or more (for Windows® 7 [64-bit], Windows® 8 [64-bit], and Windows® 8.1 [64-bit])
HDD	40 GB or more of free space
Display	1024 x 768 or higher resolution
Interface	• Ethernet port (for getting access to the Internet using LAN) or Modem (for getting access to the Internet using Public Telephone Line) • USB ports (Maximum of 5 ports) - 1 USB port is required for WibuKey connection - Maximum of 4 USB ports are required for Echelon® U10 USB Network Interface * Maximum number of required USB ports depends on the applicable system configurations.
Software	Internet Explorer® 8, 9, 10 or 11 / Adobe® Reader® 9.0 or later
Optical drive	DVD-ROM drive

<Packing list>

Name and shape	Quantity	Application
DVD-ROM	1	Includes the software and manuals
WibuKey (Software protection key)	1	Software protection key to be connected to USB port on the Service Tool-installed PC. These products runs only on a PC with WibuKey.














- Personal computer that satisfies the following system requirements
- Echelon® U10 USB Network Interface – TP/FT-10 Channel (Model number: 75010R) (Required for each VRF Network.)

VENTILATION



Effective heat exchange and simultaneous fresh air ventilation

High Efficiency and low noise levels are achieved by using a highly efficient heat exchange process. A comfortable air conditioned space is achieved by conveniently selecting whether to use heat exchange or normal ventilation setting, according to the requirements of the conditioned space.

Airflow rate (m³/h)	250	350	500	800	1000	1500	2000			
Energy Recovery Ventilator Page 202	 UTZ-BD025B	 UTZ-BD035B	 UTZ-BD050B	 UTZ-BD080B	 UTZ-BD100B					
Outdoor Air Unit Page 204					 ARXH054GTAH	 ARXH072GTAH	 ARXH096GTAH			
Connectable Capacity class (kW)	5.0	6.3	8.0	10.0	12.5	14.0	20.0	25.0	40.0	50.0
DX-Kit for air handling applications Page 206	 EEV unit UTP-VX30A Control unit UTY-VDGX		 EEV unit UTP-VX60A Control unit UTY-VDGX		 EEV unit UTP-VX90A Control unit UTY-VDGX		 EEV unit UTP-VX90A Control unit UTY-VDGX		 EEV unit UTP-VX90A × 2 Control unit UTY-VDGX	


- 202 Energy Recovery Ventilator
- 204 Outdoor Air Unit
- 206 DX-Kit for air handling applications

Energy Recovery Ventilator

Energy recovery ventilator unit offers maximum comfort and greater energy savings.

Features

Adopts a highly efficient counter-flow heat exchange element



Heat exchange ventilation and normal ventilation

Heat exchange ventilation
When a room is cooled or heated, the exhausted cooling / heating energy is recovered by heat-exchange ventilation.


Normal ventilation
The operation is used during periods when the room space requires no cooling or heating effect, i.e. when there is minimal temperature difference between the indoor and outdoor environments.

Energy efficiency and ecology

Energy consumption is dramatically reduced by using a counter-flow heat-exchange element. Air conditioning load is reduced by approximately 20%, resulting in significant energy savings. Recovers up to 77% of the heat in the outgoing air.

Features of heat exchange element

With the cross-flow element, air moves in a straight line across the element. With the counter-flow element, air flows through the element for a longer time (longer distance), so the heat-exchange effect remains unchanged.



Quiet operation

Significantly reducing low pressure loss and noise allows low-noise operation.

Extended range of an external static pressure

An external static pressure is improved by adopting a powerful fan motor. This allows for application in a wide variety building.


Slim shape and easier installation

Counter-flow heat exchange element used for reduced noise and slimmer, more compact body shape.



Reverse mountable direct air supply / exhaust system

Adoption of straight air supply / exhaust system: Duct design is simplified because the air supply / exhaust ducts are straight. Since each unit can be mounted in reverse position, only one inspection hole is needed for two units: Two units can share one inspection hole so duct work is easier and more flexible.



Model : UTZ-BD025B / UTZ-BD035B / UTZ-BD050B / UTZ-BD080B / UTZ-BD100B




Specifications

Rated flow rate				250 m³/h	350 m³/h	500 m³/h	800 m³/h	1000 m³/h
Model No.				UTZ-BD025B	UTZ-BD035B	UTZ-BD050B	UTZ-BD080B	UTZ-BD100B
Power source				220 - 240V, 50Hz				
Heat Exchange Ventilation	Input power	(Extra high)/High/Low	W	128 / 123 / 96	190 / 185 / 168	289 / 225 / 185	418 / 378 / 295	464 / 432 / 311
	Air flow rate	(Extra high)/High/Low	m³/h	250 / 250 / 190	350 / 350 / 240	500 / 500 / 440	800 / 800 / 630	1000 / 1000 / 700
	External static pressure	(Extra high)/High/Low	Pa	105 / 95 / 45	140 / 60 / 45	120 / 60 / 35	140 / 110 / 55	105 / 80 / 75
	Temperature Exchange Efficiency	(Extra high)/High/Low	%	75 / 75 / 77	75 / 75 / 78	75 / 75 / 76	75 / 75 / 76	75 / 75 / 79
	Energy Exchange Efficiency Cooling	(Extra high)/High/Low	%	63 / 63 / 65	66 / 66 / 71	62 / 62 / 64	65 / 65 / 68	65 / 65 / 70
	Energy Exchange Efficiency Heat pump	(Extra high)/High/Low	%	70 / 70 / 72	69 / 69 / 73	67 / 67 / 69	71 / 71 / 74	71 / 71 / 76
	Sound pressure level	(Extra high)/High/Low	dB*	31.5 / 30.5 / 26.5	33 / 31 / 25.5	37.5 / 35.5 / 32.5	37.5 / 37 / 34.5	38.5 / 37.5 / 34.5
Normal Ventilation	Input power	(Extra high)/High/Low	W	128 / 123 / 96	190 / 185 / 168	289 / 225 / 185	418 / 378 / 295	464 / 432 / 311
	Air flow rate	(Extra high)/High/Low	m³/h	250 / 250 / 190	350 / 350 / 240	500 / 500 / 440	800 / 800 / 630	1000 / 1000 / 700
	External static pressure	(Extra high)/High/Low	Pa	105 / 95 / 45	140 / 60 / 45	120 / 60 / 35	140 / 110 / 55	105 / 80 / 75
	Sound pressure level	(Extra high)/High/Low	dB*	31.5 / 30.5 / 26.5	33 / 31 / 25.5	38.5 / 38 / 32.5	37.5 / 37 / 34.5	40.5 / 39.5 / 36.5
Dimensions		W×D×H	mm	882 x 599 x 270	1050 x 804 x 317	1090 x 904 x 317	1322 x 884 x 388	1322 x 1134 x 388
Weight			kg	29	49	57	71	83
Outlet duct diameter			mm	150	150	200	250	250
Operation range			°C	-10 to 40	-10 to 40	-10 to 40	-10 to 40	-10 to 40
Maximum humidity			%	85	85	85	85	85

* The noise level must be measured 1.5 m below the centre of the unit.

Dimensions

(Unit : mm)



	UTZ-BD025B	UTZ-BD035B	UTZ-BD050B	UTZ-BD080B	UTZ-BD100B
A	810	978	1018	1250	1250
B	599	804	904	884	1134
C	315	580	640	428	678
D	142	112	132	228	228
E	600	600	600	600	600
F	655	860	960	940	1190
G	19	19	19	19	19
H	270	317	317	388	388
I	135	159	159	194	194
J	159	182	182	218	218
K	882	1050	1090	1322	1322
L	414	470	470	612	612
M	95	70	127	85	85
N	219	162	210	258	258
O	144	144	194	242	242

Outdoor Air Unit



The heat pump method efficiently processes the outdoor air for cooling and heating and supplies 100% fresh air into a room.

Features

One VRF system can provide air conditioning and air supply at the same time.

Outdoor Air Unit can be connected in a same VRF*1 system as one of indoor unit series and can create fresh and comfortable air supply together from our high advanced technology.


*1. Connectable VRF series: J-IIS, J-II, V-II, VR-IIIn J-II series alone, OAU is prohibit to connect under the ambient temperature of 40°C or higher.



* Make sure the connected capacity is within the range of 50% to 100% of the outdoor unit capacity. In addition, if there are mixed connections with indoor units, make the Outdoor Air Unit connection capacity 30% or less of the outdoor unit capacity.


High energy savings and flexible duct design by using DC motor

- Greatly reduces electricity consumption by adopting permanent magnet compared to when using an AC motor.
- Compared with AC motor, changing the speed makes it possible to respond flexibly to the external static pressure from 50 Pa to 240 Pa. Even if damper equipment is not used, static pressure can be adjusted and duct design is easy.
- Static pressure can be set easily using wired remote controller.



Top class compact design

- Top class lightweight compact design at just 425 mm in height, 55 kg in weight for ARXH072 type. This unit can be installed easily even at narrow space.



Various Controller

Supplied variety of controllers as options, such as individual controller, central controller, and building management controller.

Individual Controller



Central Controller



* The temperature setting is discharged air temperature setting. The air volume is set to a constant speed.

Model : ARXH054GTAH / ARXH072GTAH / ARXH096GTAH **Production by order**



ARXH054GTAH



ARXH072GTAH



ARXH096GTAH

Specifications

Model name			ARXH054GTAH	ARXH072GTAH	ARXH096GTAH
Power source		V/Ø/Hz	230/1/50	230/1/50	230/1/50
Capacity	Cooling	kW	14.0	22.4	28.0
	Heating		8.9	13.9	17.4
Input Power	Cooling/Heating	W	179	292	370
Airflow Rate		m³/h	1,080	1,680	2,100
Static Pressure	Standard (range)	Pa	185 (50-185)	200 (50-200)	200 (50-240)
Sound Pressure Level		dB (A)	42	44	47
Dimensions (H x W x D)		mm	425×1,367×572	425×1,367×572	450×1,583×700
Weight		kg	48	55	71
Connection Pipe Diameter	(Small / Large)	mm	Ø9.52/Ø19.05	Ø12.70/Ø22.22	Ø12.70/Ø22.22
Operation Range	Cooling	°CDB	5 to 43	5 to 43	5 to 43
	Heating		-7 to 21	-7 to 21	-7 to 21
Refrigerant			R410A	R410A	R410A

Note : Specifications are based on the following conditions.


Cooling : Outdoor temperature of 33°CDB / 28°CWB.
Heating : Outdoor temperature of 0°CDB / -2.9°CWB.

Pipe length : 7.5 m Voltage : 230 [V].


Dimensions

(Unit : mm)


ARXH054GTAH



ARXH072GTAH



ARXH096GTAH




DX-Kit For Air Handling Applications


These kits enable other manufacturers air handling units (AHU) and fan coil units (FCU) to be incorporated into a Fujitsu VRF system or, be connected to a dedicated Fujitsu VRF outdoor unit as a 1:1 system to control outside air ventilation (AHU) or room temperature (FCU).

Features

Multiple temperature sensors optimally control the air handling unit and fan coil unit.




When connecting to an air handling unit, the supply air temperature is controlled by the discharge sensor.




When connecting to a fan coil unit, the room temperature is controlled by the return air temperature sensor.

Arrangement as part of a VRF system




Supports a wide range of capacity classes

- 2 EEV units can be connected in parallel and up to 20 HP (50 kW) large capacity units. (Separation Tube of UTP-LX180A is required.)
- Connectable capacity range: 5 kW to 50 kW




A variety of controls to match the application

Central control using our VRF controllers or central management controllers



Central control from external controllers



Functions Summary

Inputs

- ON/OFF
- Setting temperature
- Capacity demand
- Heating / Cooling operation mode
- Fault information

Outputs

- ON/OFF indication
- Fan ON/OFF indication
- Thermo ON/OFF indication
- Defrost indication
- Fault indication

MODBUS® Control

Possible to control via a MODBUS enabled BMS by using optional interface.

For 2EEV units connection (option) Separation Tube: UTP-LX180A




Installation Limitation

- Connectable VRF series: J-IIS, J-II, V-II, VR-II
- Connectable DX-Kit system capacity range: 50 to 100% of the outdoor unit capacity
- Connectable DX-Kit system capacity range with indoor units: 30% or less of the outdoor unit capacity
- Max. wiring length from control unit: 10 m
- Max. piping length between EEV unit and indoor unit: 5 m
- Outdoor installation: Control unit (IP54 class) and EEV unit can be installed at an outdoor space.


Connectable capacity

• Single connection



50% - 100% of outdoor unit capacity


• Mixed connection




Within 30% of total capacity

50% - 100% of outdoor unit capacity

Piping and wiring length



Control unit: UTY-VDGX EEV unit: UTP-VX30A / UTP-VX60A / UTP-VX90A



Specifications


Connectable Capacity class			5.0 kW	6.3 kW	8.0 kW	10.0 kW	12.5 kW	14.0 kW	20.0 kW	25.0 kW	40.0 kW	50.0 kW
Capacity	Cooling	kW	5.6	6.3	8.0	10.0	12.5	14.0	22.4	25.0	40.0	50.4
	Heating		6.3	7.1	9.0	11.2	14.0	16.0	25.0	28.0	45.0	56.5
Control unit			UTY-VDGX									
Power source		V/Ø/Hz	230/1/50									
Dimensions (H × W × D)		mm	400 × 400 × 120									
EEV unit			UTP-VX30A			UTP-VX60A			UTP-VX90A		UTP-VX90A×2	
Connection pipe diameter (Liquid)		mm	Ø9.53			Ø12.7			Ø12.7		Ø12.7	
Dimensions (H × W × D)			160 × 220 × 90									

Note: Specifications are based on the following conditions.
Cooling: Indoor temperature of 27°CDB / 19°CWB, and outdoor temperature of 35°CDB / 24°CWB.
Heating: Indoor temperature of 20°CDB / (15°CWB), and outdoor temperature of 7°CDB / 6°CWB.
Pipe length: 7.5 m Voltage : 230 [V].

OPTIONAL PARTS FOR VRF

Connection Units


Separation Tube



Gas Pipe

Liquid Pipe


UTP-AX054A



Gas Pipe

Liquid Pipe


UTP-AX090A



Gas Pipe

Liquid Pipe


UTP-AX180A



Gas Pipe

Liquid Pipe

UTP-AX567A




Suction Gas Pipe

Discharge Gas Pipe

Liquid Pipe

UTP-BX090A




Suction Gas Pipe

Discharge Gas Pipe

Liquid Pipe

UTP-BX180A




Suction Gas Pipe

Discharge Gas Pipe

Liquid Pipe


UTP-BX567A

For DX-Kit



UTP-LX180A


Header



Gas Pipe

Liquid Pipe


UTR-H0906L / UTR-H1806L



Gas Pipe

Liquid Pipe


UTR-H0908L / UTR-H1808L



Gas Pipe

Liquid Pipe

UTP-CX567A




Suction Gas Pipe

Discharge Gas Pipe

Liquid Pipe

UTR-J0906A / UTR-J1806A




Suction Gas Pipe

Discharge Gas Pipe

Liquid Pipe

UTP-J0908A / UTP-J1808A



Suction Gas Pipe


Discharge Gas Pipe

Liquid Pipe

UTP-DX567A

EV Kit


For Compact Wall Mounted type



Model code ≦ 09 : UTR-EV09XB
Model code ≧ 12 : UTR-EV14XB


RB Unit

Single type



UTP-RX01AH / UTP-RX01BH / UTP-RX01CH

Multi type



UTP-RX04BH

Specifications

Separation Tube				
Model name	UTP-AX054A	UTP-AX090A	UTP-AX180A	UTP-AX567A
Total cooling capacity of indoor unit (kW)	19.6 or less	28.0 or less	28.1 to 56.0	56.1 or more
Model name	UTP-BX090A		UTP-BX180A	UTP-BX567A
Total cooling capacity of indoor unit (kW)	28.0 or less		28.1 to 56.0	56.1 or more

Header

Model name	3-6 Branches	UTR-H0906L	UTR-H1806L
	3-8 Branches	UTR-H0908L	UTR-H1808L
Total cooling capacity of indoor unit (kW)		28.0 or less	28.1 to 56.0
Model name	3-6 Branches	UTP-J0906A	UTP-J1806A
	3-8 Branches	UTP-J0908A	UTP-J1808A
Total cooling capacity of indoor unit (kW)		28.0 or less	28.1 to 56.0

Outdoor unit Branch kit

Model name	UTP-CX567A (for V-II/V-III)		UTP-DX567A (for VR-II)
Number of outdoor unit	2 outdoor units	1	
	3 outdoor units	2	

EV Kit








Model name	UTR-EV09XB	UTR-EV14XB
Application model	ASYE04GACH ASYE07GACH ASYE09GACH	ASYE12GACH ASYE14GACH

RB Unit






Type		Single type			Multi type
Model name		UTP-RX01AH	UTP-RX01BH	UTP-RX01CH	UTP-RX04BH
Power source	V/Ø/Hz	230/ 1 / 50			
Input power	W	17	24	31	96
Number of branches		1	1	1	4
Maximum capacity of connectable indoor units (Q)	kW	Q ≧ 8.0	Q ≦ 18.0	Q ≦ 28.0	Q ≦ 56.1*1
Maximum capacity of connectable indoor units per branch (Q)	kW	Q ≧ 8.0	Q ≦ 18.0	Q ≦ 28.0	Q ≦ 18.0
Maximum number of connectable indoor units per branch		3	8	8	8
Dimensions (H×W×D)	mm	198×298×268			260×658×428

*1: In case of two RB units connected in series (total 8-branches), maximum capacity of connectable indoor units is up to 56.0 kW.















Controllers

For Individual Control		
<div>Wired Remote Controller (Touch Panel) UTY-RNRYZ1 NEW</div> <div></div>	<div>Wired Remote Controller UTY-RLRY</div> <div></div>	<div>Simple Remote Controller UTY-RSKY With operation mode</div> <div></div>
<div>Simple Remote Controller UTY-RHKY Without operation mode</div> <div></div>	<div>Wireless Remote Controller UTY-LNHY</div> <div></div>	<div>IR Receiver Unit UTB-YWC For All Duct types except Large Airflow Duct</div> <div></div>
<div>IR Receiver Unit UTY-LRHBY1 For Cassette type</div> <div></div>		

For Centralized Control

<div>Group Remote Controller UTY-CGGY</div> <div></div>	<div>Central Remote Controller UTY-DCGY</div> <div></div>	<div>Touch Panel Controller UTY-DTGYZ1 NEW</div> <div><div>Option UTY-PTGXA</div><div></div></div>
<div>System Controller Lite Software UTY-ALGX</div> <div><div>Option UTY-PLGXA1 UTY-PLGXR1 UTY-PLGXE1</div><div></div></div>	<div>System Controller Software UTY-APGX</div> <div><div>Option UTY-PEGX</div><div></div></div>	

Convertors / Adaptors

For External device		
<div>BACnet® Gateway Software UTY-ABGX</div> <div><div></div><div></div></div> <div>DVD-ROM (Software)</div> <div>Software Protection Key</div>	<div>Network Converter for LONWORKS® UTY-VLGX</div> <div></div>	<div>MODBUS® Converter for VRF UTY-VMGX NEW</div> <div></div>
<div>MODBUS® Interface FJ-RC-MBS-1</div> <div></div>	<div>KNX® Interface FJ-RC-KNX-1i</div> <div></div>	<div>Wireless LAN Interface FJ-RC-WIFI-1</div> <div></div>
For System expansion		
<div>Network Converter for single split UTY-VTGX NEW</div> <div></div>	<div>Network Converter for single split UTY-VTGXV NEW AC power supply type</div> <div></div>	<div>Network Converter for Group Remote Controller UTY-VGGXZ1</div> <div></div>
<div>Signal Amplifier UTY-VSGXZ1</div> <div></div>	<div>External Switch Controller UTY-TEKX</div> <div></div>	
Panels		
For Cassette type		
<div>Cassette Grille UTG-UFYC-W For Compact Cassette type</div> <div></div>	<div>Cassette Grille UTG-UGYA-W For Cassette type</div> <div></div>	

Others

Communication system: External Connect Kit					
For Indoor unit			For Outdoor unit		
UTY-XWZXZ7		UTY-XWZXZD		UTY-XWZXZ6	
UTY-XWZXZB		UTY-XWZXZE		UTY-XWZXZ9	
UTY-XWZXZC				UTY-XWZXZF	
For RB unit		For Central Remote Controller		For Touch Panel Controller	
UTY-XWZXZ6		UTY-XWZXZ7		UTY-XWZXZA	
UTY-XWZXZB		UTY-XWZXZ8			
		UTY-XWZXZA			

Function list

	Indoor unit	Outdoor unit	Controller		Other
			Central Remote Controller	Touch Panel Controller	RB Unit
Input	Operation / Stop	●UTY-XWZXZD ○UTY-XWZXZB	—	—	—
	All On / All Off	—	●UTY-XWZXZ7 ○UTY-XWZXZB	●*3 ○*3	—
	Batch Stop	—	●UTY-XWZXZ6	—	—
	Forced Stop	●UTY-XWZXZD ○UTY-XWZXZB	—	—	—
	Emergency Stop	●UTY-XWZXZD ○UTY-XWZXZB	●UTY-XWZXZ7 ○UTY-XWZXZB	●*3 ○*3	—
	Forced Thermostat off	●UTY-XWZXZE ○UTY-XWZXZ7	—	—	—
	Low Noise Mode Operation	—	●UTY-XWZXZ6	—	—
	Cooling / Heating Priority	—	●UTY-XWZXZ6*1	—	●UTY-XWZXZ6 ○UTY-XWZXZB
	"Outdoor Unit Operation Peak Control"	—	●UTY-XWZXZ6	—	—
	"Power Usage Information from Electricity Meter"	—	●UTY-XWZXZF	●*3 ○*3	—
Output	Operation Status	●UTY-XWZXZC	○UTY-XWZXZ6	○UTY-XWZXZA	○UTY-XWZXZA
	Error Status	●UTY-XWZXZC	○UTY-XWZXZ6	○UTY-XWZXZA	○UTY-XWZXZA
	Indoor Unit Fun Operation Status	●UTY-XWZXZC	—	—	—
	Auxiliary Heater Output	●UTY-XWZXZC*2	—	—	—
	Base Heater	—	●UTY-XWZXZ9	—	—

*1. Heat Pump type only
*2. Duct type only
*3. Touch Panel Controller has these functions for Dry contact and Apply voltage, however, above External Connect Kit is not necessary because Touch Panel Controller has an external input terminal block.

●: Dry Contact ○: Apply Voltage

For Duct type			
Flange (Round) UTD-RF204 For Medium Static Pressure Duct type / Ceiling type		Flange (Square) UTD-SF045T For Medium Static Pressure Duct type	 Remote Sensor Unit UTY-XSZX For All Duct type New amenity space can be offered by installing the Remote sensor.
Long-Life Filter UTD-LF25NA For Medium Static Pressure Duct type		Auto Louver Grille Kit UTD-GXTA-W (for ARXD04/07/09/12/14GALH) (for ARXK07/09/12/14GCLH) UTD-GXTB-W (for ARXD18GALH) (for ARXK18GCLH) UTD-GXTC-W (for ARXD24GALH) (for ARXK24GCLH) For Slim Duct type / Mini Duct type	 Drain Pump Unit UTZ-PX1BBA For Low Static Pressure Duct type UTZ-PX1NBA For Medium Static Pressure Duct type
Wide Panel UTG-AKXA-W For Cassette type		Panel Spacer UTG-BKXA-W For Cassette type	 Insulation Kit for High Humidity UTZ-KXRA For Cassette type UTZ-KXGC For Compact Cassette type
Fresh Air Intake Kit UTZ-VXAA For Compact Cassette type		Air Outlet Shutter Plate UTR-YDZB For Compact Cassette type Shuts the air outlet when only using as 3 blow out.	 Air Outlet Shutter Plate UTR-YDZK For Cassette type Shuts the air outlet when only using as 3 blow out.
For Ceiling type			
Drain Pump Unit UTR-DPB24T For Ceiling type			

AIR TO WATER



WATERSTAGE™ makes an Economical and Clean hot water heating system by Heat Pump



















Complete Solution meets various needs

The clean energy produced by WATERSTAGE™ reliably delivers “comfort” to all spaces in the home up to the living room, bedrooms, bath, and swimming pool.

WATERSTAGE™

- 216 All Type Lineup
- 218 Split Type
- 218 Split DHW Integrated Type
- 220 Monobloc Type
- 221 Smart & Comfort Control
- 222 Case Studies
- 224 Optional Parts
- 226 Installation Limitations
- 227 Specifications & Dimensions

All Type Lineup

Capacity (kW)	5	6	8	10	11	14	16
Split	High Power series Single phase Page 218 Hydraulic Indoor Unit / Outdoor Unit				 WSYG140DG6 / WOYG112LCTA	 WSYG140DG6 / WOYG140LCTA	
	High Power series 3 phase Page 218 Hydraulic Indoor Unit / Outdoor Unit				 WSYK160DG9 / WOYK112LCTA	 WSYK160DG9 / WOYK140LCTA	 WSYK160DG9 / WOYK160LCTA
	Comfort series Page 218 Hydraulic Indoor Unit / Outdoor Unit	 WSYA050DG6 / WOYA060LFCA	 WSYA100DG6 / WOYA060LFCA	 WSYA100DG6 / WOYA080LFCA	 WSYA100DG6 / WOYA100LFTA		
Split DHW integrated	High Power series Single phase Page 218 Hydraulic Indoor Unit / Outdoor Unit				 WGYG140DG6 / WOYG112LCTA	 WGYG140DG6 / WOYG140LCTA	
	High Power series 3 phase Page 218 Hydraulic Indoor Unit / Outdoor Unit				 WGYK160DG9 / WOYK112LCTA	 WGYK160DG9 / WOYK140LCTA	 WGYK160DG9 / WOYK160LCTA
	Comfort series Page 218 Hydraulic Indoor Unit / Outdoor Unit	 WGYA050DG6 / WOYA060LFCA	 WGYA100DG6 / WOYA060LFCA	 WGYA100DG6 / WOYA080LFCA	 WGYA100DG6 / WOYA100LFTA		
Monobloc	Compact series with hydraulic unit Page 220 Hydraulic Indoor Unit / Outdoor Unit	 WSYP100DG6 / WPYA050LG		 WSYP100DG6 / WPYA080LG	 WSYP100DG6 / WPYA100LG		

EHPA Quality label



Fujitsu General's WATERSTAGE* have obtained the EHPA Quality Label** by tests according to the international Standards EN14511 and EN17025. The EHPA Quality Label** is a label that shows the end-consumer a quality heat pump unit on the market.
*: High Power split model
**: Check the validity of label at www.ehpa.org/QL



SG-Ready Label



SG-Ready is a defined standard by BWP***, which makes it possible that the device can be integrated into a smart grid. Heat pumps, which are equipped with the SG-Ready Label, can receive signals from the power grid (and e.g. also from PV systems) about the available (unused renewable) energy (from wind, sun & water). Fujitsu General provides the SG-Ready compatibility to all new Heat Pumps series.
***BWP: the Federal German Heat Pump Association

What's a Heat Pump ?

Absorbing free energy from the atmosphere. Heat pump system requires only 1 kW of electricity to generate 3 to 5 kW thermal energy.



Split Type High power Series/Comfort series



High power series


Hydraulic indoor unit: WSYG140DG6/[3phase] WSYK160DG9
Outdoor unit: WOYG112LCTA/WOYG140LCTA
[3phase] WOYK112LCTA/WOYK140LCTA/WOYK160LCTA

Comfort series

Hydraulic indoor unit: WSYA050DG6/WSYA100DG6
Outdoor unit: WOYA060LFCA/WOYA080LFCA/WOYA100LFTA



Split DHW Integrated Type High power Series/Comfort series




High power series

Hydraulic indoor unit: WGYG140DG6/[3phase] WGYK160DG9
Outdoor unit: WOYG112LCTA/WOYG140LCTA
[3phase] WOYK112LCTA/WOYK140LCTA/WOYK160LCTA

Comfort series

Hydraulic indoor unit: WGYA050DG6/WGYA100DG6
Outdoor unit: WOYA060LFCA/WOYA080LFCA/WOYA100LFTA




Features

High leaving water temperature


High power series: High leaving water temperature of 60°C is kept even when outdoor temperature is down to -20°C without using backup heaters.

At -20°C outdoor temperature: 60°C Hot water



Comfort series: Maximum leaving water temperature is 55°C without backup heater. Hot water supply temperature can be maintained even at -10°C outdoor temperature.


At -10°C outdoor temperature: 55°C Hot water



* If you want to raise the hot water supply temperature, backup heaters can be used for auxiliary operation.

High COP


Air to water heat pumps work with much more efficiency and save more energy than a traditional heating system.



2 Zone individual control*


2 Zone individual control (2 under floor heating zones or under floor heating + radiator zone, etc.)*

*: Optional parts are required.




Automatic heating curve control

Automatic temperature regulation in accordance with heating curve (Depends on heating terminal and outdoor temperature)




High durability

- Corrosion protected
- No flow switch necessary
- Anti-freeze-protection is unnecessary



Emergency operation

System can continuously supply hot water by built in back up heater or boiler, as emergency, even if an error has occurred.



*When additional boiler connected

Monobloc Type Comfort series

Compact series

Hydraulic indoor unit: WSY100DG6


Outdoor unit : WPYA050LG / WPYA080LG / WPYA100LG



Features


High leaving water temperature

High leaving water temperature of 55°C keeps to -20°C outdoor temperature without additional heater.




High COP

High COP is realized by using a DC twin rotary compressor, inverter technology, and high efficient water heat exchanger.



Compact & light weight design



Features of the hydraulic indoor unit

- The compact Indoor unit provides two electrical back up heater, each with 3kW capacity • 12 L expansion vessel included
- No waste of space. DHW Kit installation inside the hydraulic unit possible.
- New generation controller. Connection by MODBUS protocol possible.
- Integrated heat metering (flow sensor included).



Common Features

Smart & Comfort Control



Navigation and setting

- Selecting the heating menu
- Setting program timer

Large LCD panel

- Operation status display
- Error display
- Plain text

Simple operation mode setting


- Selecting the heating mode and Domestic hot water operation

Heating mode

- | | |
|--|--|
| Auto
Automatic mode
Comfort/Reduce mode switching automatically according to outdoor temperature | Comfort mode
Constant comfort temperature |
| Reduce mode
Constant reduce temperature | Protection mode
Stand-by mode with anti-frost protection |

Automatic heating curve operation

Automatic heating curve control based on outdoor temperature and setting room temperature. This can be adjusted when too warm or too cold.




Programmable timer

- The setting of timer operation can easily be adjusted.
- Changing the heating mode linked with time is possible.

Day-Weekly timer setting

- The day-weekly timer can be set up for up to 3 times per day.
- Allows separate settings for each day of the week.


Day-Weekly timer setting



Holiday timer setting

- The holiday timer can be set for up to 8 periods
- If you are absent for a long time in the winter, freezing of room can be prevented.

Holiday timer setting




Auto-changeover

If the cooling operation function is set, the system can automatically switch to cooling or heating, depending on the outdoor temperature to provide all-season comfortable air conditioner.

Remote control-extension


Various remote controls are available on your hands. Remote control is also available via Web. All kinds of life styles are supported.




Case Studies

Split Case studies


2 emitter simultaneous heating (Individual control)
Floor heating + Radiator



3 types of heat distribution
Floor heating + Radiator + Domestic Hot Water




Boiler connected to heating (Boiler + Heating)




Split DHW integrated Case studies


Single heating & Domestic Hot Water
Radiator + Domestic Hot Water



Boiler connected to heating (Boiler + Heating) & Domestic Hot Water
Radiator + Domestic Hot Water




2 emitter simultaneous heating (Individual control) & Domestic Hot Water
Radiator + Domestic Hot Water




Split Cascade System Case studies


2 emitter simultaneous heating (Individual control)




2 emitter simultaneous heating & Domestic Hot Water (type A)



Boiler connected to heating (Boiler + Heating)




2 emitter simultaneous heating & Domestic Hot Water (type B)




Monobloc Case studies


Single heating system
Floor heating



2 types of heat distribution
Floor heating + Domestic Hot Water
















Boiler connected to heating (Boiler + Heating)
Floor heating



Optional Parts

[illegible]

Product Name	Model Name	Split								Split DHW integrated type								Monobloc				
		High Power				Comfort				High Power				Comfort				Compact				
		10		30		10		10		10		30		10		10		10				
		11	14	11	14	16	5	6	8	10	11	14	11	14	16	5	6	8	10	5	8	10
HMI Kit		UTW-KHMXE*3	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Remote Controller	Wired 	UTW-C74TXF*3	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		UTW-C74HXF*3	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Wireless 	UTW-C78XD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
		UTW-C78XD-E*4	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Room Thermostat	Wired 	UTW-C55XA	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Wireless 	UTW-C58XD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Outdoor Sensor Transmitter		UTW-M0SXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
RF Modules	for BSB-Port 	UTW-MRCXD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Web server		UTW-KW1XD UTW-KW4XD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
LPB Clip		UTW-KL1XD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
MODBUS Clip		UTW-KMBXE	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	—*7	●	●	●
Base Heater		UTW-HAMXE	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	●	●	●
		UTW-HAMXF	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	●	—	—
Service Tool (incl.OC1700 adaptor)		UTW-KSTXD	●*5	●*6	●*3	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5	●*5
Service Tool Software		UTW-KPSXD	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6	●*6
External connect kit		UTY-XWZXZ2	●	●	●	●	—	—	—	—	●	●	●	●	●	—	—	—	—	—	—	—


*1: DHW operation is possible without DHW kit and DHW Tank. ● : Available — : Not Available
 *2: Cooling operation is possible without cooling kit
 *3: 19 Languages included, no separate Eastern European RC necessary. C74TXF: Built in Room Temperature sensor C74HXF: Built in Room temperature and Humidity sensor
 *4: Eastern European Language(English, Czech Republic, Slovakia, Poland, Turkey, Hungary, Russia, Slovenia, Greece, Serbia)
 *5: UTW-KL1XD is required for the connection.
 *6: UTW-KW1XD or UTW-KW4XD is required for the connection.
 *7: Additional optional part necessary

Installation Limitations

Equipment Installation


Split type Hydraulic indoor unit

- Hydraulic indoor unit is to be hang on the wall
- Weight < 65 kg (including water)
- Space for maintenance should be respected




Split DHW integrated type Hydraulic indoor unit

- Floor stand
- Weight 366 kg (including water)
- Space for maintenance should be respected.




Monobloc Type Hydraulic indoor unit

- Hydraulic indoor unit is to be hang on the wall
- Weight < 62 kg (including water)
- Distances for maintenance should be respected




Monobloc type Outdoor unit

- Floor stand
- Weight 72 kg (without water): WPYA080LG, WPYA100LG
- 49 kg (without water): WPYA050LG
- Distances for maintenance should be kept



Piping and Wiring


Split type




Series	Capacity range(kW)	H (m)	L (m)
Comfort	5	±20	5-30
	6		
	8		
	10		
High power	11	±15	5-20
	14		
	16		

Electrical wiring


Split type



Split DHW integrated type



Monobloc Type with Hydraulic indoor unit



Specifications & Dimensions


Split type Specifications (High power series)

Model Name	Hydraulic indoor unit		WSYG140DG6		WSYG140DG9		WSYK160DG9		WSYK160DG9		
Capacity range	Outdoor unit		WOYG112LCTA		WOYG140LCTA		WOYK112LCTA		WOYK140LCTA		
7°C/35°C floor heating *1	Heating capacity	kW	11		14		11		14		
	Input power		10.80		13.50		10.80		13.50		
	COP		2.54		3.23		2.51		3.20		
2°C/35°C floor heating *1	Heating capacity	kW	4.25		4.18		4.30		4.22		
	Input power		10.77		12.00		10.77		13.00		
	COP		3.44		3.87		3.40		4.15		
-7°C/35°C floor heating*1	Heating capacity	kW	3.13		3.10		3.17		3.13		
	Input power		10.38		11.54		10.38		12.20		
	COP		4.32		5.08		4.28		5.13		
			2.40		2.27		2.43		2.38		
			2.40		2.27		2.43		2.38		
Space heating characteristics*2											
Temperature application		°C	55	35	55	35	55	35	55	35	
Energy efficiency class			A+	A++	A+	A+	A+	A++	A+	A++	
Rated heat output (P _{rated})		kW	9	11	11	13	9	11	11	13	
Seasonal space heating energy efficiency(η _s)		%	109	151	113	148	112	154	117	150	
Annual energy consumption		kWh	6842	6062	8041	6824	6669	5930	7803	6738	
Sound power level	Hydraulic indoor unit	dB(A)	46		46		46		46		
	Outdoor unit		68		69		69		68		
									70		
									68		
									71		
Hydraulic indoor unit Specification											
Power source			1 Ø 230 V 50 Hz				3 N 400 V 50 Hz				
Dimensions H×W×D		mm	800 × 450 × 457								
Weight (Net)		kg	42								
Water circulation		Min/Max	L/min		19.5/39.0		24.4/48.7		19.5/39.0		
Buffer tank capacity		L			16				24.4/48.7		
Expansion vessel capacity		L			8				27.4/54.8		
Leaving water temperature range		Max	°C		60						
Water pipe connection diameter		Flow/Return	mm		Ø 25.4/Ø 25.4						
Backup heater		Capacity	kW		6.0(3.0kW×2pcs.)				9.0(3.0kW×3pcs.)		
Outdoor unit specification											
Power source			1 Ø 230 V 50 Hz				3 N 400 V 50 Hz				
Current		Max	A		22.0		25.0		8.5		
Dimensions H × W × D		mm	1,290 × 900 × 330				9.5		10.5		
Weight (Net)		kg	92				99				
Refrigerant		Type (Global Warming Potential)	R410A (2.088)								
Charge		kg	2.50								
Additional refrigerant charge amount		g/m	50								
Connection pipe	Diameter	Liquid	Ø 9.52								
		Gas	Ø 15.88								
	Length	Min/Max	5/20								
	Length(Pre-charge)	m	15								
Operation range	Height difference	Max	15								
	Heating	°C	-25 to 35								


*1:The values of heating capacity/input power/COP are based on measurement of EN14511 standard. Usage environment, such as operation of the heating equipment, room temperature, and controller adjustments, may cause disparities between practically determined values and these values.
*2:All information of ErP can be available for downloaded from www.fujitsu-general.com/global/products/erp-ecodesign/index.html.

Split type Dimensions (High power series)


Outdoor Unit :
WOYG112LCTA/WOYG140LCTA



Outdoor Unit :
WOYK112LCTA/WOYK140LCTA/WOYK160LCTA



Hydraulic Indoor Unit :
WSYG140DG6/WSYK160DG9



Split type Specifications (Comfort series)

Model Name			Hydraulic indoor unit		WSYA050DG6		WSYA100DG6		WSYA100DG6		WSYA100DG6								
Capacity range			Outdoor unit		WOYA060LFCA		WOYA060LFCA		WOYA080LFCA		WOYA100LFTA								
7°C/35°C floor heating * ¹			Heating capacity Input power COP		kW		5		6		8								
							4.50		6.00		7.50								
							0.996		1.41		1.84								
2°C/35°C floor heating * ¹			Heating capacity Input power COP		kW		4.52		4.27		4.08								
							4.50		4.95		5.65								
							1.39		1.53		1.78								
7°C/35°C floor heating* ¹			Heating capacity Input power COP		kW		3.24		3.24		3.17								
							4.10		4.60		5.70								
							1.47		1.74		2.23								
Space heating characteristics* ²																			
Temperature application			°C		55	35	55	35	55	35	55	35							
Energy efficiency class					A+	A++	A+	A++	A+	A++	A+	A++							
Rated heat output(P _{rated})			kW		4	4	5	5	6	7	8	8							
Seasonal space heating energy efficiency(η _s)			%		115	169	115	169	118	156	113	155							
Annual energy consumption			kWh		3026	2160	3180	2505	3886	3375	5415	4415							
Sound power level		Hydraulic indoor unit	dB(A)		46		46		46		46								
		Outdoor unit			65	60	65	63	65	69	68	69							
Hydraulic indoor unit Specification																			
Power source					1 Ø 230 V 50 Hz														
Dimensions H×W×D			mm		800 × 450 × 457														
Weight (Net)			kg		42														
Water circulation			Min/Max	L/min	8.1/16.2		10.8/21.7		13.5/27.1		18.1/36.1								
Buffer tank capacity			L		16														
Expansion vessel capacity			L		8														
Leaving water temperature range			Max	°C	55														
Water pipe connection diameter			Flow/Return		Ø 25.4/Ø 25.4														
Backup heater			Capacity		kW 6.0(3.0kW×2pcs.)														
Outdoor unit specification																			
Power source					1 Ø 230 V 50 Hz														
Current			Max	A	11.0		12.5		17.5		18.5								
Dimensions H × W × D			mm		620 × 790 ×290														
Weight (Net)			kg		41				42		90								
Refrigerant			Type (Global Warming Potential)		R410A (2,088)														
			Charge	kg	1.10				1.40		1.80								
Additional refrigerant charge amount			g/m		25						40								
					Ø 6.35						Ø 9.52								
Connection pipe			Diameter	Liquid	Ø 12.7														
			Gas	Ø 15.88															
			Length	Min/Max	m		5/30												
			Length(Pre-charge)	m		15													
			Height difference	m		20													
Operation range			Heating		°C		-20 to 35												

*1:The values of heating capacity/input power/COP are based on measurement of EN14511 standard. Usage environment, such as operation of the heating equipment, room temperature, and controller adjustments, may cause disparities between practically determined values and these values.

*2:All information of ErP can be available for downloaded from www.fujitsu-general.com/global/products/erp-ecodesign/index.html.

Split DHW Integrated type Specifications (High power series)

Model Name			Hydraulic indoor unit		WGYG140DG6		WGYG140DG6		WGYK160DG9		WGYK160DG9		WGYK160DG9		
			Outdoor unit		WOYG112LCTA		WOYG140LCTA		WOYK112LCTA		WOYK140LCTA		WOYK160LCTA		
Capacity range					11		14		11		14		16		
7°C/35°C floor heating * ¹	Heating capacity	kW	10.80		13.50		10.80		13.50		15.17				
	Input power		2.54		3.23		2.51		3.20		3.70				
	COP		4.25		4.18		4.30		4.22		4.10				
2°C/35°C floor heating * ¹	Heating capacity	kW	10.77		12.00		10.77		13.00		13.50				
	Input power		3.44		3.87		3.40		4.15		4.34				
	COP		3.13		3.10		3.17		3.13		3.11				
-7°C/35°C floor heating* ¹	Heating capacity	kW	10.38		11.54		10.38		12.20		13.50				
	Input power		4.32		5.08		4.28		5.13		5.40				
	COP		2.40		2.27		2.43		2.38		2.50				
Space heating characteristics* ²															
Temperature application			°C	55	35	55	35	55	35	55	35	55	35		
Energy efficiency class				A+	A++	A+	A+	A+	A++	A+	A++	A+	A+		
Rated heat output(P _{rated})			kW	9	11	11	13	9	11	11	13	13	14		
Seasonal space heating energy efficiency(η _s)			%	109	151	113	148	112	154	117	150	117	149		
Annual energy consumption			kWh	6842	6062	8041	6824	6669	5930	7803	6738	9062	7408		
Sound power level	Hydraulic indoor unit	dB(A)	46		46		46		46		46		46		
	Outdoor unit		68		69		69		68		70		71		
Domestic hot water characteristics* ²															
Load profile			L												
Energy efficiency class			A												
Energy efficiency(η _{wh})			%	88											
Annual electricity consumption			kWh	1166											
Hydraulic indoor unit Specification															
Power source			1 Ø 230 V 50 Hz						3 N 400 V 50 Hz						
Dimensions H×W×D			mm	1,840× 648 × 698											
Weight (Net)			kg	152											
Water circulation			L/min	19.5/39.0		24.4/28.7		19.5/39.0		24.4/48.7		27.4/54.8			
DHW capacity			L	190											
Hot water heater capacity			kW	1.5											
Expansion vessel capacity			L	12											
Leaving water temperature range			Max °C	60											
Water pipe connection diameter			Flow/Return mm	Ø 25.4/Ø 25.4											
Hot water pipe connection diameter			mm	Ø 19.05											
Backup heater			Capacity mm	6.0(3.0kW×2pcs.)						9.0(3.0kW×3pcs.)					
Outdoor unit specification															
Power source			1 Ø 230 V 50 Hz						3 N 400 V 50 Hz						
Current			Max A	22.0		25.0		8.5		9.5		10.5			
Dimensions H × W × D			mm	1,290 × 900 ×330											
Weight (Net)			kg	92						99					
Refrigerant			Type (Global Warming Potential)	R410A (2,088)											
			Charge kg	2.50											
Additional refrigerant charge amount			g/m	50											
Connection pipe	Diameter	Liquid	mm	Ø 9.52											
		Gas	mm	Ø 15.88											
	Length	Min/Max	m	5/20											
		Length(Pre-charge)	m	15											
Operation range	Height difference	Max	m	15											
		Heating °C	-25 to 35												

Split DHW Integrated type Specifications (Comfort series)


Model Name			Hydraulic indoor unit		WGYA050DG6		WGYA100DG6		WGYA100DG6		WGYA100DG6	
Capacity range			Outdoor unit		WOYA060LFCA		WOYA060LFCA		WOYA080LFCA		WOYA100LFTA	
7°C/35°C floor heating * ¹			Heating capacity		5		6		8		10	
			Input power		4.50		6.00		7.50		10.00	
			COP		0.996		1.41		1.84		2.49	
2°C/35°C floor heating * ¹			Heating capacity		4.52		4.27		4.08		4.02	
			Input power		4.50		4.95		5.65		7.70	
			COP		1.39		1.53		1.78		2.47	
-7°C/35°C floor heating* ¹			Heating capacity		3.24		3.24		3.17		3.12	
			Input power		4.10		4.60		5.70		7.40	
			COP		1.47		1.74		2.23		2.97	
Space heating characteristics** ²					2.79		2.64		2.56		2.49	
Temperature application			°C		55		35		55		35	
Energy efficiency class					A+		A++		A+		A++	
Rated heat output(P _{rated})			kW		4		4		5		7	
Seasonal space heating energy efficiency(η _s)			%		115		169		115		155	
Annual energy consumption			kWh		3026		2160		3180		2505	
Sound power level			Hydraulic indoor unit		46		46		46		46	
			Outdoor unit		65		60		65		63	
Domestic hot water characteristics** ²												
Load profile									L			
Energy efficiency class									A+			
Energy efficiency(η _{wh})			%						120			
Annual electricity consumption			kWh						880			
Hydraulic indoor unit Specification												
Power source									1 Ø 230 V 50 Hz			
Dimensions H×W×D			mm						1,840× 648 × 698			
Weight (Net)			kg						152			
Water circulation			L/min		8.1/16.2		10.8/21.7		13.5/27.1		18.1/36.1	
DHW capacity			L						190			
Hot water heater capacity			kW						1.5			
Expansion vessel capacity			L						12			
Leaving water temperature range			Max		°C				55			
Water pipe connection diameter			Flow/Return		mm				Ø 25.4/Ø 25.4			
Hot water pipe connection diameter					mm				Ø 19.05			
Backup heater			Capacity		mm				6.0(3.0kW×2pcs.)			
Outdoor unit specification												
Power source									1 Ø 230 V 50 Hz			
Current			Max		A		11.0		12.5		17.5	
Dimensions H × W × D			mm				620 × 790 ×290				830 × 900 ×330	
Weight (Net)			kg				41		42		60	
Refrigerant			Type (Global Warming Potential)						R410A (2,088)			
			Charge		kg		1.10		1.40		1.80	
Additional refrigerant charge amount			g/m				25		40		40	
							Ø 6.35				Ø 9.52	
Connection pipe			Diameter		mm							
			Length		m		Ø 12.70		5/30		Ø 15.88	
			Length(Pre-charge)		m				15			
Height difference			Max		m				20			
			Heating		°C				-20 to 35			

*1:The values of heating capacity/input power/COP are based on measurement of EN14511 standard. Usage environment, such as operation of the heating equipment, room temperature, and controller adjustments, may cause disparities between practically determined values and these values.


*2:All information of ErP can be available for downloaded from www.fujitsu-general.com/global/products/erp-ecodesign/index.html.

Split type Dimensions (Comfort series)


Outdoor Unit :
WOYA060LFCA/WOYA080LFCA



Outdoor Unit :
WOYA100LFTA



Hydraulic Indoor Unit :
WGYA050DG6/WGYA100DG6



Monobloc type Specifications

Model Name			Hydraulic indoor unit		WSYP100DG6							
			Outdoor unit		WPYA050LG		WPYA080LG		WPYA100LG			
Capacity range					5		8		10			
7°C/35°C floor heating * ¹	Heating capacity	kW			5.00		8.00		10.00			
	Input power		1.19		1.78		2.30					
	COP		4.20		4.50		4.35					
2°C/35°C floor heating * ¹	Heating capacity	kW			3.65		4.35		4.90			
	Input power		1.07		1.23		1.44					
	COP		3.40		3.55		3.40					
-7°C/35°C floor heating* ¹	Heating capacity	kW			3.55		7.10		8.00			
	Input power		1.38		2.93		3.32					
	COP		2.57		2.42		2.41					
Space heating characteristics* ²												
Temperature application		°C			55		35		55		35	
Energy efficiency class					A+		A++		A+		A++	
Rated heat output(P _{rated})		kW			4		4		6		7	
Seasonal space heating energy efficiency(η _s)		%			118		171		123		168	
Annual energy consumption		kWh			3055		1952		3828		3580	
Sound power level		Outdoor unit	dB (A)		62		61		65		68	
Hydraulic indoor unit Specification												
Power source			1 Ø 230 V 50 Hz									
Dimensions H×W×D			mm		803 × 450 × 457							
Weight (Net)			kg		40							
Buffer tank capacity			L		22							
Expansion vessel capacity			L		12							
Water pipe connection diameter		Flow/Return	mm	Ø 25.4/Ø 25.4								
Backup heater		Capacity	kW	6.0(3.0kW×2pcs.)								
Outdoor unit specification												
Power source			1 Ø 230 V 50 Hz									
Dimensions H × W × D			mm		675 × 825 × 300		882 × 850 × 330					
Weight (Net)			kg		49		72					
Current			Max		A		10.9		15.2		17.5	
Water circulation			Min/Max		L/min		5.0/20.0		10.0/30.0			
Water pipe connection diameter			Flow/Return		mm		Ø 19.05/Ø 19.05		Ø 25.4/Ø 25.4			
Refrigerant			Type (Global Warming Potential)		R410A (2,088)							
			Charge		kg		1.05		1.72			
Leaving water temperature range			Max		°C		55					
Operation range			Heating		°C		-20 to 35					

FUJITSU GENERAL LIMITED

3-3-17, Suenaga, Takatsu-ku, Kawasaki 213-8502, Japan
<http://www.fujitsu-general.com/>



Notice for specifications

I.U.=Indoor Unit O.U.=Outdoor Unit Qu=Quiet *=Not decided yet

- Specifications and design are subject to change without notice for future improvement.
- For further details, please check with our authorised dealer.
- Cooling / Heating capacities are based on the following conditions.


Cooling	Indoor temp. : 27°C DB/19°C WB Outdoor temp.: 35°C DB/24°C WB	Heating	Indoor temp. : 20°C DB Outdoor temp.: 7°C DB/6°C WB
---------	--	---------	--

- Performance test is in accordance with EN14511
- Seasonal efficiency test is on accordance with EN14825
- Sound power test is in accordance with EN12102

- The products or equipments in this catalogue contain fluorinated greenhouse gases.
- **"AIRSTAGE"** and **"WATERSTAGE"** are worldwide trademarks of FUJITSU GENERAL LIMITED and are registered trademarks in Japan and other countries or areas.
- **"nocria"** is a worldwide trademark of FUJITSU GENERAL LIMITED.
- iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries.
- Other company and product names mentioned herein may be registered trademarks, trademarks or trade names of their respective owners.

• Actual products' colors may be different from the colors shown in this printed material.

Distributed by:



ISO 9001 Certified number: 01 100 89394 ISO 14001 Certified number: 01 104 9245/01

Fujitsu General (Shanghai) Co., Ltd.



ISO 9001 Certified number: 01 100 79269



ISO 14001 Certified number: CNB311153-UK

Fujitsu General Central Air-conditioner (Wuxi) Co., Ltd.



ISO 9001 Certified number: 15914Q1006584M ISO 14001 Certified number: 15912E10022R3M